



BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : BlueDEF Diesel Exhaust Fluid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Solution for NOx reduction in SCR systems

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
4065 Commercial Ave.
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

Signal word (GHS-US) : None
Hazard statements (GHS-US) : None
Precautionary statements (GHS-US) : None

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% by wt	GHS-US classification
Water	(CAS No) 7732-18-5	67.5	Not classified
urea	(CAS No) 57-13-6	32.5	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : The EPA has no established reportable quantity for spills for this material, secondary containment is not specified.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Dilute with plenty of water and mop up. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective goggles.



BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless; Clear
Odor	: ammonia odor
Odor threshold	: No data available
pH	: 9 - 10
Relative evaporation rate (butylacetate=1)	: < 1
Freezing point	: -11 °C (12 °F)
Boiling point	: > 100 °C (212 °F)
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: Not Applicable
Relative vapor density at 20 °C	: 0.6 H ₂ O, >1
Specific Gravity	: 1.09
Solubility	: Soluble in water. Water: 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases. oxidizing agents (peroxides, chromates, dichromates).

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

urea (57-13-6)	
LD50 oral rat	8,471 mg/kg (Rat)
LD50 dermal rat	> 3,200 mg/kg (Rat)
LD50 dermal rabbit	> 21,000 mg/kg (Rabbit)
ATE US (oral)	8,471 mg/kg bodyweight
Skin corrosion/irritation	: Not classified pH: 9 - 10
Serious eye damage/irritation	: Not classified pH: 9 - 10
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

urea (57-13-6)	
LC50 fish 1	> 6,810 mg/l (96 h; Leuciscus idus)
EC50 Daphnia 1	> 10,000 mg/l (48 h; Daphnia magna)
LC50 fish 2	17,500 mg/l (96 h; Poecilia reticulata)
EC50 Daphnia 2	> 10,000 mg/l (24 h; Daphnia magna)
TLM fish 1	17,500 ppm (96 h; Poecilia reticulata)
Threshold limit other aquatic organisms 1	120,000 mg/l (16 h; Bacteria; Toxicity test)
Threshold limit other aquatic organisms 2	> 10,000 mg/l (Pseudomonas putida)
Threshold limit algae 2	> 10,000 mg/l (168 h; Scenedesmus quadricauda)

12.2. Persistence and degradability

urea (57-13-6)	
Persistence and degradability	Inherently biodegradable. Hydrolysis in water.
ThOD	0.27 g O ₂ /g substance

12.3. Bioaccumulative potential

urea (57-13-6)	
BCF fish 1	1 (72 h; Brachydanio rerio; Fresh water)
BCF other aquatic organisms 1	11700 (Chlorella sp.)
Log Pow	-2.59 - -1.59
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

12.5. Other adverse effects

Effect on ozone layer	:
Effect on global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. As a non-hazardous liquid waste, it should be solidified with stabilizing agents such as sand, fly ash, or clay absorbent, so that no free liquid remains before disposal to an industrial waste landfill.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

- In accordance with DOT
- Not a dangerous good in sense of transport regulations
- Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

- UN-No. (IMDG) : Not regulated by IMDG (in quantities under 5,000 lbs in any one inner package)

Air transport

- UN-No.(IATA) : Not regulated by IATA (in quantities under 5,000 lbs in any one inner package)

SECTION 15: Regulatory information

15.1. US Federal regulations

BlueDEF Diesel Exhaust Fluid	
EPA TSCA Regulatory Flag	This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA)
RQ (Reportable quantity, section 304 of EPA's List of Lists)	None. This material is not classified as hazardous under U.S. EPA regulations.
SARA Section 302 Threshold Planning Quantity (TPQ)	No extremely hazardous substances are in this product.
SARA Section 311/312 Hazard Classes	Urea. No hazards resulting from the material as supplied.

urea (57-13-6)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

CANADA

BlueDEF Diesel Exhaust Fluid	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

WHMIS Classification

Uncontrolled product
according to WHMIS
classification criteria

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

BlueDEF Diesel Exhaust Fluid	
Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).	

15.3. US State regulations

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 Minimal Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.