

## 2263, 2264, 20126, 3843, 3844 SPECIAL TEC F ECO 5W-20 1L, 5L, 20L, 60L, 205L

Liqui Moly GmbH

Chemwatch Hazard Alert Code: 1

Chemwatch: 48-0455

Version No: 4.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 19/01/2017

Print Date: 19/01/2017

S.GHS.USA.EN

### SECTION 1 IDENTIFICATION

#### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | 2263, 2264, 20126, 3843, 3844 SPECIAL TEC F ECO 5W-20 1L, 5L, 20L, 60L, 205L |
| Synonyms                      | Item No: 2263, 2264, 20126, 3843, 3844                                       |
| Other means of identification | Not Available  |

#### Recommended use of the chemical and restrictions on use

|                          |   |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions.<br>Motor Oil. |
|--------------------------|---|

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

|                         |  |
|-------------------------|--|
| Registered company name | Liqui Moly GmbH                            |
| Address                 | Jerg-Wieland-Strasse 4 Ulm D-89081 Germany |
| Telephone               | +49 731 1420 0                             |
| Fax                     | +49 731 1420 82                            |
| Website                 | Not Available                              |
| Email                   | Not Available                              |

#### Emergency phone number

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Association / Organisation        | INFOTRAC                        |
| Emergency telephone numbers       | +1800 535 5053 (US & Canada)    |
| Other emergency telephone numbers | +1 352 323 3500 (International) |

### SECTION 2 HAZARD(S) IDENTIFICATION

#### Classification of the substance or mixture

##### CHEMWATCH HAZARD RATINGS

|              | Min | Max |
|--------------|-----|-----|
| Flammability | 1   |     |
| Toxicity     | 0   |     |
| Body Contact | 0   |     |
| Reactivity   | 1   |     |
| Chronic      | 0   |     |

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

##### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

|                |                |
|----------------|----------------|
| Classification | Not Applicable |
|----------------|----------------|

#### Label elements

|                    |                |
|--------------------|----------------|
| GHS label elements | Not Applicable |
|--------------------|----------------|

|             |                |
|-------------|----------------|
| SIGNAL WORD | NOT APPLICABLE |
|-------------|----------------|

#### Hazard statement(s)

Not Applicable

#### Hazard(s) not otherwise specified

Not Applicable

#### Precautionary statement(s) Prevention

Not Applicable

#### Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

Not Applicable

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

#### Mixtures

| CAS No      | %[weight] | Name  |
|-------------|-----------|---|
| 72623-87-1. | 10-<30    | <u>lubricating oils, petroleum C20-50, hydrotreated neutral</u> |
| 36878-20-3  | 1-<10     | <u>nonylated diphenylamines</u>                                 |
| 64742-54-7. | 1-<10     | <u>paraffinic distillate, heavy, hydrotreated (severe)</u>      |
|             |           | base oil as   |
| Not avail.  | 1-<10     | <u>mineral oil</u>  |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### SECTION 4 FIRST-AID MEASURES

#### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>  |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>  |

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

### SECTION 5 FIRE-FIGHTING MEASURES

#### Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

#### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

#### Special protective equipment and precautions for fire-fighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>  |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include:</p> <ul style="list-style-type: none"> <li>‘ carbon dioxide (CO<sub>2</sub>)</li> <li>‘ other pyrolysis products typical of burning organic material.</li> </ul> |

Continued...

May emit poisonous fumes.

**CARE:** Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <p>Slippery when spilt.</p> <ul style="list-style-type: none"> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul> |
| <b>Major Spills</b> | <p>Slippery when spilt.<br/>Moderate hazard.</p> <ul style="list-style-type: none"> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> </ul>                             |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<math>\leq 1</math> m/sec until fill pipe submerged to twice its diameter, then <math>\leq 7</math> m/sec).</li> <li>Avoid splash filling.</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>  |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>  |
| <b>Storage incompatibility</b> | <p><b>CARE:</b> Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.</p> <ul style="list-style-type: none"> <li>Avoid reaction with oxidising agents</li> </ul> |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

| Source  | Ingredient   | Material name   | TWA     | STEL          | Peak          | Notes               |
|---|--|---|---------|---------------|---------------|---------------------|
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | lubricating oils, petroleum C20-50, hydrotreated neutral | Oil mist, mineral   | 5 mg/m3 | Not Available | Not Available | Not Available       |
| US ACGIH Threshold Limit Values (TLV)                 | lubricating oils, petroleum C20-50, hydrotreated neutral | Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined | 5 mg/m3 | Not Available | Not Available | TLV® Basis: URT irr |
| US NIOSH Recommended Exposure Limits (RELs)           | lubricating oils, petroleum C20-50, hydrotreated neutral | Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist   | 5 mg/m3 | 10 mg/m3      | Not Available | Not Available       |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | paraffinic distillate, heavy, hydrotreated (severe)      | Oil mist, mineral   | 5 mg/m3 | Not Available | Not Available | Not Available       |
| US ACGIH Threshold Limit Values (TLV)                 | paraffinic distillate, heavy, hydrotreated (severe)      | Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined | 5 mg/m3 | Not Available | Not Available | TLV® Basis: URT irr |
| US NIOSH Recommended Exposure Limits (RELs)           | paraffinic distillate, heavy, hydrotreated (severe)      | Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist   | 5 mg/m3 | 10 mg/m3      | Not Available | Not Available       |

Continued...

## 2263, 2264, 20126, 3843, 3844 SPECIAL TEC F ECO 5W-20 1L, 5L, 20L, 60L, 205L

|   |             |   |                     |                      |               |                     |
|---|-------------|---|---------------------|----------------------|---------------|---------------------|
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | mineral oil | Oil mist, mineral   | 5 mg/m <sup>3</sup> | Not Available        | Not Available | Not Available       |
| US ACGIH Threshold Limit Values (TLV)                 | mineral oil | Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined | 5 mg/m <sup>3</sup> | Not Available        | Not Available | TLV® Basis: URT irr |
| US NIOSH Recommended Exposure Limits (RELs)           | mineral oil | Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist   | 5 mg/m <sup>3</sup> | 10 mg/m <sup>3</sup> | Not Available | Not Available       |

## EMERGENCY LIMITS

| Ingredient   | Material name | TEEL-1        | TEEL-2        | TEEL-3        |
|--|---------------|---------------|---------------|---------------|
| 2263, 2264, 20126, 3843, 3844 SPECIAL TEC F ECO 5W-20 1L, 5L, 20L, 60L, 205L | Not Available | Not Available | Not Available | Not Available |

| Ingredient   | Original IDLH | Revised IDLH  |
|--|---------------|---------------|
| lubricating oils, petroleum C20-50, hydrotreated neutral | Not Available | Not Available |
| nonylated diphenylamines                                 | Not Available | Not Available |
| paraffinic distillate, heavy, hydrotreated (severe)      | Not Available | Not Available |
| mineral oil  | Not Available | Not Available |

## Exposure controls

|                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>  |
| Personal protection              |    |
| Eye and face protection          | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.</li> </ul>  |
| Skin protection                  | See Hand protection below   |
| Hands/feet protection            | <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> |
| Body protection                  | See Other protection below  |
| Other protection                 | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> </ul>  |
| Thermal hazards                  | Not Available   |

## Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator   |
|------------------------------------|----------------------|----------------------|--------------------------|
| up to 10 x ES                      | AK-AUS P2            | -                    | AK-PAPR-AUS / Class 1 P2 |
| up to 50 x ES                      | -                    | AK-AUS / Class 1 P2  | -                        |
| up to 100 x ES                     | -                    | AK-2 P2              | AK-PAPR-2 P2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | Brown colour liquid with characteristic odour; not miscible with water. |  |                |
| <b>Physical state</b>                               | Liquid  | <b>Relative density (Water = 1)</b>            | 0.85           |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Applicable  | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | -20   | <b>Viscosity (cSt)</b>                         | 42.4           |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | 200   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Applicable  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available   | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Immiscible  | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available   | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | Inhalation hazard is increased at higher temperatures.<br>Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.  |
| <b>Ingestion</b>    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.   |
| <b>Skin Contact</b> | <p>The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> |
| <b>Eye</b>          | Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).   |
| <b>Chronic</b>      | Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.   |

|  |   |                   |
|--|---|-------------------|
| 2263, 2264, 20126, 3843, 3844<br>SPECIAL TEC F ECO 5W-20<br>1L, 5L, 20L, 60L, 205L | <b>TOXICITY</b>                                     | <b>IRRITATION</b> |
|  | Not Available                                       | Not Available     |
| lubricating oils, petroleum<br>C20-50, hydrotreated<br>neutral                     | <b>TOXICITY</b>                                     | <b>IRRITATION</b> |
|  | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>    | Not Available     |
|  | Inhalation (rat) LC50: >3.9 mg/l/4hr <sup>[1]</sup> |                   |
|  | Inhalation (rat) LC50: >4.7 mg/l/4hr <sup>[1]</sup> |                   |
|  | Inhalation (rat) LC50: >5 mg/l/4hr <sup>[1]</sup>   |                   |
|  | Inhalation (rat) LC50: >5.2 mg/l/4hr <sup>[1]</sup> |                   |
|  | Inhalation (rat) LC50: >5.3 mg/l/4hr <sup>[1]</sup> |                   |

## 2263, 2264, 20126, 3843, 3844 SPECIAL TEC F ECO 5W-20 1L, 5L, 20L, 60L, 205L

|   |   |                   |
|---|---|-------------------|
|   | Inhalation (rat) LC50: 10.5 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: 5.7 mg/l/4hr <sup>[1]</sup>  |                   |
|   | Inhalation (rat) LC50: 9.6 mg/l/4hr <sup>[1]</sup>  |                   |
|   | Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>         |                   |
| nonylated diphenylamines                            | <b>TOXICITY</b>                                     | <b>IRRITATION</b> |
|   | Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>         | Not Available     |
| paraffinic distillate, heavy, hydrotreated (severe) | <b>TOXICITY</b>                                     | <b>IRRITATION</b> |
|   | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>    | Not Available     |
|   | Inhalation (rat) LC50: >3.9 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: >4.7 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: >5 mg/l/4hr <sup>[1]</sup>   |                   |
|   | Inhalation (rat) LC50: >5.2 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: >5.3 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: 10.5 mg/l/4hr <sup>[1]</sup> |                   |
|   | Inhalation (rat) LC50: 5.7 mg/l/4hr <sup>[1]</sup>  |                   |
|   | Inhalation (rat) LC50: 9.6 mg/l/4hr <sup>[1]</sup>  |                   |
|   | Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>         |                   |
| mineral oil   | <b>TOXICITY</b>                                     | <b>IRRITATION</b> |
|   | Not Available                                       | Not Available     |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |   |
|---|---|
| <b>NONYLATED DIPHENYLAMINES</b>   | Heating of substituted diphenylamines may generate vapours which can irritate the eyes and airways. Drying of skin and mucous membranes leading to irritation may occur with prolonged or repeated contact. Overexposure may cause skin and airway irritation with dizziness and flu-like symptoms. All show a slight to very low order of toxicity following oral or topical administration.   |
| <b>PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)</b>  | The substance is classified by IARC as Group 3:<br><b>NOT</b> classifiable as to its carcinogenicity to humans.<br>Evidence of carcinogenicity may be inadequate or limited in animal testing.  |
| <b>MINERAL OIL</b>  | Toxicity and Irritation data for petroleum-based mineral oils are related to chemical components and vary as does the composition and source of the original crude.<br>A small but definite risk of occupational skin cancer occurs in workers exposed to persistent skin contamination by oils over a period of years. This risk has been attributed to the presence of certain polycyclic aromatic hydrocarbons (PAH) (typified by benz[a]pyrene).<br>Petroleum oils which are solvent refined/extracted or severely hydrotreated, contain very low concentrations of both.   |
| <b>LUBRICATING OILS, PETROLEUM C20-50, HYDROTREATED NEUTRAL &amp; PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)</b> | The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;<br>The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: <ul style="list-style-type: none"> <li>▶ The adverse effects of these materials are associated with undesirable components, and</li> <li>▶ The levels of the undesirable components are inversely related to the degree of processing;</li> <li>▶ Distillate base oils receiving the same degree or extent of processing will have similar toxicities;</li> <li>▶ The potential toxicity of <i>residual base oils</i> is independent of the degree of processing the oil receives.</li> <li>▶ The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.</li> </ul> Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. |
| <b>LUBRICATING OILS, PETROLEUM C20-50, HYDROTREATED NEUTRAL &amp; PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)</b> | For highly and severely refined distillate base oils:<br>In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.  |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ☐ | Carcinogenicity          | ☐ |
| Skin Irritation/Corrosion         | ☐ | Reproductivity           | ☐ |
| Serious Eye Damage/Irritation     | ☐ | STOT - Single Exposure   | ☐ |
| Respiratory or Skin sensitisation | ☐ | STOT - Repeated Exposure | ☐ |
| Mutagenicity                      | ☐ | Aspiration Hazard        | ☐ |

**Legend:** ✗ – Data available but does not fill the criteria for classification  
✓ – Data required to make classification available  
☐ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

Continued...

**Toxicity**

| Ingredient   | Endpoint | Test Duration (hr) | Species                       | Value     | Source |
|--|----------|--------------------|-------------------------------|-----------|--------|
| lubricating oils, petroleum C20-50, hydrotreated neutral | EC50     | 48                 | Crustacea                     | >1000mg/L | 1      |
| lubricating oils, petroleum C20-50, hydrotreated neutral | EC50     | 48                 | Crustacea                     | >1000mg/L | 1      |
| lubricating oils, petroleum C20-50, hydrotreated neutral | NOEC     | 504                | Crustacea                     | >1mg/L    | 1      |
| nonylated diphenylamines                                 | NOEC     | 96                 | Crustacea                     | <10mg/L   | 1      |
| paraffinic distillate, heavy, hydrotreated (severe)      | EC50     | 48                 | Crustacea                     | >1000mg/L | 1      |
| paraffinic distillate, heavy, hydrotreated (severe)      | EC50     | 96                 | Algae or other aquatic plants | >1000mg/L | 1      |
| paraffinic distillate, heavy, hydrotreated (severe)      | EC50     | 96                 | Algae or other aquatic plants | >1000mg/L | 1      |
| paraffinic distillate, heavy, hydrotreated (severe)      | NOEC     | 504                | Crustacea                     | >1mg/L    | 1      |

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

**Bioaccumulative potential**

| Ingredient | Bioaccumulation                       |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

**Mobility in soil**

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> |
|-------------------------------------|--|

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

|                         |    |
|-------------------------|----|
| <b>Marine Pollutant</b> | NO |
|-------------------------|----|

**Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

Continued...



## SECTION 15 REGULATORY INFORMATION

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### LUBRICATING OILS, PETROLEUM C20-50, HYDROTREATED NEUTRAL(72623-87-1.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |  |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  |
| US - Alaska Limits for Air Contaminants   | US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  |
| US - California Permissible Exposure Limits for Chemical Contaminants                         | US - Washington Permissible exposure limits of air contaminants  |
| US - California Proposition 65 - Carcinogens  | US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants   |
| US - Hawaii Air Contaminant Limits  | US ACGIH Threshold Limit Values (TLV)  |
| US - Idaho - Limits for Air Contaminants  | US ACGIH Threshold Limit Values (TLV) - Carcinogens  |
| US - Michigan Exposure Limits for Air Contaminants  | US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens  |
| US - Minnesota Permissible Exposure Limits (PELs)   | US NIOSH Recommended Exposure Limits (RELs)  |
| US - Oregon Permissible Exposure Limits (Z-1)   | US OSHA Permissible Exposure Levels (PELs) - Table Z1  |
| US - Pennsylvania - Hazardous Substance List  | US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants                     | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  |

#### NONYLATED DIPHENYLAMINES(36878-20-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |
|---|
| US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory |
|---|

#### PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)(64742-54-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |  |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  |
| US - Alaska Limits for Air Contaminants   | US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  |
| US - California Permissible Exposure Limits for Chemical Contaminants                         | US - Washington Permissible exposure limits of air contaminants  |
| US - California Proposition 65 - Carcinogens  | US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants   |
| US - Hawaii Air Contaminant Limits  | US ACGIH Threshold Limit Values (TLV)  |
| US - Idaho - Limits for Air Contaminants  | US ACGIH Threshold Limit Values (TLV) - Carcinogens  |
| US - Michigan Exposure Limits for Air Contaminants  | US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens  |
| US - Minnesota Permissible Exposure Limits (PELs)   | US NIOSH Recommended Exposure Limits (RELs)  |
| US - Oregon Permissible Exposure Limits (Z-1)   | US OSHA Permissible Exposure Levels (PELs) - Table Z1  |
| US - Pennsylvania - Hazardous Substance List  | US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants                     | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  |

#### MINERAL OIL(NOT AVAIL.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

|   |  |
|---|--|
| International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs | US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants  |
| US - Alaska Limits for Air Contaminants   | US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants  |
| US - California Permissible Exposure Limits for Chemical Contaminants                         | US - Washington Permissible exposure limits of air contaminants  |
| US - California Proposition 65 - Carcinogens  | US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants   |
| US - Hawaii Air Contaminant Limits  | US ACGIH Threshold Limit Values (TLV)  |
| US - Idaho - Limits for Air Contaminants  | US ACGIH Threshold Limit Values (TLV) - Carcinogens  |
| US - Michigan Exposure Limits for Air Contaminants  | US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens  |
| US - Minnesota Permissible Exposure Limits (PELs)   | US NIOSH Recommended Exposure Limits (RELs)  |
| US - Oregon Permissible Exposure Limits (Z-1)   | US OSHA Permissible Exposure Levels (PELs) - Table Z1  |
| US - Pennsylvania - Hazardous Substance List  | US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity |
| US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants                     |  |

### Federal Regulations

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### SECTION 311/312 HAZARD CATEGORIES

|                                 |    |
|---------------------------------|----|
| Immediate (acute) health hazard | No |
| Delayed (chronic) health hazard | No |
| Fire hazard                     | No |
| Pressure hazard                 | No |
| Reactivity hazard               | No |

#### US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

|               |
|---------------|
| None Reported |
|---------------|

### State Regulations

#### US. CALIFORNIA PROPOSITION 65

|   |
|---|
| WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm |
|---|

#### US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

|   |
|---|
| Soots, tars, and mineral oils (untreated and mildly treated oils and used engine oils) Listed |
|---|

| National Inventory | Status |
|--------------------|--------|
|--------------------|--------|



|                               |  |
|-------------------------------|--|
| Australia - AICS              | N (mineral oil)  |
| Canada - DSL                  | N (mineral oil)  |
| Canada - NDSL                 | N (paraffinic distillate, heavy, hydrotreated (severe); nonylated diphenylamines; mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral)                                 |
| China - IECSC                 | N (mineral oil)  |
| Europe - EINEC / ELINCS / NLP | N (mineral oil)  |
| Japan - ENCS                  | N (mineral oil; lubricating oils, petroleum C20-50, hydrotreated neutral)  |
| Korea - KECI                  | N (mineral oil)  |
| New Zealand - NZIoC           | N (mineral oil)  |
| Philippines - PICCS           | N (mineral oil)  |
| USA - TSCA                    | N (mineral oil)  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC — TWA: Permissible Concentration-Time Weighted Average  
 PC — STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.