

=====

MATERIAL SAFE DATA SHEET

=====

Effective Date: February 1, 2005 Code: Brake Lining Material

=====

=====

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME: ASBESTOS FREE METALLIC DISC BRAKE LINING MATERIAL  
ASBESTOS FREE ORGANIC DISC BRAKE LINING MATERIAL

IDENTIFY BY EDGE CODES: AE-2390-FE, AE-2310-FF, NSS-2170-FE

MANUFACTURER'S NAME:  
Honeywell Friction Materials  
Health, Safety & Environment Quality  
(248) 362-7274

EMERGENCY TELEPHONE NUMBER:  
(24 Hours/Day, 7Days/Week)  
Chemtrec:  
1-800-424-9300  
Spill Response:  
Honeywell Information:  
1-800-707-4555

SUPPLIER'S NAME:  
Rayloc  
Division of Genuine Parts Company  
3100 Windy Hill Road  
Atlanta, GA 30339

REVISION DATE:  
Nov. 1, 2012

=====

SECTION 2: HAZARDOUS INGREDIENTS

=====

Ingredient Name:	CAS Number	Weight %
Cured Polymer Resin encapsulating the following:	None	Balance
Barium Sulfate	7727-43-7	1-30%
Copper	7440-50-8	0-15%
Graphite	7782-42-5	0-15%
Coke	64743-05-01	0-15%
Steel Fibers	7439-89-6	0-15%
Molybdenum Disulfide	1317-33-5	0-7%
Titanium Dioxide	13463-67-7	0-7%
Magnesium Oxide	1309-48-4	0-7%
Antimony Trisulfide	1345-04-6	0-7%
Aluminum Oxide	1344-28-1	0-3%
Sodium Hexafluoroaluminate	15096-52-3	0-3%
Zirconium Silicate	14940-68-2	0-3%
Silica/Quartz	14808-60-7	0-2%

Trace impurities and additional material names not listed above may also appear in Section 15 towards the end of the MSDS. These materials may be listed for local Right-To-Know compliance and for other reasons.

=====

SECTION 3: HAZARDS IDENTIFICATION

=====

EMERGENCY OVERVIEW: Disc brakes are not normally considered hazardous; however, toxic and irritating materials may be released in a fire, machining, grinding, arching, etc. Exposure to dusts may cause eye irritation, soreness in the throat, nose and respiratory tract, and dermatitis-like reactions.

POTENTIAL HEALTH HAZARDS

Skin: Some persons may be sensitive to residual uncured phenolic or cashew resins and develop dermatitis-like reactions similar to poison ivy.

Eyes: Exposure to dust may cause eye irritation.

Inhalation: Irritation or soreness in throat, nose and respiratory tract.

Ingestion: Not an anticipated route of entry.

Delayed Effects: The inhalation of airborne silica-quartz containing dusts may cause serious bodily harm such as pneumoconiosis or silicosis. Man-made vitreous fibers are considered an animal carcinogen via inhalation. Other ingredients are associated with lung irritation and possible lung injury from prolonged overexposure. However, the potential for exposure from this product is low because the ingredients in friction materials are physically bonded together by a resin polymer matrix.

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

Ingredient Name	NTP Status	IARC Status	OSHA List
Silica Quartz	Yes	Yes	Yes

=====

SECTION 4: FIRST AID MEASURES

=====

If any of the symptoms persist, seek medical attention immediately.

SKIN: Wash skin with soap and water after handling parts. Seek medical

attention for persistent irritation.

Eyes: Flush eyes with cool running water if dust becomes embedded. Seek medical attention if reddening persists.

Inhalation: Remove affected person to fresh air.

Ingestion: Not an anticipated route of entry.

Advice to Physician: No specialized first aid or medical treatment procedures are required. Treat according to symptoms present.

---

## SECTION 5: FIREFIGHTING MEASURES

---

FLASH POINT: None

Flash Point Method: Not applicable

Autoignition Temperature: Not established

Upper Flame Limit (volume % in air): Not applicable

Lower Flame Limit (Volume % in air): Not applicable

Flame Propagation Rate (solids): Not established

OSHA Flammability Class: Not classified as flammable material by OSHA

Extinguishing Media: Use extinguishing media appropriate for the surrounding area.

Unusual Fire and Explosion Hazards: Toxic and irritating materials may be released in a fire. This friction material product, as shipped, is not considered hazardous, but machining (arcining, grinding, drilling, or chamfering) may create dusts that are combustible and should be considered hazardous. If the product is ground or machined, local exhaust in accordance with the American National Standards Institute Z9.2 is recommended. Refer to the AlliedSignal Brake Aftermarket Technical Bulletin Rebuilder Supplier Vol. No 80 104 for additional information.

Special Fire Fighting Precautions/Instructions: Self Contained Breathing Apparatus (SCBA) and full fire fighting turn-out gear (Bunk Gear) are recommended if articles are involved in a fire.

---

## SECTION 6: ENVIRONMENTAL RELEASE MEASURES

---

IN CASE OF SPILL OR OTHER RELEASE: Always wear recommended personal protective equipment. No special precautions are required for intact packaging containing this product. If product is crushed, use respiratory protection equipment. Do not dry sweep product or use compressed air to clean up any residues. Use a wet method or vacuums equipped with High Efficiency Particulate (HEPA) filters to clean up any residues from this product. Wastes should be placed in dust tight containers or sealed plastic bags for disposal. Label Properly.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

---

---

## SECTION 7: HANDLING AND STORAGE

---

---

### NORMAL HANDLING:

Always wear recommended personal protective equipment. Avoid breathing or creating dust. See Section 16 "Other Information" and follow the OSHA Appendix F to 1910.1001 "Work Practices and Engineering Controls for Automotive Brake and Clutch Inspection, Disassembly, Repair and Assembly - Mandatory".

STORAGE RECOMMENDATIONS: No special requirements.

---

---

## SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

---

---

ENGINEERING CONTROLS: This friction material product, as shipped, is not considered hazardous, but machining (arcing, grinding, drilling or chamfering) may create dusts or airborne fibers in excess of the OSHA Permissible Exposure Limits (PEL's) for the respective ingredients and should be considered hazardous. If dusts exceed one or more of the OSHA PEL, NIOSH-approved respirators should be worn and proper engineering controls implemented. If the product is ground or machined, local exhaust to control dusts is recommended. The work should be monitored to determine whether employee exposures exceed OSHA PEL's for the respective ingredients. Packages containing this friction material product should be labeled as follows:

CAUTION  
AVOID CREATING OR BREATHING DUSTS  
CONTAINS HAZARDOUS SUBSTANCES  
WHICH MAY CAUSE LUNG INJURY

Standard industrial hygiene practices, including housekeeping and vacuuming with High Efficiency Particulate (HEPA) filters or wet cleaning work surfaces to prevent dusts from becoming airborne should be implemented and maintained.

### PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION: Chemical Resistant/Impermeable Gloves are recommended when handling or removing brake parts.

### EYE PROTECTION:

Safety glasses are adequate for all uses.

#### RESPIRATORY PROTECTION:

Respiratory protection may be required if the ingredient exposures exceed their respective Permissible Exposure Limits (PEL's) or the Time Weighted Average (TWA). Self Contained Breathing Apparatus (SCBA) should be used if dusts are created due to fire or explosion.

#### ADDITIONAL RECOMMENDATIONS:

See additional recommendations in Section 16 "Other Information" below and follow attached 29 CFR 1910.1001, Appendix F "Work Practices and Engineering Controls for Automotive Brake and Clutch Inspection, Disassembly, Repair and Assembly - Mandatory."

#### EXPOSURE GUIDELINES

INGREDIENT NAME	ACGIH TLV	OSHA PEL	OTHER LIMIT (NIOSH)
Antimony Trisulfide	0.5 mg/m3 TWA	0.5 mg/m3 TWA	None
Barium Sulfate	0.5 mg/m3 TWA total dust	0.5 mg/m3 TWA total dust	NIOSH 5 mg/m3 respirable 10 mg/m3 TWA
Aluminum Oxide	5 mg/m3 Respirable 10 mg/m3	15 mg/m3 Total	NIOSH 5 mg/m3 respirable 10 mg/m3 Total TWA
Magnesium Oxide	10 mg/m3 TWA (Fume)total dust	5 mg/m3 TWA (Fume)total dust	None
Zirconium Silicate	5 mg/m3	5 mg/m3	None
Graphite	2.0 mg/m3 respirable 15 mg/m3 Total TWA	5 mg/m3 respirable 15 mg/m3 Total TWA	NIOSH 2.5 mg/m3 (Natural Graphite)
Silica/Quartz	0.1 mg/m3	See OSHA -1000	6 mg/m3 Total
Titanium Dioxide	10 mg/m3	15 mg/m3	None
Inert Dusts	5 mg/m3 respirable 10 mg/m3 total TWA	5 mg/m3 respirable 15 mg/m3 total dust TWA	None

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Gray or dark solid brake part
PHYSICAL STATE:	Solid
MOLECULAR WEIGHT:	May vary based on concentration of components
CHEMICAL FORMULA:	May vary based on concentration of components
ODOR:	Mild odor

SPECIFIC GRAVITY (water = 1.0): 1.7 - 2.5 gm/cc  
SOLUBILITY IN WATER (weight %): None  
pH: Not established  
BOILING POINT: Not applicable  
MELTING POINT: Not applicable  
VAPOR PRESSURE: Not applicable  
VAPOR DENSITY (air=1.0): No volatiles in product  
EVAPORATION RATE: Not applicable COMPARED TO: None  
% VOLATILES: None  
FLASH POINT: None  
(Flash point method and additional flammability data are found in  
Section 5.)

---

#### SECTION 10: STABILITY AND REACTIVITY

---

NORMALLY STABLE? (CONDITIONS TO AVOID):

Product is stable

HAZARDOUS POLYMERIZATION:

None

INCOMPATIBILITIES:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

Toxic and irritating materials may be released in a fire.

---

#### SECTION 11: TOXICOLOGICAL INFORMATION

---

IMMEDIATE (ACUTE) EFFECTS: Skin and eye irritation may occur on repeated contact to dusts.

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS: The inhalation of airborne silica containing dusts may cause serious bodily harm such as pneumoconiosis or silicosis. The inhalation of man-made vitreous fibers has been linked to respiratory cancers in test animals. In addition, other ingredients (tin and barium oxides) can cause respiratory irritation and with prolonged overexposure, lung injury. These lung injuries may not be recognized until many years after exposure. The potential for such exposure from this product is low because the ingredients in friction materials are physically bonded together by a resin polymer matrix.

OTHER DATA: None

---

#### SECTION 12: ECOLOGICAL INFORMATION

=====

Normal decomposition is not expected to result in ecological damage.

=====

=====

SECTION 13: DISPOSAL CONSIDERATIONS

=====

RCRA Is the unused product a RCRA hazardous waste if discarded? No  
Is yes, the RCRA ID number is:

OTHER DISPOSAL CONSIDERATIONS: Dispose in accordance to all applicable federal, state and local regulations.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

=====

SECTION 14: TRANSPORT INFORMATION

=====

US DOT HAZARD CLASS: None

US DOT ID NUMBER: None

For additional information on shipping regulations affecting this, material, contact the information number found in Section 1.

=====

SECTION 15: REGULATORY INFORMATION

=====

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Articles are manufactured from materials found on the TSCA Inventory.

OTHER TSCA ISSUES: None

SARA TITLE III/CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities (TPQs) exist for the following ingredients.

INGREDIENT NAME	SARA/CERCLA RQ (LB)	SARA EHS TPQ (LB)
Barium Sulfate	1000	
Zinc Compounds	100	NA
Copper	5000	NA

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Product as shipped - None

SARA 313 TOXIC CHEMICALS: The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

INGREDIENT NAME	COMMENT
Aluminum Oxide	De Minimus concentration for section 313 is 1.0% (Aluminum Oxide fibrous forms and Aluminum fumes and dusts).
Antimony	De Minimus concentration for section 313 is 1.0%
Barium Sulfate	De Minimus concentration for section 313 is 1.0% (Barium and Barium Compounds).
Copper	De Minimus concentration for section 313 is 1.0%
Zinc and Zinc Sulfide	De Minimus concentration for section 313 is 1.0%

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME	WEIGHT %	COMMENT
Aluminum Oxide	0-3	CA,CT,FL,IL,IN,KY,MA,MN,NJ,PA AND RI
Graphite	0-15	CA,FL,IL,IN,KY,MA,MN,NC,PA AND RI
Silica	0-2	CA,FL,MA,MN AND NJ
Titanium Dioxide	0-7	MA,NJ,PA AND RI

ADDITIONAL REGULATORY INFORMATION: The finished units of friction material shipped to you contain polymer resin encapsulated ingredients. Subsequent processing (arcing, grinding, drilling or chamfering) may create a potential for the release of the ingredients to the atmosphere (e.g. from your dust collection system if you grind our product) or to a landfill (e.g. if you dispose of wetted or palletized grinding dust or drill chips). If they are not of sufficient quantities, you may be required to report such "Releases" on EPA Form "R".

WHMIS CLASSIFICATION (CANADA): Not a controlled product as shipped. Certain processes (e.g., grinding) may cause this article to be considered as a controlled product.

FOREIGN INVENTORY STATUS: Not determined.

SECTION 16: OTHER INFORMATION



#### Other Information:

1. Always follow the "Work Practices and Engineering Controls for Brake and Clutch Inspection, Disassembly, Repair and Assembly - Mandatory" (29 CFR 1910.1001, Appendix F). Although some friction materials used for brake service still contain asbestos, most suppliers are replacing asbestos with steel, mineral, and/or synthetic fibers. Because long term medical effects of these fibers are unknown, it is suggested that exposure levels be controlled for all replacement friction materials.
2. Whenever possible, purchase friction materials that are preground and ready for installation. If machining is necessary, there is a possibility that the Permissible Exposure Limit (PEL) for one or more of the ingredients in the friction material may be exceeded. Local exhaust ventilation must be provided so that worker exposures are maintained below the PEL. Local exhaust ventilation consists of dust collection hoods or enclosures connected by ductwork or piping to a pollution control device.
3. In certain grinding operations where concentrations cannot be reduced below the PEL, a respirator program should be implemented. Respirators also may be required during certain maintenance, start-up or emergency situations where engineering controls cannot maintain concentrations below the PEL.
4. Good housekeeping is essential in a workplace where friction materials are handled. Vacuums equipped with High Efficiency Particulate (HEPA) filters should be used to remove accumulations of friction dusts and wastes. Never use compressed air or dry sweeping for cleaning.
5. Good personal hygiene practices are important in minimizing dust exposures. Do not smoke. Wash before eating. If the PEL is exceeded, protective equipment should be worn. Change into work clothes upon arrival at work and change from work clothes at conclusion of work.

#### DISCLAIMER OF LIABILITY:

The information contained here in is based on data taken from sources believed to be both current and reliable at the time of publication. Rayloc, however, makes no warranties expressed or implied, as to it's accuracy and assumes no liability arising from its use by others. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the users.