

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** SPRAY 'N' SEAL LEAK REPAIR 9.25 OZ  
**Item No:** 82099  
**Product Type:** Aerosol adhesive

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
ACETONE 67-64-1	25-35	500 ppm	1000 ppm; 2400 mg/m <sup>3</sup>
TOLUENE 108-88-3	5-15	20 ppm	200 ppm
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	<10	Not listed	Not listed
2-PROPANOL 67-63-0	<10	200 ppm	400 ppm; 980 mg/m <sup>3</sup>
PROPANE 74-98-6	<10	1000 ppm	1000 ppm; 1800 mg/m <sup>3</sup>
BUTANE 106-97-8	<10	1000 ppm	800 ppm; 1900 mg/m <sup>3</sup>
XYLENE 1330-20-7	<5	100 ppm	100 ppm; 435 mg/m <sup>3</sup>
N-HEXANE 110-54-3	<2	50 ppm	500 ppm; 1800 mg/m <sup>3</sup>
ETHYL BENZENE 100-41-4	0.1-1.0	100 ppm	100 ppm; 435 mg/m <sup>3</sup>

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. Aspiration hazard if swallowed. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. n-Hexane may damage peripheral nerve tissue. Toluene: Repeated exposure has been associated with high frequency hearing loss based on evidence in laboratory animals; the human health consequences of this finding is uncertain. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness. Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	25-35	Not known	A4 - Not Classifiable as a Human Carcinogen	
TOLUENE 108-88-3	5-15	male rat-no evidence; female rat-no evidence; male mice-no, female mice-no	A4 - Not Classifiable as a Human Carcinogen	Group 3; Monograph 71, 1999; Monograph 47, 1989
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	<10	male rat-some evidence, female rat-no evidence, male mice-no evidence, female mice-equivocal evidence		
2-PROPANOL 67-63-0	<10		A4 - Not classifiable as a human carcinogen	Group 3 Monograph 71, 1999; Supp.7, 1987; Monograph 15, 1977

Component	Weight%	NTP	ACGIH Carcinogens	IARC
XYLENE 1330-20-7	<5	male rat-no evidence; female rat-no evidence; male mice-no evidence; female mice-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3: Monograph 71, 1999; Monograph 47, 1989
ETHYL BENZENE 100-41-4	0.1-1.0	male rat-clear evidence; female rat-some evidence; male mice-some evidence; female mice-some evidence	A3 Confirmed animal carcinogen with unknown relevance to humans	Group 2B Monograph 77, 2000

**Medical Conditions Recognized as Being Aggravated by Exposure:** Heart disease, respiratory disorders, liver and kidney diseases, amenia, rhythm disorders of the heart. Toluene: Eye, liver, skin, respiratory and central nervous system disorders, alcoholism.

#### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** <0° F Based on propellant

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Oxides of carbon

**Unusual Fire/Explosion Hazards:** Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

**Lower Explosive Limit:** 1.0

**Upper Explosive Limit:** 12.8

#### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

#### 7. HANDLING AND STORAGE

**Storage:** Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.

**Handling:** Avoid contact with skin and eyes. Use only in a well ventilated area. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Do not use near heat, sparks or open flame. Vapors may accumulate readily and may ignite explosively. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Do not puncture or incinerate container. Wash thoroughly after handling.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.

**Skin:** Neoprene or nitrile gloves recommended.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Clear liquid

**Odor:** Solvent

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point:</b>	<0°F - 395°F
<b>pH:</b>	Does not apply
<b>Solubility in Water:</b>	Nil
<b>Specific Gravity:</b>	0.77
<b>VOC(Wt.%):</b>	54.4%
<b>Vapor Pressure:</b>	Not Determined
<b>Vapor Density (Air=1):</b>	Heavier than air
<b>Evaporation Rate:</b>	Faster than ether

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable at normal conditions
<b>Hazardous Polymerization:</b>	Will not occur.
<b>Incompatibilities:</b>	Strong oxidizers
<b>Conditions to Avoid:</b>	Keep away from heat, sparks and open flame.
<b>Hazardous Products of Combustion:</b>	Oxides of carbon

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

<b>Recommended Method of Disposal:</b>	Disposal should be made in accordance with federal, state and local regulations.. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.
<b>US EPA Waste Number:</b>	D001 as per 40CFR 261.21

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### Ground Transport (DOT)

<b>DOT Shipping Name:</b>	Consumer Commodity
<b>Hazard Class:</b>	ORM-D
<b>UN/ID Number:</b>	None

#### IATA

<b>Proper Shipping Name:</b>	Consumer Commodity (Not more than 1 liter)
<b>Class or Division:</b>	Class 9
<b>UN/ID Number:</b>	ID 8000

#### IMDG

<b>Proper Shipping:</b>	Aerosols, Limited Quantity
<b>Hazard Class:</b>	Class 2.1
<b>UN Number:</b>	UN 1950

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

TOLUENE, XYLENE, N-HEXANE, ETHYL BENZENE

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

**Product Name:** SPRAY 'N' SEAL LEAK REPAIR 9.25  
OZ

**Item No:** 82099

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 4, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** December 15, 2009

**Revision** 11

**Number:**

**Telephone No.:** 1-87-Permatex (877) 376-2839