

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

| |
|--|
| 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING |
|--|

| | | |
|-----------------------|-------------------------------|----------------|
| ACM | Regulatory Information Number | 1-800-325-3751 |
| 3901 E. Provident Dr. | Telephone | 1-800-274-5263 |
| Cincinnati, OH 45204 | Emergency telephone number | 1-800-274-5263 |

| | |
|--------------|---|
| Product name | NAPA® PREM PERF UFMO SAE 15W-40 MOTOR OIL |
|--------------|---|

| | |
|--------------|--------|
| Product code | 792606 |
|--------------|--------|

| |
|----------------------------------|
| 2. HAZARDS IDENTIFICATION |
|----------------------------------|

Emergency Overview

Appearance: liquid, amber

WARNING! CAUSES EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS. MAY BE HARMFUL IF SWALLOWED.

Potential Health Effects**Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

| |
|--|
| 3. COMPOSITION/INFORMATION ON INGREDIENTS |
|--|

| Hazardous Components | CAS-No. / Trade Secret No. | Concentration |
|-----------------------------|----------------------------|---------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 | >=80-<90% |
| ZINC COMPOUNDS | 68649-42-3 | >=1.5-<5% |

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

4. FIRST AID MEASURES**Eyes**

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

Dry chemical, Carbon dioxide (CO2), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons, hydrogen sulfide, zinc oxide, oxides of sulfur, nitrogen and phosphorus, Amines

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE**Handling**

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Contains no substances with occupational exposure limit values.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist. Maintain eye wash station near work area.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Physical state | liquid |
| Colour | amber |
| Odour | hydrocarbon-like |
| Flash point | (>)390 °F / 199 °C Cleveland open cup |
| Lower explosion limit/Upper explosion limit | 1 %(V) / 6 %(V) |
| Vapour pressure | 0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor Pressure |
| Density | 0.880 g/cm ³ @ 60.1 °F / 15.6 °C |
| | 7.4 lb/gal @ 60.1 °F / 15.6 °C |
| Water solubility | negligible |

10. STABILITY AND REACTIVITY**Stability**

Stable.

Conditions to avoid

excessive heat

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

SAFETY DATA SHEET

Revision Date: 08/12/2011
 Print Date: 1/23/2012
 MSDS Number: 000000213183
 Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
 MOTOR OIL
 792606

11. TOXICOLOGICAL INFORMATION**Acute oral toxicity**

Acute oral toxicity - Product : no data available

Acute oral toxicity - Components

HEAVY PARAFFINIC DISTILLATE : LD 50: > 15 g/kg Species: Rat

ZINC COMPOUNDS : LD 50: 2,000 - 5,000 mg/kg Species: Rat

Acute inhalation toxicity

Acute inhalation toxicity - Product : no data available

Acute dermal toxicity

Acute dermal toxicity - Product : no data available

Acute dermal toxicity - Components

HEAVY PARAFFINIC DISTILLATE : LD 50: > 5 g/kg Species: Rabbit

ZINC COMPOUNDS : LD 50: > 2,000 mg/kg Species: Rabbit

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

12. ECOLOGICAL INFORMATION**Biodegradability**

Biodegradability - Product : no data available

SAFETY DATA SHEET

Revision Date: 08/12/2011
Print Date: 1/23/2012
MSDS Number: 000000213183
Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects**Toxicity to fish**

Toxicity to fish - Product : no data available

Toxicity to daphnia and other aquatic invertebrates.

Toxicity to daphnia and other aquatic invertebrates.
- Product : no data available

Toxicity to algae

Toxicity to algae - Product : no data available

Toxicity to bacteria

Toxicity to bacteria - Product : no data available

13. DISPOSAL CONSIDERATIONS**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION**REGULATION**

SAFETY DATA SHEET

Revision Date: 08/12/2011
 Print Date: 1/23/2012
 MSDS Number: 000000213183
 Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
 MOTOR OIL
 792606

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT /LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|-----------------------------|
|-----------|----------------------|---------------|--------------------|---------------|-----------------------------|

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SAFETY DATA SHEET

Revision Date: 08/12/2011
 Print Date: 1/23/2012
 MSDS Number: 000000213183
 Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
 MOTOR OIL
 792606

15. REGULATORY INFORMATION**California Prop. 65**

| | |
|--|--|
| Proposition 65 warnings are not required for this product based on the results of a risk assessment. | |
|--|--|

SARA Hazard Classification**SARA 311/312 Classification**

| |
|---------------------|
| Acute Health Hazard |
|---------------------|

SARA 313 Component(s)

| | |
|----------------|--------|
| ZINC COMPOUNDS | 1.59 % |
|----------------|--------|

New Jersey RTK Label Information

| | |
|-----------------------------|------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 |
| LUBRICANT ADDITIVE | |
| ZINC COMPOUNDS | |
| ZINC COMPOUNDS | 68649-42-3 |

Pennsylvania RTK Label Information

| | |
|-----------------------------|------------|
| HEAVY PARAFFINIC DISTILLATE | 64742-54-7 |
| LUBRICANT ADDITIVE | |

Notification status

| | |
|--|----------------------|
| US. Toxic Substances Control Act | y (positive listing) |
| Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) | y (positive listing) |
| Australia. Industrial Chemical (Notification and Assessment) Act | y (positive listing) |
| New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand | n (Negative listing) |
| Japan. Kashin-Hou Law List | n (Negative listing) |
| Korea. Toxic Chemical Control Law (TCCL) List | y (positive listing) |

SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 1/23/2012

MSDS Number: 000000213183

Version: 1.0

NAPA® PREM PERF UFMO SAE 15W-40
MOTOR OIL
792606

| | |
|---|----------------------|
| Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act | y (positive listing) |
| China. Inventory of Existing Chemical Substances | y (positive listing) |

Reportable quantity - Product

| | |
|--|-----------|
| US. EPA CERCLA Hazardous Substances (40 CFR 302) | 66666 lbs |
|--|-----------|

Reportable quantity-Components

| | | |
|---------|-----------|-------|
| ARSENIC | 7440-38-2 | 1 lbs |
|---------|-----------|-------|

| | HMIS | NFPA |
|------------------|-------------|-------------|
| Health | 2 | 1 |
| Flammability | 1 | 1 |
| Physical hazards | 0 | |
| Instability | | 0 |
| Specific Hazard | -- | -- |

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by ACM's Environmental Health and Safety Department (1-800-325-3751)