

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE MaxLife™ Motor Oil

Valvoline MaxLife™ is the first motor oil specially formulated for higher mileage engines. Valvoline MaxLife™ is a blend of premium synthetic and conventional basestocks with a seal conditioning agent, extra cleaning agents, additional antiwear additives and friction modifiers.

The Valvoline MaxLife™ Motor Oil Advantage

- Conditions engine seals
- Minimizes oil consumption
- Maximizes power output
- Resists thermal breakdown
- Reduces deposit formation
- Provides easier cold starts

Approvals/Performance Levels

API SN/SM

Valvoline's Maxlife™ motor oil is safe for use in new and rebuilt engines and will not void new car warranties.

Meets engine and emission system protection requirements of ILSAC GF-5.

Test	SAE 5W-20	SAE 5W-30	SAE 10W-30	SAE 10W-40	SAE 20W-50
Vis @ 100°C (cSt)	8.8	11.5	11.5	15	19.5
Vis @ 40°C (cSt)	51	67	75	102	170
Viscosity Index	152	163	146	158	132
Spec Gravity @ 60°F	0.86	0.87	0.87	0.87	0.88
Density (lbs/gal)	7.2	7.2	7.2	7.2	7.3
Total Base Number	8.7	8.7	8.7	8.7	8.7
Flash Point COC (°C)	217	221	216	220	236
Pour Point (°C)	-42	-42	-42	-39	-33
CCS cP (°C)	6000@-30C	5800@-30C	6200@-25C	6000@-25C	7000@-15C
MRV TP-1 cP (°C)	22,000@-35C	25,000@-35C	25,000@-30C	24,000@-30C	20,000@-20C
Noack % off @ 250°C	12	12	11	12.0	7
Sulfated Ash	0.93	0.93	0.93	0.93	0.93
Zinc/Phosphorus, wt%	0.083/0.076	0.083/0.076	0.083/0.076	0.083/0.076	0.083/0.076
Calcium/Moly, wt%	0.211/0.014	0.211/0.014	0.211/0.014	0.211/0.014	0.211/0.014
Sodium, wt%	0.049	0.049	0.049	0.049	0.049

. See operator's manual for recommended viscosity grade and API service classification.

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:
12-15-10

Replaces:
1-22-09

Author's Initials:
DJD

Pages

Rev. Code
004

ASHLAND

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE MaxLife™ Motor Oil

Valvoline MaxLife™ is the first motor oil specially formulated for higher mileage engines. Valvoline MaxLife™ is a blend of premium synthetic and conventional basestocks with a seal conditioning agent, extra cleaning agents, additional antiwear additives and friction modifiers.

The Valvoline MaxLife™ Motor Oil Advantage

- Conditions engine seals
- Minimizes oil consumption
- Maximizes power output
- Resists thermal breakdown
- Reduces deposit formation
- Provides easier cold starts

Approvals/Performance Levels

API SN/SM

Valvoline's Maxlife™ motor oil is safe for use in new and rebuilt engines and will not void new car warranties. Meets engine and emission system protection requirements of ILSAC GF-5.

Test	SAE 30
Vis @ 100°C (cSt)	11.4
Vis @ 40°C (cSt)	85
Viscosity Index	124
Spec Gravity @ 60° F	0.88
Density (lbs/gal)	7.3
Total Base Number	8.7
Flash Point COC (°C)	220
Pour Point (°C)	-30
Noack % off @ 250°C	<12.0
Sulfated Ash	0.93
Zinc/Phosphorus, wt%	0.083/0.076
Calcium/Moly, wt. %	0.211/0.014
Sodium, wt%	0.049

. See operator's manual for recommended viscosity grade and API service classification.

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:
12-15-10

Replaces:
1-22-09

Author's Initials:
DJD

Pages

Rev. Code
004

ASHLAND