MSDS# 26655 Version 1.0 Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Material Safety Data Sheet

1. MATERIAL AND COMPANY IDENTIFICATION

Material Name Pennzoil Synthetic Multi-Vehicle ATF

Uses Transmission fluid

: SOPUS Products Manufacturer/Supplier

PO BOX 4427

Houston, TX 77210-4427

USA

MSDS Request : 877-276-7285

Emergency Telephone Number

Spill Information 877-242-7400 Health Information 877-504-9351

2. COMPOSITION/INFORMATION ON INGREDIENTS

Synthetic base oil and additives.

Highly refined mineral oil.

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odour : Red. Liquid at room temperature. Slight hydrocarbon.

Not classified as dangerous for supply or conveyance. **Health Hazards**

Safety Hazards Not classified as flammable but will burn.

Not classified as dangerous for the environment. **Environmental Hazards**

Health Hazards : Not expected to be a health hazard when used under normal

conditions.

Health Hazards

Inhalation : Under normal conditions of use, this is not expected to be a

primary route of exposure.

Skin Contact : Prolonged or repeated skin contact without proper cleaning can

clog the pores of the skin resulting in disorders such as oil

acne/folliculitis.

Eye Contact : May cause slight irritation to eyes.

Ingestion Low toxicity if swallowed.

Other Information : Used oil may contain harmful impurities.

Signs and Symptoms : Oil acne/folliculitis signs and symptoms may include formation

> of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. : Pre-existing medical conditions of the following organ(s) or

Aggravated Medical Conditions

organ system(s) may be aggravated by exposure to this

material: Skin.

1/8

Print Date 08/09/2012 00000032952 MSDS US

MSDS# 26655 Version 1.0

Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

Material Safety Data Sheet

Environmental Hazards Additional Information

: Not classified as dangerous for the environment.

: Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous

this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal

conditions.

Inhalation : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact : Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent

irritation occurs, obtain medical attention.

Eye Contact : Flush eye with copious quantities of water. If persistent

irritation occurs, obtain medical attention.

Ingestion : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Advice to Physician : Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Flash point : Typical 190 °C / 374 °F (COC)

Upper / lower : Typical 1 - 10 %(V)

Flammability or Explosion limits

Auto ignition temperature : > 320 °C / 608 °F

Specific Hazards : Hazardous combustion products may include: A complex

mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

Suitable Extinguishing

Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing

Media

Do not use water in a jet.

Protective Equipment for

Firefighters

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment

to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or

other appropriate barriers.

2/8

Print Date 08/09/2012 000000032952 MSDS US

MSDS# 26655 Version 1.0

Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR **Material Safety Data Sheet**

1910.1200

Clean Up Methods Slippery when spilt. Avoid accidents, clean up immediately.

> Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

: Local authorities should be advised if significant spillages **Additional Advice**

cannot be contained.

7. HANDLING AND STORAGE

General Precautions Use local exhaust ventilation if there is risk of inhalation of

> vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Handling : Avoid prolonged or repeated contact with skin. Avoid inhaling

vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment

should be used.

Storage : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labelled and closeable containers. Store at

ambient temperature.

Recommended Materials : For containers or container linings, use mild steel or high

density polyethylene.

Unsuitable Materials : PVC.

Additional Information : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Oil mist,	ACGIH	TWA(Inhalabl		5 mg/m3	
mineral		e fraction.)			
Oil mist,	OSHA Z1	PEL(Mist.)		5 mg/m3	
mineral					
Oil mist,	OSHA Z1A	TWA(Mist.)		5 mg/m3	
mineral					
Oil mist,	OSHA Z1	(Mist.)			Listed.
mineral					

Shell has adopted as Interim Standards the OSHA Z1A values Additional Information

that were established in 1989 and later rescinded.

Exposure Controls : The level of protection and types of controls necessary will vary

3/8

Print Date 08/09/2012 00000032952 MSDS US

MSDS# 26655 Version 1.0 Effective Date 08/08/2012

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne

concentrations to be generated.

Personal Protective

Equipment

Respiratory Protection

Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers.

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point

>65°C(149 °F)].

Hand Protection : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection : Wear safety glasses or full face shield if splashes are likely to

occur.

Protective Clothing : Skin protection not ordinarily required beyond standard issue

work clothes.

Monitoring Methods : Monitoring of the concentration of substances in the breathing

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also

be appropriate.

Environmental Exposure

Controls

Minimise release to the environment. An environmental

assessment must be made to ensure compliance with local

environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Red. Liquid at room temperature.

Odour : Slight hydrocarbon. pH : Not applicable.

Initial Boiling Point and : > 280 °C / 536 °F estimated value(s)

4/8

Print Date 08/09/2012 000000032952 MSDS US

MSDS# 26655 Version 1.0 Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Material Safety Data Sheet

Boiling Range

Pour point : Data not available

Typical 190 °C / 374 °F (COC) Flash point

Upper / lower Flammability

or Explosion limits

 $: > 320 \, ^{\circ}\text{C} / 608 \, ^{\circ}\text{F}$

: Typical 1 - 10 %(V)

Auto-ignition temperature

: < 0.5 Pa at 20 °C / 68 °F (estimated value(s)) Vapour pressure

: Typical 0.85 at 15 °C / 59 °F Specific gravity

Density : Typical 850 kg/m3 at 15 °C / 59 °F

Water solubility : Negligible.

n-octanol/water partition

: > 6 (based on information on similar products)

coefficient (log Pow)

Kinematic viscosity : Typical 35 mm2/s at 40 °C / 104 °F

Vapour density (air=1) : > 1 (estimated value(s)) Evaporation rate (nBuAc=1) : Data not available

10. STABILITY AND REACTIVITY

Stability Stable.

Conditions to Avoid Extremes of temperature and direct sunlight.

Materials to Avoid Strong oxidising agents.

Hazardous Decomposition : Hazardous decomposition products are not expected to form

Products

during normal storage.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment Information given is based on data on the components and the

toxicology of similar products.

Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit Not considered to be an inhalation hazard under normal

conditions of use.

Expected to be slightly irritating. Prolonged or repeated skin **Skin Irritation**

contact without proper cleaning can clog the pores of the skin

resulting in disorders such as oil acne/folliculitis.

Eye Irritation Expected to be slightly irritating.

Respiratory Irritation

Inhalation of vapours or mists may cause irritation.

Sensitisation

Not expected to be a skin sensitiser.

Repeated Dose Toxicity

Not expected to be a hazard.

Mutagenicity

Not considered a mutagenic hazard.

Carcinogenicity

Components are not known to be associated with carcinogenic

effects.

Reproductive and **Developmental Toxicity Additional Information**

Not expected to be a hazard.

Used oils may contain harmful impurities that have

accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

5/8

00000032952 Print Date 08/09/2012 MSDS US

MSDS# 26655 Version 1.0 Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Material Safety Data Sheet

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test

extract.

Mobility : Liquid under most environmental conditions. Floats on water. If

it enters soil, it will adsorb to soil particles and will not be

mobile.

Persistence/degradability: Expected to be not readily biodegradable. Major constituents

are expected to be inherently biodegradable, but the product contains components that may persist in the environment. Contains components with the potential to bioaccumulate.

Bioaccumulation
Other Adverse Effects

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

Container Disposal : Dispose in accordance with prevailing regulations, preferably

to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

14. TRANSPORT INFORMATION

US Department of Transportation Classification (49CFR)

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

MSDS# 26655 Version 1.0 Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Material Safety Data Sheet

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

EINECS All components listed or

polymer exempt.

TSCA All components listed.
DSL All components listed.

Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA Hazard Categories (311/312)

No SARA 311/312 Hazards.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

NFPA Rating (Health, : 0, 1, 0

Fire, Reactivity)

MSDS Version Number : 1.0

MSDS Effective Date : 08/08/2012

7/8

Print Date 08/09/2012 000000032952 MSDS US

MSDS# 26655 Version 1.0

Effective Date 08/08/2012

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

Material Safety Data Sheet

MSDS Revisions

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

MSDS Regulation : The content and format of this MSDS is in accordance with the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

MSDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : The information contained herein is based on our current

knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to

be obtained from the use of the product.