Page: 1/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

1 Identification

· Product identifier

· Trade name: Bar's Leaks® Jack Oil with Stop Leak

Product code: HJ12

· Recommended use and restriction on use

· Recommended use: Lubricant

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Bar's Products P.O. Box 187 Holly, MI 48442 USA Phone: (810) 603-1321



ChemTel Inc.

+1 (800)255-3924, +1 (813)248-0585



2 Hazard(s) identification

· Classification of the substance or mixture

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS08

· Signal word: Danger

Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), hydrotreated light

· Hazard statements:

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Cont'd. on page 2)

Page: 2/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 1)

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:			
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic (IP 346 < 3%; ≤ 20.5 mm	² /s @ 20-40%		
40 °C)			
♦ Asp. Tox. 1, H304			
64742-47-8 Distillates (petroleum), hydrotreated light	20-40%		
& Asp. Tox. 1, H304 Flam. Liq. 4, H227			

· Additional information:

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This product meets these requirements.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Wash with soap and water.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

A person vomiting while lying on their back should be turned onto their side.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Coughing

Slight irritant effect on eyes.

Slight irritant effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

(Cont'd. on page 3)

Page: 3/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 2)

Nausea in case of ingestion.

· Danger:

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

· Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Medical supervision for at least 48 hours.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

Foam

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

- For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.

· Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Remove from the water surface (e.g. skim or suck off).

Send for recovery or disposal in suitable receptacles.

Reference to other sections:

See Section 7 for information on safe handling.

(Cont'd. on page 4)

Page: 4/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep containers tightly sealed.

· Specific end use(s): No relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada) Long-term value: 200 mg/m³ Skin

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

- · Engineering controls: No relevant information available.
- Breathing equipment:

Not required under normal conditions of use.

(Cont'd. on page 5)

Page: 5/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 4)

Use suitable respiratory protective device when aerosol or mist is formed. For spills, respiratory protection may be advisable.

Protection of hands:



Protective gloves

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Oil resistant protective clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

Physical and chemical properties				
Information on basic physical and chemical properties				
· Appearance:				
Form:	Liquid			
Color:	Yellow			
· Odor:	Petroleum-like			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
Melting point/Melting range:	Not determined.			
Boiling point/Boiling range:	Not determined.			
· Flash point:	184 °C (363 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Auto-ignition temperature:	Not determined.			
Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not self-igniting.			
Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits				
Lower:	Not determined.			
Upper:	Not determined.			
		(Cont'd. on page		

Page: 6/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

		(Cont'd. of page
Oxidizing properties:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	0.858 g/cm³ (7.16 lbs/gal)	
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic at 40 °C (104 °F):	12 cSt	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

To avoid thermal decomposition, do not overheat.

· Possibility of hazardous reactions:

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong oxidizing agents.

- · Conditions to avoid: Excessive heat.
- · Incompatible materials: Oxidizers
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Slight irritant effect on skin and mucous membranes.
- · On the eye: Slight irritant effect on eyes.
- Sensitization: No sensitizing effects known.

(Cont'd. on page 7)

Page: 7/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eve contact.

Skin contact.

- Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- · Toxicity
- · Aquatic toxicity The material is harmful to the environment.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Ecotoxical effects:
- · Remark: Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- Additional ecological information
- · General notes: Avoid release to the environment.
- · Other adverse effects: No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

(Cont'd. on page 8)

Page: 8/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 7)

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.
Transport hazard class(es)	
· DOT, ADR, IMDG, IATA · Class	Not regulated.
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.
· Environmental hazards · Marine pollutant:	No
· Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	of Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 304 (emergency release notification):

None of the ingredients are listed.

(Cont'd. on page 9)

Page: 9/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 8)

· Sections 311/312 (hazardous chemical threshold planning quantity in pounds):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Present in trace quantities.

91-20-3 naphthalene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

- Canadian substance listings
- · Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 04/12/2016 / -
- · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 04/12/2016 Revision: 04/12/2016

Trade name: Bar's Leaks® Jack Oil with Stop Leak

(Cont'd. of page 9)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids, Hazard Category 4 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 1SBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com