

Issuing Date 03-Apr-2007

Revision Date 03-May-2013

Revision Number 3

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Name** Mothers Mag & Aluminum Polish  
**Product Code(s)** 05100, 05101, 05102, 05104, 35100, 55100  
**Recommended Use** Metal polish

**Supplier Address**  
 MOTHERS POLISHES WAXES CLEANERS  
 5456 Industrial Drive  
 Huntington Beach, CA 92649  
 TEL: 714-891-3364  
 FAX: 714-893-1827

**Emergency Telephone Number** Chemtrec 1-800-424-9300

**2. HAZARDS IDENTIFICATION**

**WARNING!**

**Emergency Overview**

May be harmful if swallowed  
 Harmful: may cause lung damage if swallowed  
 May cause skin and eye irritation  
 Repeated contact may cause allergic reactions in very susceptible persons  
 May cause drowsiness and dizziness  
 Combustible material

**Appearance** White

**Physical State** Solid.

**Odor** Pine

**Potential Health Effects**

**Principle Routes of Exposure** Skin contact. Eye contact.

**Acute Toxicity**

**Eyes**

May cause irritation.

**Skin**

May cause skin irritation and/or dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking.

**Inhalation**

May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

**Ingestion**

Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause additional affects as listed under "Inhalation". Harmful: may cause lung damage if swallowed.

**Chronic Effects**

Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

**Aggravated Medical Conditions**

Allergies. Skin disorders. Respiratory disorders. Central nervous system. Pre-existing eye disorders.

**Interactions with Other Chemicals** Use of alcoholic beverages may enhance toxic effects. Irritants. Sensitizers. Epoxies.

**Environmental Hazard** See Section 12 for additional Ecological Information.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	25-50
Aluminum oxide	1344-28-1	25-50
Stearic acid	57-11-4	<10
Triethanolamine	102-71-6	<10
Tall oil fatty acids	61790-12-3	<10
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	9036-19-5	<10
Hexylene glycol	107-41-5	<10

### 4. FIRST AID MEASURES

<b>General Advice</b>	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
<b>Ingestion</b>	Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Consult a physician.
<b>Notes to Physician</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Combustible material: may burn but does not ignite readily.
<b>Flash Point</b>	194 °F / 90 °C
<b>Suitable Extinguishing Media</b>	Carbon dioxide (CO <sub>2</sub> ). Dry powder. Dry chemical. Foam.
<b>Unsuitable Extinguishing Media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	Yes.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapors.
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<b>NFPA</b>	<b>Health Hazard</b> 1	<b>Flammability</b> 2	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> N/A
<b>HMIS</b>	<b>Health Hazard</b> 1	<b>Flammability</b> 2	<b>Physical Hazard</b> 0	<b>Personal Protection</b> B

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Use personal protective equipment. Avoid contact with the skin and the eyes.
<b>Environmental Precautions</b>	Refer to protective measures listed in Sections 7 and 8.
<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Cleaning Up</b>	Dam up. Soak up with inert absorbent material. Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Avoid contact with skin and eyes.
<b>Storage</b>	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> (as oil mist)	TWA: 5 mg/m <sup>3</sup> (as oil mist)	
Aluminum oxide 1344-28-1	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	
Triethanolamine 102-71-6	TWA: 5 mg/m <sup>3</sup>	-	
Tall oil fatty acids 61790-12-3	5 mg/m <sup>3</sup> (resp) 10 mg/m <sup>3</sup> STEL (resp)	5 mg/m <sup>3</sup> (resp)	
Hexylene glycol 107-41-5	Ceiling: 25 ppm	(vacated) Ceiling: 25 ppm (vacated) Ceiling: 125 mg/m <sup>3</sup>	Ceiling: 25 ppm Ceiling: 125 mg/m <sup>3</sup>

*Immediately Dangerous to Life or Health.*

### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems

### Personal Protective Equipment

#### Eye/Face Protection

Safety glasses with side-shields.

#### Skin and Body Protection

Protective gloves.

#### Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

### Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	White.	<b>Odor</b>	Pine.
<b>Odor Threshold</b>	No information available.	<b>Physical State</b>	Solid.
<b>pH</b>	No information available.	<b>Autoignition Temperature</b>	No information available.
<b>Flash Point</b>	194 °F / 90 °C	<b>Boiling Point/Boiling Range</b>	No information available.
<b>Decomposition Temperature</b>	No information available.	<b>Flammability Limits in Air</b>	No information available.
<b>Melting Point/Range</b>	55 °C	<b>Evaporation Rate</b>	No information available.
<b>Solubility</b>	No information available.	<b>Vapor Density</b>	No data available.
<b>Vapor Pressure</b>	No data available.		
<b>VOC Content (%)</b>	<30		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Incompatible Products</b>	None known based on information supplied.
<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Hazardous Decomposition Products</b>	None under normal use. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Product Information

<b>Inhalation</b>	May cause drowsiness and dizziness.
<b>Eye Contact</b>	May cause slight irritation.
<b>Skin Contact</b>	Prolonged or repeated contact may dry skin and cause irritation
<b>Ingestion</b>	Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, hydrotreated light	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Aluminum oxide	> 5000 mg/kg ( Rat )		
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Stearic acid	-	5 g/kg ( Rabbit )	-
Triethanolamine	= 4190 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit ) > 16 mL/kg ( Rat )	
Tall oil fatty acids	= 7600 mg/kg ( Rat )		
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	= 4190 mg/kg ( Rat )		
Hexylene glycol	= 3692 mg/kg ( Rat )	12,3000 mg/kg ( Rabbit )	> 310 mg/m <sup>3</sup> ( Rat ) 1 h

### Chronic Toxicity

<b>Chronic Toxicity</b>	Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal
-------------------------	--

Chemical Name	ACGIH	IARC	NTP	OSHA
Triethanolamine		Group 3		

<b>Target Organ Effects</b>	Central nervous system (CNS). Eyes. Respiratory system. Skin.
-----------------------------	---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Do not allow material to contaminate ground water system.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light		LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 45 mg/L flow-through (Pimephales promelas)		LC50 96 h: = 4720 mg/L (Daphnia magna)
Aluminum oxide		LC50 96 h: > 100 mg/L semistatic (Salmo trutta)		LC50 48 h: > 100 mg/L (daphnia magna)
Triethanolamine	EC50 72 h: = 216 mg/L (Desmodesmus subspicatus) EC50 96 h: = 169 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600 - 13000 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1000 mg/L static (Pimephales promelas) LC50 96 h: 450 - 1000 mg/L static (Lepomis macrochirus)	EC50 > 10000 mg/L 30 min	EC50 24 h: = 1386 mg/L (Daphnia magna)
Tall oil fatty acids	EC50 72 h: >= 1000 mg/L (Pseudokirchneriella subcapitata)			
Hexylene glycol		LC50 96 h: 10500-11000 mg/L flow-through (Pimephales promelas) LC50 96 h: = 10000 mg/L static (Lepomis macrochirus) LC50 96 h: = 10700 mg/L static (Pimephales promelas) LC50 96 h: = 8690 mg/L flow-through (Pimephales promelas)	EC50 = 3038 mg/L 5 min	EC50 48 h: 2700 - 3700 mg/L (Daphnia magna)
<b>Chemical Name</b>		<b>Log Pow</b>		
Triethanolamine		-2.53		
Tall oil fatty acids		5.98		
Hexylene glycol		0.13986		

## 13. DISPOSAL CONSIDERATIONS

### Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

### Contaminated Packaging

Do not re-use empty containers.

California Hazardous Waste Codes 331

## 14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>EINECS</b>	Complies
<b>ELINCS</b>	Complies

### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

### SARA 311/312 Hazard Categories

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

### Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

### U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Aluminum oxide	X	X	X		X
Solvent naphtha (petroleum), medium aliphatic	X				
Triethanolamine	X	X	X		X
Hexylene glycol	X	X	X		X

**International Regulations****Mexico - Grade**

Slight risk, Grade 1

Chemical Name	Carcinogen Status	Exposure Limits
Aluminum oxide		Mexico: TWA 10 mg/m <sup>3</sup>
Hexylene glycol		Mexico: Ceiling 25 ppm Mexico: Ceiling 125 mg/m <sup>3</sup>

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

D2B Toxic materials

**16. OTHER INFORMATION**

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 03-Apr-2007  
**Revision Date** 03-May-2013  
**Revision Note** Product Code change

**General Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**