



# SAFETY DATA SHEET

## Section 1: IDENTIFICATION

### 1.1 PRODUCT IDENTIFIER

**Product Name:** Squeak Relief <sup>TM</sup>  
**Product Code:** 90031

### 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Use:** Brake lubricant.

### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Name/Address:** International Lubricants, Inc.  
P.O. Box 24743, Seattle WA  
98124-0743, USA  
**Telephone Number:** (206) 762-5343  
(800) 333-LUBE (5823)

### 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone Number:** CHEM TEL (800) 255-3924  
CHEM TEL (813) 248-0585

## Section 2: HAZARD(S) IDENTIFICATION

### 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

#### Hazard class

Flammable Aerosol 1  
Gases Under Pressure - Liquefied Gas  
Eye irritation 2A  
Skin sensitization 1  
Specific target organ toxicity - Single exposure 3

### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

#### Hazard Pictogram:



**Signal Word:** Danger

**Hazard Statement:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid breathing gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Use only outdoors or in a well-ventilated area.



## SAFETY DATA SHEET

<b>Response:</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Storage:</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up.
<b>Disposal:</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 ADDITIONAL INFORMATION

**Hazards not otherwise classified:** Not applicable.

9 % of the mixture consists of ingredient(s) of unknown acute toxicity.

**WHMIS Classification(s):**

- Class A - Compressed Gas
- Class B5 - Flammable Aerosol
- Class D2B - Skin Sensitization
- Class D2B - Skin/Eye Irritant

**WHMIS Hazard Symbols:**



**WHMIS Signal Word:** DANGER

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 MIXTURES

Ingredient	CAS No	Wt. %
Acetone	67-64-1	30 - 60
Aluminum, elemental	7429-90-5	10 - 30
Propane	74-98-6	10 - 30
Stoddard solvent	8052-41-3	5 - 10
Isobutane	75-28-5	5 - 10
Sulfonic acids, petroleum, calcium salts	61789-86-4	1 - 5

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### Section 4: FIRST-AID MEASURES

#### 4.1 DESCRIPTION OF THE FIRST AID MEASURE

**Eye:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.



## SAFETY DATA SHEET

- Skin:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- Inhalation:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
- Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.
- Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

- Note to Physicians:** Symptoms may not appear immediately.
- Specific Treatments:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## Section 5: FIRE-FIGHTING MEASURES

### 5.1 FLAMMABILITY

- Flammability:** Flammable by WHMIS/OSHA criteria.

### 5.2 EXTINGUISHING MEDIA

- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
- Unsuitable Extinguishing Media:** Direct water spray.

### 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

### 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Containers may explode when heated. Use water spray to keep fire-exposed containers cool.



# SAFETY DATA SHEET

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back.

### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak. Provide ventilation.

## Section 7: HANDLING AND STORAGE

### 7.1 PRECAUTIONS FOR SAFE HANDLING

**Handling:** Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Container may explode if heated. Use only non-sparking tools. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapors/spray. Do not swallow. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. (See section 8)

**General Hygiene Advice:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Storage:** Keep out of the reach of children. Store in dry, cool, well-ventilated area. Do not store at temperatures above 50 °C / 122 °F. Store away from direct sunlight or other heat sources. Store locked up. (See section 10)

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 CONTROL PARAMETERS

#### Exposure Guidelines

Occupational Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV
Acetone	1000 ppm; 2400 mg/m <sup>3</sup>	500 ppm
Aluminum, elemental	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)	1 mg/m <sup>3</sup> (respirable fraction)
Propane	1000 ppm; 1800 mg/m <sup>3</sup>	1000 ppm
Stoddard solvent	2900 mg/m <sup>3</sup> ; 500 ppm	100 ppm
Isobutane	Not available.	Not available.
Sulfonic acids, petroleum, calcium salts	Not available.	Not available.



## SAFETY DATA SHEET

### 8.2 EXPOSURE CONTROLS

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### 8.3 INDIVIDUAL PROTECTIVE MEASURES

**Personal Protective Equipment:**

**Eye/Face Protection:** Wear eye protection.

**Skin Protection:**

**Hand Protection:** Wear chemically resistant protective gloves.

**Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Not available.
<b>Color:</b>	Silver.
<b>Odor:</b>	Not available.
<b>Odor Threshold:</b>	Not available.
<b>Physical State:</b>	Gas/Pressurized Liquid.
<b>pH:</b>	Not available.
<b>Melting Point/Freezing Point:</b>	Not available.
<b>Initial Boiling Point and Boiling Range:</b>	Not available.
<b>Flash Point:</b>	Not available.
<b>Evaporation Rate:</b>	Not available.
<b>Flammability:</b>	Flammable.
<b>Lower Flammability/Explosive Limit:</b>	Not available.
<b>Upper Flammability/Explosive Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.
<b>Relative Density/Specific Gravity:</b>	Not available.
<b>Solubility:</b>	Not available.
<b>Partition coefficient: n-octanol/water:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Decomposition Temperature:</b>	Not available.



## SAFETY DATA SHEET

**Viscosity:** Not available.  
**Explosive Properties:** Not available.  
**Oxidizing Properties:** Not available.

### Section 10: STABILITY AND REACTIVITY

#### 10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

#### 10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

#### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

#### 10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Sources of ignition.

#### 10.5 INCOMPATIBLE MATERIALS

Oxidizers.

#### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

### Section 11: TOXICOLOGICAL INFORMATION

#### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

**Likely Routes of Exposure:** Skin contact, skin absorption, eye contact, inhalation, and ingestion.

**Symptoms related to physical/chemical/toxicological characteristics:**

**Eye:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.

**Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.

**Acute Toxicity:**

Ingredient	LC50	LD50
Acetone	Inhalation 50100 mg/m <sup>3</sup> 8h, rat	Oral 5800 mg/kg, rat
Aluminum, elemental	Not available.	Oral > 10000 mg/kg, rat
Propane	Inhalation 658 mg/L 4h, rat	Not available.
Stoddard solvent	Not available.	Not available.
Isobutane	Inhalation 658 mg/L 4h, rat	Not available.
Sulfonic acids, petroleum, calcium salts	Not available.	Oral >5000 mg/kg, rat Dermal >4000 mg/kg, rabbit

**SAFETY DATA SHEET**

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
> 5 mg/L 4h, rat	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit

  

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Acetone	G-A4
Aluminum, elemental	G-A4
Propane	Not listed.
Stoddard solvent	Not listed.
Isobutane	Not listed.
Sulfonic acids, petroleum, calcium salts	Not listed.

\* See Section 15 for more information.

**11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE**

<b>Skin Corrosion/Irritation:</b>	May cause skin irritation.
<b>Serious Eye Damage/Irritation:</b>	Causes serious eye irritation.
<b>Respiratory Sensitization:</b>	Based on available data, the classification criteria are not met.
<b>Skin Sensitization:</b>	May cause an allergic skin reaction.
<b>STOT-Single Exposure:</b>	May cause drowsiness or dizziness.
<b>Chronic Health Effects:</b>	
<b>Carcinogenicity:</b>	Based on available data, the classification criteria are not met.
<b>Germ Cell Mutagenicity:</b>	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity:</b>	
<b>Developmental:</b>	Based on available data, the classification criteria are not met.
<b>Teratogenicity:</b>	Based on available data, the classification criteria are not met.
<b>Embryotoxicity:</b>	Based on available data, the classification criteria are not met.
<b>Fertility:</b>	Based on available data, the classification criteria are not met.
<b>STOT-Repeated Exposure:</b>	Based on available data, the classification criteria are not met.
<b>Aspiration Hazard:</b>	Based on available data, the classification criteria are not met.
<b>Toxicologically Synergistic Materials:</b>	Not available.
<b>Other Information:</b>	Not available.

**Section 12: ECOLOGICAL INFORMATION****12.1 ECOTOXICITY**

**Acute/Chronic Toxicity:** May cause long-term adverse effects in the aquatic environment.

**12.2 PERSISTENCE AND DEGRADABILITY**

Not available.

**12.3 BIOACCUMULATIVE POTENTIAL**

**Bioaccumulation:** Not available.



## SAFETY DATA SHEET

### 12.4 MOBILITY IN SOIL

Not available.

### 12.5 OTHER ADVERSE EFFECTS

Not available.

---

### Section 13: DISPOSAL CONSIDERATIONS

---

#### 13.1 WASTE TREATMENT METHODS

**Disposal Method:** This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

**Other disposal recommendations:** Not available.

---

### Section 14: TRANSPORT INFORMATION

---

#### 14.1 UN NUMBER

DOT	TDG
UN1950	UN1950

#### 14.2 UN PROPER SHIPPING NAME

DOT	TDG
Aerosols, flammable	Aerosols, flammable

#### 14.3 TRANSPORT HAZARD CLASS (ES)

DOT	TDG
2.1	2.1

#### 14.4 PACKING GROUP

DOT	TDG
Not applicable.	Not applicable.

#### 14.5 ENVIRONMENTAL HAZARDS

Not available.

#### 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

#### 14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

---

### Section 15: REGULATORY INFORMATION

---

#### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012





## SAFETY DATA SHEET

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Acetone	Not listed.	Not listed.	5,000	Not listed.
Aluminum, elemental	Not listed.	Not listed.	Not listed.	313 (fume or dust)
Propane	Not listed.	Not listed.	Not listed.	Not listed.
Stoddard solvent	Not listed.	Not listed.	Not listed.	Not listed.
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Sulfonic acids, petroleum, calcium salts	Not listed.	Not listed.	Not listed.	Not listed.

### State Regulations

**California Proposition 65:**

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Global Inventories:**

Ingredient	Canada DSL/NDSL	USA TSCA
Acetone	DSL	Yes.
Aluminum, elemental	DSL	Yes.
Propane	DSL	Yes.
Stoddard solvent	DSL	Yes.
Isobutane	DSL	Yes.
Sulfonic acids, petroleum, calcium salts	DSL	Yes.

### NFPA National Fire Protection Association:

<b>Health:</b>	2
<b>Fire:</b>	4
<b>Reactivity:</b>	0

### HMIS-Hazardous Materials Identification System

<b>Health:</b>	2*
<b>Fire:</b>	4
<b>Physical Hazard:</b>	0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

**SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:**

- CP65**      **California Proposition 65**
- OSHA (O)**    **Occupational Safety and Health Administration.**
- ACGIH (G)**   **American Conference of Governmental Industrial Hygienists.**  
 A1 - Confirmed human carcinogen.  
 A2 - Suspected human carcinogen.  
 A3 - Animal carcinogen.  
 A4 - Not classifiable as a human carcinogen.  
 A5 - Not suspected as a human carcinogen.



## SAFETY DATA SHEET

### IARC (I)

#### International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

### NTP (N)

#### National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

---

### Section 16: OTHER INFORMATION

---

**Date of Preparation:** April 1, 2015

**Expiry Date:** April 1, 2018

**Version:** 1.0

**Revision Date:** April 1, 2015

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Prepared by:** Nexreg Compliance Inc.  
Phone: (519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)

**Prepared for:** International Lubricants, Inc.

## End of Safety Data Sheet