

SAE 50 FULL SYNTHETIC MANUAL HD TRANSMISSION FLUID

Full Synthetic for Extended Drain Intervals Outstanding Low & High Temperature Performance Non EP Manual Transmission Fluid

DESCRIPTION:

SynGard® Synthetic Heavy Duty Manual Transmission Fluid Sae 50 Is designed for use in Manual Transmissions of Heavy Duty Trucks and other Machinery Where Non-EP SAE 50 OILS ARE RECOMMENDED. IT IS ALSO RECOMMENDED FOR OIL LUBRICATED WHEEL BEARINGS ON HEAVY DUTY TRUCKS AND TRAILERS. THIS PRODUCT IS SUITABLE FOR USE IN EXTENDED DRAIN INTERVALS PER MANUFACTURER'S RECOMMENDATIONS.

SynGard® Synthetic Heavy Duty Manual Transmission Fluid Sae 50 is recommended for use in Heavy Duty Manual Transmissions used in Over-The-Road Trucks and Other EQUIPMENT WHERE NON - EP SAE 50 TRANSMISSION FLUIDS ARE RECOMMENDED. SYNGARD SAE 50 UTILIZES A SPECIAL ADDITIVE PACKAGE WHICH DOES NOT USE SULPHUR EP ADDITIVES ALLOWING FOR LONG SERVICE LIFE FOR TRANSMISSION FLUID COOLING SYSTEMS AND OTHER TRANSMISSION COMPONENTS.

BENEFITS:

- EXTENDED DRAIN INTERVALS PER MANUFACTURER'S RECOMMENDATIONS FOR SYNTHETIC LUBRICANTS
- SYNTHETIC BASESTOCKS MAXIMIZE OXIDATION RESISTANCE
 GREATER FILM STRENGTH AT HIGH OPERATING TEMPERATURES
- REDUCED WEAR AT START UP AND EASE OF OPERATION EVEN IN ARCTIC CONDITIONS
- OEM APPROVED EP ADDITIVE SYSTEM PROTECTS GEARS UNDER HEAVY LOADS
- OUTSTANDING RESISTANCE TO FOAMING
- PREVENTS CORROSION OF COPPER AND BRASS

APPLICATIONS:

- · HEAVY DUTY MANUAL TRANSMISSIONS IN OVER-THE-ROAD TRUCKS
- OIL LUBRICATED WHEEL BEARINGS WHERE SAE 50 FLUIDS ARE RECOMMENDED
- OTHER TRANSMISSION APPLICATIONS WHERE NON EP SAE 50 OILS ARE RECOMMENDED.

PERFORMANCE LEVELS:

API SAE MT-1 "CLEAN GEAR"

TYPICAL PROPERTIES		METHOD		RESULT				
AE VISCOSITY GRADE			J300	50				
PECIFIC GRAVITY			D1298	0.8478				
ISCOSITY cSt @ 40°C			D445	113.9				
ISCOSITY cSt @ 100°C			D445	18.9				
ISCOSITY Cp @ -40°C			D2983	134,000				
ISCOSITY INDEX			D2270	187				
OUR POINT °C (°F)			D97	-12(-11)				
LASH POINT, COC °C (°F)			D92	250(482)				
STOCK NO.	PRODUCT	SIZE	UNIT UPC	CASE UPC	CASE	CUBE	WGT.	FULL PALLET
584982 SynGard™	'FS SAE 50 TRANS FLUID	1/35 #	0 72372 31027 8				38 LBS	42 EA 1448 LBS



MARTIN LUBRICANTS

 DIVISION OF MARTIN OPERATING PARTNERSHIP, LP

 AR 71762
 2727 ROE LANE, KANSAS CITY, KS 66103

 DNE: 870 881-8700
 FAX: 870 864-8661
 484 E. 6TH ST., SMACKOVER, AR 71762
PHONE: 870 881-8700