



Trade name: Dry Charge Battery  
Print date: May 13, 2015

Page 1 of 20

Revision date: May 13, 2015

---

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**1.1.1. Trade name/designation**  
Dry Charge Battery

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**1.2.1. Relevant identified uses**  
Power sport batteries

**1.2.2. Uses advised against**  
Any other not listed above

### 1.3. Details of the supplier

**1.3.1. Supplier:**  
GS Battery (U.S.A) Inc.

**1.3.2. Website**  
[www.gsbattery.com](http://www.gsbattery.com)

**1.3.3. Information contact**  
1150 Northmeadow Parkway  
STE110  
Roswell  
GA 30076-3886

**1.3.4. National contact**  
GS Battery (U.S.A.) Inc: (678) 762-4818

### 1.4. Emergency Telephone Number

CHEMTREC: Domestic (800)424-9300  
International: 1(703)527-3887

## SECTION 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture:

**2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**  
Class 13: Non-flammable solids in non-flammable package

Trade name: Dry Charge Battery  
Print date: May 13, 2015

Page 2 of 20

Revision date: May 13, 2015

### 2.1.2 Classification according to 67/548/EEC or 1999/45/EC

Xi: Irritating

## 2.2. Label elements

### 2.2.1 Labeling according to Regulation (EC) No 1272/2008

*Product identifier:*


Dry Charge Battery

*Hazard pictograms:*



Xi: Irritating

*NFPA:*



*WHMIS:*

Not Regulated

*Signal word:*

CAUTION

*Hazard statements:*

May be harmful in contact with skin

Causes skin irritation

May cause respiratory irritation

Warning! Contains lead

*Precautionary statements:*

Keep out of reach of children.

Keep containers tightly closed.

Keep away from heat, sparks, and open flame while charging batteries.

## 2.3. Other hazards

Adverse human health effects and symptoms:

*Inhalation:* (Acute): Under normal conditions of use, no health effects are expected.

(Chronic): Repeated and prolonged exposure may cause irritation.



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 3 of 20

*Skin:* (Acute): Under normal conditions of use, no health effects are expected.  
(Chronic): No data available

*Eye:* (Acute): Under normal conditions of use, no health effects are expected. Exposure to dust may cause irritation.  
(Chronic): no data available.

*Ingestion:* (Acute): Under normal conditions of use, no health effects are expected. Lead ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping.  
(Chronic): no data available.

**Carcinogenic Effects:**

Material is an article. No health effects are expected related to normal use of this product as sold. Material does contain components that exhibit carcinogenic effects.

Symptoms of lead toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability. Lead absorption may cause nausea, weight loss, abdominal spasms, and pain in arms, legs and joints.

Effects of chronic lead exposure may include central nervous system (CNS) damage, kidney dysfunction, anemia, neuropathy particularly of the motor nerves with wrist drop, and potential reproductive effects.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****3.1. Description of the mixture:**

CAS No	EC No	% [weight]	Name	WHMIS Classifications	Classification according to CLP (1272/2008)
7439-92-1	231-100-4	89-92%	Lead	D2A	Xn, N, T; R20/22, R33, R50, R50/53, R53, R61, R62; Repr. Cat. 1, Repr. Cat. 3; S53, S45, S60, S61 except those specified elsewhere in the annex
7440-36-0	231-146-5	0.2%	Antimony	Uncontrolled product according to WHMIS classification criteria; D1B (powder)	Xn, N; R20/22, R51/53; S2, S61 except tetroxide, pentoxide, trisulphide, pentasulphide, and those specified elsewhere in the annex
7440-31-5	231-141-8	0.006%	Tin	Uncontrolled product according to WHMIS classification criteria	Not Listed
7440-38-2	231-148-6	0.003%	Arsenic	D1A, D2A	T, N; R23/25, R50/53; S1/2, S20/21, S28, S45, S60, S61
7440-70-2	231-179-5	0.002%	Calcium	B6, E	F; R15; S2, S8, S24/25, S43

Case material composes 5-6% of the article. Case material includes the following components: 1-Propene, homopolymer (9003-07-0); Polystyrene (9003-53-6); Acrylonitrile, polymer with styrene (9003-54-7); Acrylonitrile, polymer with 1,3-butadiene and styrene (9003-56-9); Styrene polymer with 1,3-butadiene and styrene (9003-56-9); Styrene polymer with 1,3-butadiene (Kraton) (9003-55-8); Ethylene, chloro-, polymer (9003-86-2); Hard Rubber; Polycarbonate; Polyethylene.

**SECTION 4. FIRST AID MEASURES****4.1. Description of first aid measures****4.1.1 Eye contact:**

First aid is not expected to be necessary if material is used under ordinary conditions and as recommended.



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 4 of 20

---

If contact with material occurs flush eyes with water. If signs/symptoms develop, get medical attention.

**4.1.2 Inhalation:**

First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If signs/symptoms develop, move person to fresh air.

**4.1.3 Skin contact:**

First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. Wash skin with soap and water. If signs/symptoms develop, get medical attention.

**4.1.4 Ingestion:**

First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If ingested consult physician immediately.

**4.1.5 Self-protection of the first aider:**

If artificial respiration is required use a pocket mask equipped with a one-way valve or other proper respiratory medical device.

## SECTION 5. FIREFIGHTING MEASURES

**5.1. Extinguishing media:****5.1.1 Suitable extinguishing media:**

CO<sub>2</sub>, dry chemical or foam

**5.1.2 Unsuitable extinguishing media:**

Avoid using water

**5.2. Special hazards arising from the substance or mixture****5.2.1 Hazardous combustion products:**

Lead portion of battery will likely produce toxic metal fume, vapor or dust.

**5.3. Advice for fire-fighters:**

Keep sparks or other sources of ignition away from batteries. Do not allow metallic materials to simultaneously contact negative and positive terminals of cells and batteries.

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

**5.4. Additional information:**

Material itself is non-combustible although in fire situations will likely produce toxic metal fume, vapor or dust.



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 5 of 20

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

No special precautions expected to be necessary if material is used under ordinary conditions and as recommended. Avoid contact of lead with skin.

#### 6.1.1 For non-emergency personnel

Protective equipment: Wear chemical gloves

#### 6.1.2 For emergency responders

No emergency procedures are expected to be necessary if material is used under ordinary conditions as recommended. Use normal clean up procedures.

Personal protective equipment:

Wear chemical gloves, goggles, acid resistant clothing and boots, respirator if insufficient ventilation.

### 6.2. Environmental precautions:

Prevent entry into waterways, sewers, basements or confined areas. Runoff from fire control and dilution water may be toxic and corrosive and may cause adverse environmental impacts.

### 6.3. Methods and material for containment and cleaning up

#### 6.3.1 For containment:

Lead dust should be vacuumed or wet swept into a D.O.T. approved container. Use controls that minimize fugitive emissions. Do not use compressed air.

#### 6.3.2 For cleaning up:

Contact local and/or state officials for proper disposal requirements.

## SECTION 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### 7.1.1 Protective measures:

Handle batteries cautiously. Do not tip to avoid spills (if filled with electrolyte). Avoid contact with internal components. Wear protective clothing when filling or handling batteries. Follow manufacturer's instructions for installation and service. Do not allow conductive material to touch the battery terminals. Short circuit may occur and cause battery failure and fire.

#### 7.1.2 Advice on general occupational hygiene

Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Eye-wash stations and safety showers should be provided with unlimited water supply. Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

Avoid contact with strong bases, acids, combustible organic materials, halides, halogenates, potassium



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

nitrate, permanganate, peroxides, nascent hydrogen, reducing agents and water.

Technical measures and storage conditions:

Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Batteries should be stored under roof for protection against adverse weather conditions. Place cardboard between layers of stacked batteries to avoid damage and short circuits. Store batteries on an impervious surface. Storage class:

Class 13: Non-flammable solids in non-flammable package

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### 8.1.1 Occupational exposure limits:

Limit value type (County of origin)	Sub- stance name	EC-No.	CAS-No	Limit value	Monitoring and observa- tion processes
TWA (ACGIH USA) STEL (CA-ON) TWA (CA- ON) TWA (CA-QU) STEL (CH) TWA (CH) TWA (FI) Biological Limit Value (FI) TWA (ME) Ceiling (NIOSH)	Arsenic		7440-38-2	0.01 mg/m <sup>3</sup> 50 µg/m <sup>3</sup> 10 µg/m <sup>3</sup> 1.1 mg/m <sup>3</sup> 1.2 mg/m <sup>3</sup> 0.01 mg/m <sup>3</sup> 0.01 mg/m <sup>3</sup> 70 nmol/L 1.1 mg/m <sup>3</sup> 1.2 mg/m <sup>3</sup>	Designated substance regulation  Medium: Urine Time: end of shift at end of workweek
TWA(ACGIH USA) TWA (CA) TWA (FI) STEL(ME) TWA (ME) TWA (NIOSH USA)	Tin	231-141-8	7440-31-5	2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 4 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup>	
TWA(ACGIH USA) TWA (CA) TWA (FI) STEL(ME) TWA (ME) TWA (NIOSH USA)	Tin	231-141-8	7440-31-5	2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 4 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 2 mg/m <sup>3</sup>	
TWA (ACGIH) TWA(CA ON) TWA(CA QU) STEL(CH) TWA(CH) TWA(FI) Biological Limit Value (FI) TWA(JP) TWA(ME) TWA(NIOSH) TWA(OSHA)	Lead	231-100-4	7439-92-1	0.05 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 0.15 (0.09) mg/m <sup>3</sup> 0.05(0.03)mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 1.4 umol/L 0.1 mg/m <sup>3</sup> 0.15 mg/m <sup>3</sup> 0.05 mg/m <sup>3</sup> 50 ug/m <sup>3</sup>	Designated substance regulation Dust (fume) Dust (fume) Dust As Pb, dust and fume



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 7 of 20

## 8.2. Exposure controls

### 8.2.1 *Appropriate engineering controls:*

Store and charge in a well-ventilated area. General dilution ventilation is acceptable.

### 8.2.2 *Personal protective equipment:*

#### 8.2.2.1 *Pictograms:*



#### 8.2.2.2 *Eye/Face protection:*

Wear protective eyewear (goggles, face shield or safety glasses with side shields).

#### 8.2.2.3 *Skin protection:*

Wear appropriate gloves.

No skin protection is ordinarily required under normal conditions of use. In accordance with industrial hygiene practices, if contact with leaking battery is expected precautions should be taken to avoid skin contact. Under severe exposure or emergency conditions, wear acid-resistant clothing and boots.

#### 8.2.2.4 *Respiratory protection:*

In case of insufficient ventilation, wear suitable respiratory equipment.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### 9.1.1. *Appearance*

Physical state: Solid      Color: Bluish gray metal      Odor: Odorless      Odor threshold: No Data

#### 9.1.2. *Safety relevant basic data*

pH (20 °C): No Data

Melting point/range(°C): 252.2222-360

Initial boiling point/range (°C): 1380

Decomposition temperature (°C): No Data

Flash point (°C): No Data

Ignition temperature (°C): No Data

Vapor pressure (hPa): No Data

Vapor density (air = 1): No Data

Density (g/cm<sup>3</sup>): 599.3267-705.4575 lbs/ft<sup>3</sup>

Bulk density (kg/m<sup>3</sup>): No Data

Specific Gravity/Relative Density (Water=1): 9.6-11.3

Water solubility (20°C in g/l): No Data

Solubility(ies): No Data

Partition coefficient: No Data



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 8 of 20

---

N-Octanol/Water (log Po/w): No Data

Viscosity, dynamic (mPa s): No Data

**9.2. Other safety information:**

Properties of explosive atmospheres (mixtures):

Gases and vapors: No Data

Dusts: No Data

Physical chemical properties of nanoparticles: No Data

Limiting oxygen concentration: No Data

Bulk density: No Data

Solubility in different media: No Data

Stability in organic solvents and identity of relevant degradation products: No Data

Evaporation rate: No Data

Conductivity: No Data

Surface tension: No Data

Dissociation constant in water (pKa): No Data

Oxidation-reduction Potential: No Data

Fat solubility (solvent – oil to be specified): No Data

Critical temperature: No Data

**SECTION 10. STABILITY AND REACTIVITY****10.1. Reactivity:**

Not reactive

**10.2. Chemical stability:**

Stable under normal temperatures and pressures

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid:**

Prolonged overcharge, sources of ignition.

**10.5. Incompatible materials:**

Avoid contact with strong bases, acids, combustible organic materials, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, reducing agents and water.

**10.6. Hazardous decomposition products:**

Lead compounds exposed to high temperatures will likely produce toxic metal fume, vapor or dust; contact with strong acid/base or presence of nascent hydrogen may generate highly toxic arsine gas.





Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects:

Lead (7439-92-1)	Effect dose / Concentration	Species	Method	Time
Acute oral toxicity	155 mg/kg	Human	LDLo	
Acute oral toxicity	1050 ug/kg	Rat	TDLo	30 Weeks(int.)
Acute inhalative toxicity (dust/mist)	0.011 mg/m <sup>3</sup>	Human	LCLo	26 Weeks (int.)
Mutagen	23 ug/m <sup>3</sup>	Rat	Inhalation	16 Weeks
Reproductive	790 mg/kg	Rat	TDLo (Oral)	
Reproductive	3 mg/m <sup>3</sup>	Rat	TCLo (Inhalation)	1-21 Days preg.
Antimony (7440-36-0)	Effect dose / Concentration	Species	Method	Time
Acute oral toxicity	100 mg/kg	Rat	LD50	
Acute inhalative toxicity (dust/mist)	13.5 mg/m <sup>3</sup>	Human	LCLo	4 Hours
Tumorigen/Carcinogen	50 mg/m <sup>3</sup>	Rat	TCLo	7 hours 52 weeks (int.)
Arsenic (7440-38-2)	Effect dose / Concentration	Species	Method	Time
Acute oral toxicity	763 mg/kg	Rat	LD50	
Acute oral toxicity	5 mg/kg	Rat	LDLo	
Mutagen	0.211 mg/L	Human	Oral	15 Years
Reproductive	605 ug/kg	Rat	TDLo	35 weeks preg.

### 11.2. Other information:

#### 11.2.1 Carcinogenic Effects:

Material is an article. No health effects are expected related to normal use of this product as sold. Material does contain components that exhibit carcinogenic effects.

Carcinogenic Effects			
	CAS	IARC	NTP
Lead	7439-92-1	Group 2A-Probable Carcinogen	Reasonably anticipated to be human carcinogen

#### 11.2.2 Routes of exposure:

##### 11.2.2.1 In case of ingestion:

Acute (Immediate): Under normal conditions of use, no health effects are expected. Lead ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping.

Chronic (Delayed): No data available

##### 11.2.2.2 In case of skin contact:

Acute (Immediate): Under normal conditions of use, no health effects are expected.

Chronic (Delayed): No data available

##### 11.2.2.3 In case of inhalation:

Acute (Immediate): Under normal conditions of use, no health effects are expected. Contents of an open battery can cause respiratory irritation.

Chronic (Delayed): Repeated and prolonged exposure may cause irritation.



Trade name: Dry Charge Battery  
Print date: May 13, 2015

Revision date: May 13, 2015

*11.2.2.4 In case of eye contact:*

Acute (Immediate): Under normal conditions of use, no health effects are expected. Exposure to dust may cause irritation.

Chronic (Delayed): No data available

**SECTION 12. ECOLOGICAL INFORMATION**

**12.1. Toxicity:**

Aquatic toxicity

*12.1.1 Substances*

Acute (short-term) toxicity: No Data

Effect dose	Exposure time	Species	Method	Evaluation	Remark

Persistence/Degradability: Lead is persistent in soils and sediments.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment method**

*13.1.1 Product/packaging disposal:*

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

*13.1.2 Waste codes/waste designations according to EWC/AVV:*

16 06 05

**13.2. Additional information:**

Any waste marked with an asterisk (\*) is considered as a hazardous waste pursuant to Directive 91/689/EEC on hazardous waste, and subject to the provisions of that Directive unless Article 1(5) of that Directive applies.

**SECTION 14. TRANSPORT INFORMATION**

The transportation of dry batteries is Not Regulated

**14.1. Land transport (CFR 49: DOT)**

This product is not hazardous as defined by 49CFR 172.101 by the U.S. Department of Transportation

UN-No:

Proper shipping name:

Class(es):

Packing group:



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 11 of 20

---

Hazard label(s):

Special provision(s)/Exceptions:

**14.2. Land transport (ADR/RID/GGVSEB):**

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

UN-No:

Proper shipping name:

Class(es):

Classification Code:

Packing group:

Hazard label(s):

Special provision(s):

Land transport (TDG):

This product is not classified as dangerous goods by the TDG standards UN- No:

Proper shipping name:

Class(es):

Packing group:

Hazard label(s):

Special provision(s):

**14.3. Sea transport (IMDG-Code/GGVSee):**

This product is not classified as dangerous goods by the IMO UN No:

Proper shipping name:

Class(es):

Packing group:

Marine Pollutant:

Special provision(s):

**14.4. Air transport (ICAO-IATA/DGR):**

This product is not classified as dangerous goods by the International Air Transport Association (IATA) or the ICAO.

UN No:

Proper shipping name:

Class(es):

Packing group:

Special provision(s):



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 12 of 20

## SECTION 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the mixture

#### 15.1.1 National regulations (Canada):

##### WHMIS Classification:

This product does not meet the classification criteria of the Controlled Products Regulations.

*This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Controlled Products Regulations.*

##### Canada DSL:

The following substances are listed on the Canadian DSL:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

##### Canada NDSL:

None of the components on this SDS are listed on the Canadian NDSL:

##### WHMIS: Ingredient Disclosure List

Substance	CAS No.	Wt %	Disclosure Limit %
Calcium	7440-70-2	0.002%	Not Listed
Lead	7439-92-1	89-92%	0.1%
Lead as Lead compounds		89-92%	Not Listed
Lead as Lead, inorganic compounds		89-92%	1%
Tin	7440-31-5	0.006%	1%
Antimony	7440-36-0	0.2 %	1%
Antimony as Antimony compounds		0.2%	1%
Arsenic	7440-38-2	0.003%	0.1%

##### CEPA: Priority Substances List

Substance	CAS No.	Wt %	Status
Calcium	7440-70-2	0.002%	Not Listed
Lead	7439-92-1	89-92%	Not Listed
Lead as Lead compounds		89-92%	Not Listed
Lead as Lead, inorganic compounds		89-92%	Not Listed
Tin	7440-31-5	0.006%	Not Listed
Antimony	7440-36-0	0.2 %	Not Listed
Antimony as Antimony compounds		0.2%	Not Listed
Arsenic	7440-38-2	0.003%	Not Listed

#### 15.1.2 National regulations (China):

The following components are listed on the Inventory list for China:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

#### 15.1.3 National regulations (European Union):

Classification:

Xi

Risk Phrases:

R36, R38

Safety Phrases:

S1/2, S26, S30, S45



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 13 of 20

The following components are listed on the EU EINECS:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

None of the above mentioned components are listed on the EU ELNICS.

#### CLP (1272/2008) Concentration Limits

Substance	CAS	WT %	Concentration Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	2.5% ≤ C: Repr. Cat. 3; R62 1% ≤ C: Xn; R20/22 0.5% ≤ C: R33
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	0.25% ≤ C: Xn; R20/22
Arsenic	7440-38-2	0.003	Not Listed

Substance	CAS	WT %	Substances and Preparations
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	A, E, 1 (except those specified elsewhere in the annex)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	A, 1 (except tetroxide, pentoxide, trisulphide, pentasulphide and those specified elsewhere in the annex)
Arsenic	7440-38-2	0.003	Not Listed

#### Germany

##### Lead Restrictions:

Lead concentration in the blood above 300 µg/L in male employees and 100 µg/L in female employees requires additional training for personal hygiene and vigilance. Lead concentration in the blood above 350 µg/L in male employees and 200 µg/L in female employees requires additional training for personal hygiene and vigilance; Lead concentration in the blood above 400 µg/L in male employees and 300 µg/L in female employees requires additional training for personal hygiene and vigilance; See TRGS 505 for detailed regulations regarding lead and lead compounds.

Employment restrictions for employees below the age of 18 years; Employment restrictions for pregnant or breastfeeding women; Prohibited for use at home based workplaces; Restrictions apply for use of lead compounds in packaging material, drinking water systems, cars, electrical and electronical devices; See TRGS 505 for detailed regulations regarding lead and lead compounds.



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Emission Limits for Inorganic Dusts

Substance	CAS	WT %	Emission Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	2.5 g/h Mass flow (class II); 0.5 mg/m <sup>3</sup> mass concentration (Class II)
Lead as Lead compounds		89-92	2.5 m/h Mass flow (Class II, as Pb); 0.5 mg/m <sup>3</sup> Mass concentration (Class II, as Pb)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	5 g/h Mass flow (Class III); 1 mg/m <sup>3</sup> Mass concentration (Class III)
Antimony	7440-36-0	0.2	5 g/h Mass flow (Class III); 1 mg/m <sup>3</sup> Mass concentration (Class III)
Antimony as Antimony compounds		0.2	5 g/h Mass flow (Class III, as Sb); 1 mg/m <sup>3</sup> Mass concentration (Class III, as Sb)
Arsenic	7440-38-2	0.003	Not Listed

**15.1.4 National regulations (Japan):**

The following chemicals are on the Japanese ENCS:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.1% weight
Lead as Lead compounds		89-92	0.1% weight
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	0.1% weight

ISHL Prevention of Lead Poisoning

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

ISHL Notifiable Substances

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.1% weight
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	0.1% weight
Tin	7440-31-5	0.006	0.1% weight
Antimony	7440-36-0	0.2	0.1% weight
Antimony as Antimony compounds		0.2	0.1% weight
Arsenic	7440-38-2	0.003	0.1% weight



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

**Air Pollution Control Law: Emission Standards for Air Pollutants**

Substance	CAS	WT %	Emission Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	16-20 mg/Nm <sup>3</sup>
Lead as Lead compounds		89-92	16-20 mg/Nm <sup>3</sup>
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

**Pollutant Release Transfer Register (PRTR): Class 1 Substances**

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	304
Lead as Lead compounds		89-92	305 (Designated class 1 substance)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	31
Antimony as Antimony compounds		0.2	31
Arsenic	7440-38-2	0.003	332 (Designated class 1 substance)

**ISHL Working Environment Evaluation Standards: Administrative Control Levels**

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.05 mg/m <sup>3</sup> ACL
Lead as Lead compounds		89-92	0.05 mg/m <sup>3</sup> ACL (as Pb)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	0.003 mg/m <sup>3</sup> ACL

**15.1.5 National regulations (Korea):**

The following substances are listed on the Korean KECL:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

**15.1.6 National regulations (Mexico):**

Pollutant Release and Transfer Register: Reporting Emissions

Substance	CAS	WT %	Threshold Quantities
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	1 kg/yr TQ
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	1 kg/yr TQ



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 16 of 20

**15.1.7 National regulations (United States):**

The following substances are on the MA, NJ, and PA Right To Know Lists:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

The following substances are on the TSCA inventory:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

## OSHA: Specifically Regulated Chemicals

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	30 µg/m <sup>3</sup> Action Level (Poison, See 29 CFR 1910.1025); 50 µg/m <sup>3</sup> TWA
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	30 µg/m <sup>3</sup> Action Level (Poison, See 29 CFR 1910.1025, as Pb); 50 µg/m <sup>3</sup> TWA (as Pb)
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

## CAA: 1990 Hazardous Air Pollutants

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	(includes any unique chemical substance that contains Lead as part of its infrastructure)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	(includes any unique chemical substance that contains Antimony as part of its infrastructure)
Arsenic	7440-38-2	0.003	Not Listed





## SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH)

Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 17 of 20

## CERCLA/SARA

## Hazardous Substances and Their Reportable Quantities

Substance	CAS	WT %	Reportable Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	10 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 4.54 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	1 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 0.454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)

## Section 302 Extremely Hazardous Substances EPCRA RQs

Substance	CAS	WT %	Reportable Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

## Section 302 Extremely Hazardous Substances TPQs

Substance	CAS	WT %	Threshold Planning Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed



SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH)

Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

RCRA

Basis for Listing: Appendix VII

Substance	CAS	WT %	Basis
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Included in waste streams: F039, K021, K161, K177
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Included in waste streams: F032, F034, F035, F039, K031, K060, K084, K101, K102, K161, K171, K172, K176

D Series Wastes: Max Concentration of Contaminants for the Toxic Characteristic

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	5.0 mg/L
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	5.0 mg/L

Hazardous Constituents: Appendix VIII to 40 CFR 261

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Hazardous constituent – no waste number
Lead as Lead compounds		89-92	Hazardous constituent – no waste number
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Hazardous constituent – no waste number
Antimony as Antimony compounds		0.2	Hazardous constituent – no waste number
Arsenic	7440-38-2	0.003	Hazardous constituent – no waste number



SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH)

Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

California: California Proposition 65

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Carcinogen(initial date 10/1/92); developmental toxicity(initial date 2/27/87); 0.5 µg/day(Maximum Allowable Dose Level); 15 µg/day oral(No Significant Risk Level); female reproductive toxicity(initial date 2/27/87); male reproductive toxicity(initial date 2/27/87)
Lead as Lead compounds		89-92	Carcinogen(initial date 10/1/92)
Lead as Lead, inorganic compounds		89-92	Developmental toxicity(initial date 2/27/87)
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	0.06µg/day inhalation(No Significant Risk Level); 10µg/day except inhalation(No Significant Risk Level)

Pennsylvania

Environmental Hazard list

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	
Lead as Lead compounds		89-92	
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	
Antimony as Antimony compounds		0.2	
Arsenic	7440-38-2	0.003	

Special hazardous Substances

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	

Rhode Island: Hazardous Substances List

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Flammable
Lead	7439-92-1	89-92	Toxic (dust and fume)
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Toxic
Antimony	7440-36-0	0.2	Toxic
Antimony as Antimony compounds		0.2	Toxic
Arsenic	7440-38-2	0.003	Toxic; Carcinogen



Trade name: Dry Charge Battery

Print date: May 13, 2015

Revision date: May 13, 2015

Page 20 of 20

---

## SECTION 16. OTHER INFORMATION

### 16.1. Relevant R-, H- and EUH-phrases (number and full text):

#### *Hazard Abbreviations:*

Xn: Harmful

Xi: Irritant

C: Corrosive

#### *Risk Phrases:*

R35: Causes severe burns

R36: Irritating to eyes R38: Irritating to skin **Safety Phrases:**

S1/2: Keep locked up and out of the reach of children

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S30: Never add water to this product

S45: In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)

#### *Hazard statements:*

H314: Causes severe skin burns and eye damage

H315: Causes skin irritation

H335: May cause respiratory irritation

#### *Precautionary statements:*

P102: Keep out of reach of children.

P233: Keep containers tightly closed.

P210: Keep away from heat, sparks, and open flame while charging batteries.

### 16.2. Further information:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Yuasa, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, GS Battery (U.S.A.) Inc assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.