

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

1 Identification

- **Product identifier**
- **Trade name:** Buffing Solution (Rubber Cleaner)
- **Other means of identification:** NAPA Part Numbers: 765-1322
- **Recommended use and restriction on use**
- **Recommended use:** Cleaner solvent
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure.
Route of exposure: Inhalation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 1)

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements:**










- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves and eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P314 Get medical advice/attention if you feel unwell.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

110-54-3	n-hexane	 Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336  Eye Irrit. 2B, H320	25-50%
142-82-5	Heptane	 Flam. Liq. 2, H225  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
67-64-1	Acetone	 Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	10-25%

· **Additional information:** For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 2)

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

- **Most important symptoms and effects, both acute and delayed:**

Headache

Breathing difficulty

Coughing, dizziness, if inhaled.

Irritant to skin and mucous membranes.

Causes eye irritation.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Disorientation

- **Danger:**

Danger of impaired breathing.

Vapors may cause drowsiness and dizziness.

Suspected of damaging fertility or the unborn child.

Danger of disturbed cardiac rhythm.

Danger of convulsion.

Possible risk of irreversible effects.

- **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information:**

Eliminate all ignition sources if safe to do so.

Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 3)

- **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

- **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up**

Allow to evaporate.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

Rags, metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed metal container rated for flammable waste.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

Fumes can combine with air to form an explosive mixture.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

110-54-3 n-hexane

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 4)

PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m ³ , 50 ppm
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE

142-82-5 Heptane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m ³ , 500 ppm Long-term value: 1635 mg/m ³ , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm
LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE

Ingredients with biological limit values:

110-54-3 n-hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis
-----------	---

67-64-1 Acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift
-----------	--

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 5)

Parameter: Acetone (nonspecific)

· Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Pregnant women should strictly avoid inhalation or skin contact.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Engineering controls:

Take precautionary measures against static discharge.

Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place.

· Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For spills, respiratory protection may be advisable.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Solvent resistant protective clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form: Liquid

Color: White

· Odor: Solvent-like

· Odor threshold: Not determined.

· pH-value: Not determined.

· Melting point/Melting range: Not determined.

· Boiling point/Boiling range: 82 °C (179.6 °F)

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 6)

· Flash point:	-15 °C (5 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	215 °C (419 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits Lower: Upper:	1.1 Vol % 13.0 Vol %
· Oxidizing properties:	Not determined.
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Density at 20 °C (68 °F):	0.76 g/cm ³ (6.34 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not determined.
· Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity Dynamic: Kinematic:	Not determined. Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Reacts violently with oxidizing agents.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Keep away from heat and direct sunlight.
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizing agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 7)

11 Toxicological information

· Information on toxicological effects

- **Acute toxicity:** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

142-82-5 Heptane

Oral	LD50	> 5000 mg/kg (rat)
Inhalative	LC50/4h	103 mg/l (rat)

· Primary irritant effect:

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Causes serious eye irritation.
- **Sensitization:** No sensitizing effects known.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity:** Based on available data, the classification criteria are not met.

- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.

- **STOT-single exposure:** May cause drowsiness or dizziness.

- **STOT-repeated exposure:**

May cause damage to the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

· Toxicity

- **Aquatic toxicity** Toxic for aquatic organisms

- **Persistence and degradability** Easily biodegradable

- **Bioaccumulative potential:** No relevant information available.

- **Mobility in soil:** No relevant information available.

· Additional ecological information

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- **Results of PBT and vPvB assessment**

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)




(Cont'd. of page 8)

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| · UN-Number | |
| · DOT, ADR/RID/ADN, IMDG, IATA | UN1993 |
| · UN proper shipping name | |
| · DOT, ADR/RID/ADN, IMDG, IATA | FLAMMABLE LIQUID, N.O.S. (HEXANES, HEPTANES) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 |
| · Label | 3 |
| · ADR/RID/ADN | |
|  | |
| · Class | 3 (F1) |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 |
| · Label | 3 |

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 9)

· **Packing group**

· DOT, ADR/RID/ADN, IMDG, IATA

II

· **Environmental hazards**

Product contains environmentally hazardous substances: n-hexane, Heptane

· **Marine pollutant:**



Yes

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E, S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· **IATA**

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 10)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3 | n-hexane

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

110-54-3 | n-hexane

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

110-54-3 | n-hexane

II

142-82-5 | Heptane

D

67-64-1 | Acetone

I

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 06, 2018

Revision: December 06, 2018

Trade name: Buffing Solution (Rubber Cleaner)

(Cont'd. of page 11)

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bio-accumulable, Toxic
vPvB: very Persistent and very Bioaccumulative
OSHA: Occupational Safety & Health Administration
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com