Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® Full Synthetic High Mileage SAE 10W-30

Motor Oil

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Motor Oil

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	, , ,
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	, , ,
1-800-TEAMVAL (1-800-832-6825)	Product Information
,	1-800-TEAMVAL (1-800-832-6825)
	,

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	6.039
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.366

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

In case of skin contact : Remove contaminated clothing. Wash exposed area with

soap and water. If symptoms persist, seek medical attention.

Launder clothing before reuse.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : If symptoms develop, move individual away from exposure

and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual

difficulty, seek medical attention.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave

individual unattended.

Most important symptoms and effects, both acute and delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally,

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Dry chemical

Carbon dioxide (CO2)

Water spray

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

nitrogen oxides (NOx)

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning

liquid.

Use water spray to cool fire exposed containers and

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

Special protective equipment for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Do not let product enter drains.

Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Other information : Comply with all applicable federal, state, and local regulations.

Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Containers of this material may be hazardous when emptied.

Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data

sheet must be observed.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Conditions for safe storage : Store in a cool, dry, ventilated area.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components with workplace c				
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
DISTILLATES (PETROLEUM),	64742-65-0	TWA	5 mg/m3	OSHA Z-1
SOLVENT-DEWAXED HEAVY			Mist	
PARAFFINIC				
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	

The identity and concentration of one or more component(s) is being withheld under business confidentiality.

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your

Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 626 °F / 330 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : 394 - 480 °F / 201 - 249 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 1.3333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Relative density : No data available

Density : 0.861 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Stable.

Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

: Inhalation Skin contact

Eye Contact

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

IngestionInhalation Skin absorption Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Distillates (Petroleum), Hydrotreated Heavy Paraffinic: May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

Toxicity to daphnia and other

aquatic invertebrates

: NOEC (Aquatic invertebrates): 10 mg/l

(Chronic toxicity)

Persistence and degradability

No data available

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Bioaccumulative potential

No data available **Mobility in soil** No data available **Other adverse effects**

No data available

Product:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG ROAD C

<u> </u>	
	Not dangerous goods

TDG RAIL C

IDG_KAIL_C	
	Not dangerous goods

TDG_INWT_C

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

Not danger	ous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

•	#IX_DO
	Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

,,,				
Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
TOLUENE	108-88-3	1000	*	

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
SULFUR DIOXIDE	7446-09-5	500	*
SULFUR DIOXIDE	7446-09-5		*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

California Prop 65 WARNING: This product contains a chemical known to the

State of California to cause birth defects or other reproductive

harm.

SULFUR DIOXIDE 7446-09-5

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : q (quantity restricted)

KECI : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)

PICCS : Not in compliance with the inventory

TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/22/2018



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 01/22/2018
	Print Date: 3/21/2018
	SDS Number: R0396488
NAPA® Full Synthetic High Mileage SAE 10W-30 Motor Oil	Version: 1.7
883576	

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System