

## Royal Purple Automatic Transmission Fluid

### Max ATF

Max ATF is a synthetic, high-performance automatic transmission fluid. Its low co-efficient of friction and high film strength dramatically reduce heat and wear. Additionally, Max ATF is more oxidation stable than other transmission fluids for a longer fluid life.

Automatic transmissions generate a great deal of heat and depend on the transmission fluid for cooling and protection. More than 90 percent of all automatic transmission failures are caused by overheating; a 20°F reduction in fluid temperature can double the life of the transmission (*Source: Perma Industries Inc*). Max ATF significantly reduces heat to extend the life of your transmission.

Max ATF is fully compatible and can be mixed with other automatic transmission fluids; however, for the best results drain or flush the current oil and then fill with Max ATF.

Max ATF is recommended for vehicles requiring any of these automatic transmission fluids.



|                          |                            |                           |
|--------------------------|----------------------------|---------------------------|
| Allison C-4              | GM Dexron-II               | Nissan Matic-J            |
| Allison TES-295          | GM Dexron-IID              | Nissan Matic-K            |
| Audi G-052-025-A2        | GM Dexron-IIIG & H         | Toyota Type T             |
| BMW LA2634               | Honda ATF-Z1 (except CV1s) | Toyota Type T-III         |
| BMW LT71141              | Hyundai SP-II & SP-III     | Toyota Type IV            |
| Chrysler ATF+, ATF+2     | JWS 3309                   | Voith 1161521& 1161540    |
| Chrysler ATF+2 Type 7176 | KIA SP-II & SP-III         | Voith 55.6335.32 (G607)   |
| Chrysler ATF+3           | MAN 339F                   | Voith H55.6336.33 (G1363) |
| Chrysler ATF+4           | Mercedes Benz 236.x        | VW TL52162                |
| Ford Mercon              | Mitsubishi Diamond SP-II   | ZF TE-ML 14B              |
| Ford Mercon V            | Mitsubishi Diamond SP-III  | ZF TE-ML 16L              |
| GM 9986195               | Nissan Matic-D             | ZF TE-ML 17C              |
| GM Dexron                |                            |                           |

Max ATF **IS NOT** recommended for any CVT applications or vehicles that require these transmission fluids: Ford Type F, Ford Mercon SP, GM Dexron VI, Mercedes Benz NAG-2, Toyota WS, Volvo 5 speed.