

Printing date 03/18/2004

Reviewed on 03/18/2004

1 Identification of substance

- **Product details**
- **Trade name:** Curil K2
- **Article number:** 532.215/534.501/534.714/036.129
- **Application of the substance / the preparation** Sealing compound
- **Manufacturer/Supplier:**
ElringKlinger AG
Max-Eyth-Straße 2
D-72581 Dettingen/Erms
- **Information department:** 2ZEW Tel.: ++49/(0)7123/724-253
- **Emergency information:** Tel.: ++49/(0)7123/724-0

2 Composition/Data on components

- **Chemical characterization**
- **Description:**
Castor oil derivative (modified with phenolic resin) solved in Ethanol.

· **Dangerous components:**

64-17-5 ethanol

F; R 11 25-50%

3 Hazards identification· **Hazard description:**

F Highly flammable

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Highly flammable.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 3
Reactivity = 1

· **WHMIS-ratings (scale 0 - 4)**

Health = 2
Fire = 3
REACTIVITY 1
Reactivity = 1

4 First aid measures

- **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 2)

Trade name: Curil K2

(Contd. of page 1)

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the material, its products of combustion or resulting gases:**
During heating or in case of fire poisonous gases are produced.
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information:** Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Pick up mechanically.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Dispose of the collected material according to regulations.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Use solvent-proof equipment.
Avoid contact with skin or eyes.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

64-17-5 ethanol

PEL 1900 mg/m³, 1000 ppm

REL 1900 mg/m³, 1000 ppm

TLV 1880 mg/m³, 1000 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.
Immediately remove all soiled and contaminated clothing.
Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.
Do not inhale gases / fumes / aerosols.

- **Breathing equipment:**

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A

- **Protection of hands:** Solvent resistant gloves

(Contd. on page 3)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Page 3/6

Printing date 03/18/2004

Reviewed on 03/18/2004

Trade name: Curil K2

(Contd. of page 2)

- **Material of gloves**
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing

9 Physical and chemical properties

· **General Information**

Form: Viscous
Color: Yellowbrown
Odor: Like alcohol

· **Change in condition**

Melting point/Melting range: Undetermined
Boiling point/Boiling range: 78°C (172°F)

· **Flash point:** 17°C (63°F)

· **Ignition temperature:** 425°C (797°F) (DIN 51794)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 3.5 Vol %
Upper: 15.0 Vol %

· **Vapor pressure at 20°C (68°F):** 58 mbar (prEN 13016-1)

· **Density at 20°C (68°F):** 1.04 g/cm³ (DIN 51757)

· **Solubility in / Miscibility with**

Water: Partly soluble.

· **Viscosity:**

Dynamic at 20°C (68°F): 1200 - 1800 mPas

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions**
Reacts with alkaline metals.
Reacts with earth alkaline metals.
Reacts with strong oxidizing agents.
- **Dangerous products of decomposition:**
Carbon monoxide and carbon dioxide
Irritant gases/vapors

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64-17-5 ethanol

Oral LD50 7060 mg/kg (rat)

Inhalative LC50/4 h 20000 mg/l (rat)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 4)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Page 4/6

Printing date 03/18/2004

Reviewed on 03/18/2004

Trade name: Curil K2

- Sensitization: No sensitizing effects known.
- Additional toxicological information:
Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

(Contd. of page 3)

12 Ecological information

- General notes:
At present there are no ecotoxicological assessments.
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- Product:
- Recommendation:
Take to special waste combustion plant.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Regulations of local authorities have to be followed.
- Uncleaned packagings:
- Recommendation:
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
Non contaminated packagings can be treated like household garbage.

14 Transport information

· DOT regulations:



- Hazard class: 3
- Identification number: UN1170
- Packing group: III
- Proper shipping name (technical name): ETHANOL, SOLUTION
- Label: 3

· Land transport ADR/RID (cross-border):



- ADR/RID class: 3 (F1) Flammable liquids
- Danger code (Kemler): 33
- UN-Number: 1170
- Packaging group: III

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1170
- Label: 3
- Packaging group: III
- EMS Number: F-E,S-D

(Contd. on page 5)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/18/2004

Reviewed on 03/18/2004

Trade name: *Curil K2*

(Contd. of page 4)

· **Proper shipping name:** ETHANOL, SOLUTION

· **Air transport ICAO-TI and IATA-DGR:**



· ICAO/LATA Class:	3
· UNID Number:	1170
· Label	3
· Packaging group:	III
· Proper shipping name:	ETHANOL, SOLUTION

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

78-93-3 | butanone

· **TSCA (Toxic Substances Control Act):**

8001-79-4 | Castor oil

64-17-5 | ethanol

8002-74-2 | Paraffin waxes and Hydrocarbon waxes

7732-18-5 | water, distilled, conductivity or of similar purity

7631-86-9 | silicon dioxide, chemically prepared

78-93-3 | butanone

98-54-4 | 4-tert-butylphenol

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

· **Canadian Ingredient disclosure list**

· **Limit 0,1%:**

64-17-5 | ethanol

· **Limit 1%:**

8001-79-4 | Castor oil

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

78-93-3 | butanone | D

1330-20-7 | xylene, mixed isomers, pure | D

· **IARC (International Agency for Research on Cancer)**

1330-20-7 | xylene, mixed isomers, pure | 3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

64-17-5 | ethanol | A4

1330-20-7 | xylene, mixed isomers, pure | A4

· **MAK (German Maximum Workplace Concentration)**

64-17-5 | ethanol | 5

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 6)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/18/2004

Reviewed on 03/18/2004

Trade name: Curil K2

(Contd. of page 5)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**



F Highly flammable

· **Risk phrases:**

Highly flammable.

· **Safety phrases:**

Keep out of the reach of children.
Keep container tightly closed.
Keep away from sources of ignition - No smoking.
Use only in well-ventilated areas.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	25-50

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS: 2ZEW
- Contact: Mr. Arhorn
- * Data compared to the previous version altered.