



# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>NAPA® Trans-Kleen™ Automatic Transmission Treatment</b>
<b>Other means of identification</b>	
<b>Product code</b>	095332
<b>Recommended use</b>	Improves shifting and extends transmission life
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufactured or sold by:</b>	
<b>Company name</b>	CRC Industries, Inc.
<b>Address</b>	885 Louis Dr. Warminster, PA 18974 US
<b>Telephone</b>	
<b>General Information</b>	215-674-4300
<b>Technical Assistance</b>	800-521-3168
<b>Customer Service</b>	800-272-4620
<b>24-Hour EMERGENCY (CHEMTREC)</b>	800-424-9300 (US) 703-527-3887 (International)
<b>Website</b>	www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
<b>Health hazards</b>	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
<b>Environmental hazards</b>	Aspiration hazard	Category 1
	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



**Signal word**

Danger

**Hazard statement**

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing genetic defects. Suspected of causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Use explosion-proof equipment. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash contaminated clothing before reuse. If exposed or concerned: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

### Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### Supplemental information

36.73% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Diesel Fuel No. 2		68476-34-6	60 - 70
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	20 - 30
Sec-butyl alcohol		78-92-2	5 - 10
1,2,3,4-Tetrahydronaphthalene		119-64-2	1 - 3
Tri-butoxyethyl phosphate		78-51-3	1 - 3
Naphthalene		91-20-3	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

### General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

---

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

---

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
<b>Environmental precautions</b>	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.  Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

---

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. For product usage instructions, please see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Eliminate sources of ignition. Avoid spark promoters. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	PEL	5 mg/m <sup>3</sup>	Mist.
		2000 mg/m <sup>3</sup> 500 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m <sup>3</sup> 10 ppm	
		450 mg/m <sup>3</sup>	
Sec-butyl alcohol (CAS 78-92-2)	PEL	150 ppm	

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Diesel Fuel No. 2 (CAS 68476-34-6)	TWA	100 mg/m <sup>3</sup>	Inhalable fraction and vapor.
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Sec-butyl alcohol (CAS 78-92-2)	TWA	100 ppm	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m <sup>3</sup>	
	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.
Naphthalene (CAS 91-20-3)	STEL	75 mg/m <sup>3</sup> 15 ppm	
	TWA	50 mg/m <sup>3</sup> 10 ppm	
	STEL	455 mg/m <sup>3</sup>	
Sec-butyl alcohol (CAS 78-92-2)	TWA	150 ppm 305 mg/m <sup>3</sup> 100 ppm	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

### Exposure guidelines

#### US ACGIH Threshold Limit Values: Skin designation

Diesel Fuel No. 2 (CAS 68476-34-6) Can be absorbed through the skin.  
Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear protective gloves such as: Neoprene. Nitrile. Polyvinyl chloride (PVC).

**Other** Wear appropriate chemical resistant clothing.

<b>Respiratory protection</b>	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

---

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Light amber.
<b>Odor</b>	Petroleum.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-173.2 °F (-114 °C) estimated
<b>Initial boiling point and boiling range</b>	211.1 °F (99.5 °C) estimated
<b>Flash point</b>	86 °F (30 °C) Tag Closed Cup
<b>Evaporation rate</b>	Slow.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.6 % estimated
<b>Flammability limit - upper (%)</b>	12.3 % estimated
<b>Vapor pressure</b>	1.7 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.85
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	494 °F (256.7 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.
<b>Percent volatile</b>	98.5 % estimated

## 10. Stability and reactivity

---

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Hydrocarbon fumes and smoke.

## 11. Toxicological information

---

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.
<b>Skin contact</b>	Causes skin irritation.

<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Product	Species	Test Results
NAPA® Trans-Kleen™ Automatic Transmission Treatment		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	2224 mg/kg estimated
<b>Inhalation</b>		
LC50	Rat	27 mg/l estimated
<b>Oral</b>		
LD50	Rat	3933 mg/kg estimated

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	Suspected of causing genetic defects.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Diesel Fuel No. 2 (CAS 68476-34-6)	3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects.

**12. Ecological information**

Product	Species	Test Results
Ecotoxicity Harmful to aquatic life with long lasting effects.		
NAPA® Trans-Kleen™ Automatic Transmission Treatment		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50 Daphnia	2.5136 mg/l, 48 hours estimated
Fish	LC50 Fish	50.7266 mg/l, 96 hours estimated
<b>Components</b>		
1,2,3,4-Tetrahydronaphthalene (CAS 119-64-2)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia pulex)	2.412 mg/l, 48 hours

Components	Species	Test Results
Diesel Fuel No. 2 (CAS 68476-34-6)		
<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 35 mg/l, 96 hours
Naphthalene (CAS 91-20-3)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> ) 1.6 mg/l, 96 hours
Sec-butyl alcohol (CAS 78-92-2)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> ) 1859 - 7143 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) 3380 - 3990 mg/l, 96 hours
Tri-butoxyethyl phosphate (CAS 78-51-3)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	LC50	<i>Daphnia magna</i> 84 mg/l, 24 hours 75 mg/l, 48 hours
Fish	EC50	Fathead minnow ( <i>Pimephales promelas</i> ) 16 mg/l, 96 hours Killifish ( <i>Cyprinodon dearborni</i> ) 44 mg/l, 48 hours at 10 °C 27 mg/l, 48 hours at 20 °C 6.8 mg/l, 48 hours at 30 °C

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Naphthalene	3.3
Sec-butyl alcohol	0.61
Tri-butoxyethyl phosphate	3.75

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal of waste from residues / unused products** If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information**

**DOT**

<b>UN number</b>	UN1268
<b>UN proper shipping name</b>	Petroleum distillates, n.o.s. or Petroleum products, n.o.s., Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III



**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** 144, B1, IB3, T4, TP1, TP29  
**Packaging exceptions** 150  
**Packaging non bulk** 203  
**Packaging bulk** 242

**IATA**

**UN number** UN1268  
**UN proper shipping name** Petroleum products, n.o.s., Limited Quantity  
**Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
**Packing group** III  
**Environmental hazards** No.  
**ERG Code** 3L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
    **Passenger and cargo aircraft** Allowed.  
    **Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN1268  
**UN proper shipping name** PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S., LIMITED QUANTITY  
**Transport hazard class(es)**  
    **Class** 3  
    **Subsidiary risk** -  
**Packing group** III  
**Environmental hazards**  
    **Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Sec-butyl alcohol (CAS 78-92-2)  
Tri-butoxyethyl phosphate (CAS 78-51-3)

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Sec-butyl alcohol (CAS 78-92-2) Listed.  
Tri-butoxyethyl phosphate (CAS 78-51-3) Listed.

**CERCLA Hazardous Substances: Reportable quantity**

Sec-butyl alcohol (CAS 78-92-2) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Tri-butoxyethyl phosphate (CAS 78-51-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.



**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 311/312** Immediate Hazard - Yes  
**Hazard categories** Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**US state regulations**

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Diesel Fuel No. 2 (CAS 68476-34-6)  
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)  
Naphthalene (CAS 91-20-3)  
Tri-butoxyethyl phosphate (CAS 78-51-3)

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**  
Not listed.

**US. New Jersey Worker and Community Right-to-Know Act**

Diesel Fuel No. 2 (CAS 68476-34-6)  
Sec-butyl alcohol (CAS 78-92-2)  
Tri-butoxyethyl phosphate (CAS 78-51-3)  
Naphthalene (CAS 91-20-3)

**US. Massachusetts RTK - Substance List**

Sec-butyl alcohol (CAS 78-92-2)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Sec-butyl alcohol (CAS 78-92-2)  
Tri-butoxyethyl phosphate (CAS 78-51-3)  
Naphthalene (CAS 91-20-3)  
1,2,3,4-Tetrahydronaphthalene (CAS 119-64-2)  
Diesel Fuel No. 2 (CAS 68476-34-6)

**US. Rhode Island RTK**

Sec-butyl alcohol (CAS 78-92-2)  
Tri-butoxyethyl phosphate (CAS 78-51-3)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

**Volatile organic compounds (VOC) regulations**

**EPA**

**VOC content (40 CFR 51.100(s))** 98.6 %  
**Consumer products (40 CFR 59, Subpt. C)** Not regulated

**State**

**Consumer products** Not regulated  
**VOC content (CA)** 72.7 %  
**VOC content (OTC)** 72.7 %

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

<b>Issue date</b>	05-30-2015
<b>Prepared by</b>	Allison Cho
<b>Version #</b>	01
<b>Further information</b>	CRC # 606B
<b>HMIS® ratings</b>	Health: 2* Flammability: 4 Physical hazard: 0 Personal protection: B
<b>NFPA ratings</b>	Health: 2 Flammability: 4 Instability: 0

### NFPA ratings



### Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.