



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Trans-X® High Mileage Stop Leak & Tune Up

**Other means of identification**

**Product code** 402916

**Recommended use** Automatic transmission fluid additive

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service**

**24-Hour Emergency (CHEMTREC)** 800-272-4620

703-527-3887 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause damage to organs (liver, kidneys, brain, lungs) through prolonged or repeated exposure. Suspected of causing cancer. Suspected of damaging the unborn child. Harmful to aquatic life.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse. If exposed or concerned: Get medical attention. In case of fire: Use appropriate media to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	70 - 80
Isopropyl alcohol		67-63-0	10 - 20
Xylene		1330-20-7	5 - 10
Toluene		108-88-3	3 - 5
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol)		123-42-2	1 - 3
Ethylbenzene		100-41-4	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire-fighting equipment/instructions**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**General fire hazards**

Highly flammable liquid and vapor.

## 6. Accidental release measures

---

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental precautions**

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

---

**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Eliminate sources of ignition. Avoid spark promoters. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

---

**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	PEL	240 mg/m <sup>3</sup>	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	50 ppm	Mist.
		5 mg/m <sup>3</sup>	
Ethylbenzene (CAS 100-41-4)	PEL	2000 mg/m <sup>3</sup>	
		500 ppm	
		435 mg/m <sup>3</sup>	
		100 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Isopropyl alcohol (CAS 67-63-0)	PEL	980 mg/m3	
Xylene (CAS 1330-20-7)	PEL	400 ppm 435 mg/m3 100 ppm	

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value	Form
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	TWA	50 ppm	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	TWA	240 mg/m3	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	50 ppm 1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	125 ppm 435 mg/m3 100 ppm	
Isopropyl alcohol (CAS 67-63-0)	STEL	1225 mg/m3	
	TWA	500 ppm 980 mg/m3 400 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm	
	TWA	375 mg/m3 100 ppm	

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

## Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear safety glasses with side shields (or goggles).

### Skin protection

#### Hand protection

Wear protective gloves such as: Neoprene. Nitrile.

#### Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

### Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Red.

### Odor

Mild petroleum.

### Odor threshold

Not available.

### pH

Not available.

### Melting point/freezing point

-138.8 °F (-94.9 °C) estimated

### Initial boiling point and boiling range

179.6 °F (82 °C) estimated

### Flash point

57 °F (13.9 °C) Tag Closed Cup

### Evaporation rate

Slow.

### Flammability (solid, gas)

Not available.

## Upper/lower flammability or explosive limits

Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	12 % estimated
Vapor pressure	8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.88
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	600 °F (315.6 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	97 % estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Halogens. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
----------------	-----------------------------------------------

Product	Species	Test Results
Trans-X® High Mileage Stop Leak & Tune Up		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	16612 mg/kg estimated
<b>Inhalation</b>		
LC50	Rat	45005 ppm, 4 hours estimated 146 mg/l, 4 hours estimated
<b>Oral</b>		
LD50	Rat	4984 mg/kg estimated

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.

<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not available.

<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure: Brain. Kidneys. Liver. Lungs.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.

**12. Ecological information**

**Ecotoxicity** Harmful to aquatic life.

Product		Species	Test Results
<b>Trans-X® High Mileage Stop Leak &amp; Tune Up</b>			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia	301.0404 mg/l, 48 hours estimated
Fish	LC50	Fish	31.4661 mg/l, 96 hours estimated
<b>Components</b>			
<b>Species</b>			
<b>Test Results</b>			
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	8750 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	420 mg/l, 96 hours
		Goldfish (Carassius auratus)	> 5000 mg/l, 24 hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Fathead minnow (Pimephales promelas)	> 30000 mg/l
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	2.1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	12.1 mg/l, 96 hours
Isopropyl alcohol (CAS 67-63-0)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	7550 - 13299 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	3200 mg/l, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	9.5 - 19.2 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol)	-0.098
Ethylbenzene	3.15
Isopropyl alcohol	0.05
Toluene	2.73
Xylene	3.12 - 3.2

**Bioconcentration factor (BCF)**

Xylene	15
--------	----

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal of waste from residues / unused products** If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

**DOT**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	Flammable liquids, n.o.s. (Isopropyl alcohol RQ = 787 LBS, Xylene RQ = 1818 LBS), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	IB2, T7, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	202
<b>Packaging bulk</b>	242

**IATA**

<b>UN number</b>	UN1993
<b>UN proper shipping name</b>	Flammable liquids, n.o.s. (Isopropyl alcohol, Xylene), Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3H
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



**Other information**

**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN1993  
**UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, Xylene), LIMITED QUANTITY  
**Transport hazard class(es)**  
**Class** 3  
**Subsidiary risk** -  
**Packing group** II  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Ethylbenzene (CAS 100-41-4)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

**CERCLA Hazardous Substances: Reportable quantity**

Ethylbenzene (CAS 100-41-4)	1000 LBS
Toluene (CAS 108-88-3)	1000 LBS
Xylene (CAS 1330-20-7)	100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3)	6594
------------------------	------

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3)	35 %WV
------------------------	--------

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3)	594
------------------------	-----

**Food and Drug Administration (FDA)** Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Section 311/312** Immediate Hazard - Yes  
**Hazard categories** Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

## US state regulations

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Isopropyl alcohol (CAS 67-63-0)  
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

### US. New Jersey Worker and Community Right-to-Know Act

4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl alcohol (CAS 67-63-0)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)  
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

### US. Massachusetts RTK - Substance List

4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)  
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  
Ethylbenzene (CAS 100-41-4)  
Isopropyl alcohol (CAS 67-63-0)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Ethylbenzene (CAS 100-41-4)  
Isopropyl alcohol (CAS 67-63-0)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)  
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)

### US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Arsenic (CAS 7440-38-2)	Listed: February 27, 1987
Benzene (CAS 71-43-2)	Listed: February 27, 1987
Cadmium (CAS 7440-43-9)	Listed: October 1, 1987
Cumene (CAS 98-82-8)	Listed: April 6, 2010
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Lead (CAS 7439-92-1)	Listed: October 1, 1992

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Cadmium (CAS 7440-43-9)	Listed: May 1, 1997
Lead (CAS 7439-92-1)	Listed: February 27, 1987
Sulfur dioxide (CAS 7446-09-5)	Listed: July 29, 2011
Toluene (CAS 108-88-3)	Listed: January 1, 1991

#### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Lead (CAS 7439-92-1)	Listed: February 27, 1987
Toluene (CAS 108-88-3)	Listed: August 7, 2009

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Benzene (CAS 71-43-2)

Listed: December 26, 1997

Cadmium (CAS 7440-43-9)

Listed: May 1, 1997

Lead (CAS 7439-92-1)

Listed: February 27, 1987


**Volatile organic compounds (VOC) regulations****EPA****VOC content (40 CFR 51.100(s))** 100 %**Consumer products (40 CFR 59, Subpt. C)** Not regulated**State****Consumer products** Not regulated**VOC content (CA)** 26 %**VOC content (OTC)** 26 %**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	08-07-2015
<b>Prepared by</b>	Allison Cho
<b>Version #</b>	01
<b>Further information</b>	CRC # 901A
<b>HMIS® ratings</b>	Health: 1* Flammability: 3 Physical hazard: 0 Personal protection: B
<b>NFPA ratings</b>	Health: 1 Flammability: 3 Instability: 0
<b>NFPA ratings</b>	

**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.