
MATERIAL SAFETY DATA SHEET

Effective Date: 10/05/2006 Code: 55126NYK Petroleum Hydrocarbon

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Truck-Lite NYK Lubricant

MANUFACTURER'S NAME: NIAGARA LUBRICANT Co, Inc. EMERGENCY TELEPHONE NO.

(716)874-2300

164 Chandler Street Buffalo, New York 14207 USA

MISCELLANEOUS INFORMATION

Section 2 - HAZARDOUS INGREDIENTS

| CAS NO. | INGREDIENT % | by Wt. | ACGIH TLV | OSHA PEL | UNITS | V.P. |
|-------------------------|--|------------------------|----------------------|----------------------|----------------------|------|
| 64742-54-7 1302-78-9 | Hydrotreated Residual Oil Highly Refined Petroleum Oil Inorganic Thickener Rheological Additive | >50 >30 >5 <3 | ND ND ND ND | ND ND ND ND | ND ND ND ND | |

Section 3 - HAZARDS INDENTIFICATION

EYE: May Cause irritation, Flush with plenty of water at least 15 minutes, get

medical attention. SKIN: May cause mild irritation, wash with soap and water, get medical attention

If needed. Remove all contaminated clothing and launder. INGESTION: Do not induce vomiting, get medical attention.

INHALATION: Remove to fresh air, get medical attention.

REPRODUCTION INFORMATION: No data available.

Section 4 - FIRST AID MEASURES

EYES-Immediately flush eyes with plenty of water for at least 15 minutes. Seek Medical attention.

SKIN-Wash with soap and water. Seek medical attention if irritation develops.

INGESTION-IF swallowed seek immediate medical attention. DO NOT INDUCE VOMITING.

INHALATION-Remove to fresh air. If not breathing give artificial respiration. Seek immediate medical attention.

NOTE TO PHYSICIANS-Supportive care. Treatment based on judgment of the physician in response to reactions of the patient. May aggravate pre-existing respiratory conditions.

Section 5 - FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: >400F (>204C) Method: TCC

FLAMMABLE LIMITS:

Lower flammable limit: Not Determined Upper flammable limit: Not Determined

AUTOIGNITION TEMPERATURE: Not Determined

EXTINGUISHING MEDIA: CO2, Dry Chemical, Foam

Firefighters should wear normal protective equipment (full bunker gear) and positive- pressure self-contained breathing apparatus.

Section 6 - ENVIRONMENTAL RELEASE MEASURES

Use judgment when cleaning large spills, shut off source of leak, and dike and contain. Soak up with an absorbent such as clay, sand or other suitable materials, dispose of properly. Prevent runoff from entering into storm sewers and ditches which lead to natural waterways.

MATERIAL SAFETY DATA SHEET

Effective Date: 10/05/2005 Code: 55126NYK Petroleum Hydrocarbon

7 - HANDLING AND STORAGE

HANDLING: Avoid contact with eyes. Keep container closed. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin.

STORAGE: Store in well ventilated area. Keep away from heat, sparks and flame. Emptied containers may retain product residues. Precautions apply to emptied containers.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: When respiratory protection is required, or concentrations are unknown use NIOSH/MSHA approved air purifying respirator equipped with organic vapor cartridges or canisters. For emergency and other conditions where exposure limit may be greatly exceeded, use and approved positive- pressure, self contained breathing apparatus or positive-pressure airline with auxiliary self contained air supply.

SKIN PROTECTION: Wear chemical resistant gloves and other protective clothing as required minimizing skin contact, Use impervious gloves such as neoprene.

EYE PROTECTION: Use chemical goggles as needed. If vapor exposure causes eye discomfort, use a full face, supplied-air respirator.

9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >700F(>370C)
MELTING POINT: 500F (260C)
VAPOR PRESSURE: Not Determined
VAPOR DENSITY: <.01 (Air=1.0)
SOLUBILITY IN WATER: negligible
SPECIFIC GRAVITY: .90 (H2o=1)

pH: No data

ODOR: Hydrocarbon order APPEARANCE: Amber Paste

10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY: (CONDITIONS TO AVOID) Keep away from flames and spark-producing equipment. Not dangerously unstable.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

HAZARDOUS POLYMERIZATION: Will not occur.

11 - TOXICOLOGICAL INFORMATION

EYE: No Data

SKIN: No Data

INGESTION: No Data SUBCHRONIC: No data

CHRONIC/CARCINOGENICITY: No Data

TERATOLOGY: No Data REPRODUCTION: No data. MUTAGENICITY: No Data

12 - ECOLOGICAL INFORMATION

ECOTOXILOGICAL No Data

CHEMICAL FATE INFORMATION: No Data

13 - DISPOSAL CONSIDERATIONS

Dispose of in compliance with Federal, State and local regulations.

14 - TRANSPORT INFORMATION

Petroleum Hydrocarbon DOT Class 65

Niagara Lubricant Co., Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose Niagara Lubricant Co., Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Niagara Lubricant Co., Inc. will not be responsible for damages resulting from use of or reliance upon this information.