

BATTERIES S

GEL SERIES



- Ideal for use in a wide range of deep cycle/starting applications.
- Gel design eliminates dangerous spills, gassing, and terminal corrosion for safer operation.
- Thick consistency of gel prevents damaging effects of vibration.
- Faster recharge time for quick efficient charging and a low self-discharge rate so it can be left for months without worrying about recharging or capacity-loss.
- 100% maintenance-free design eliminates the need to check liquid levels or add water.
- Sealed, gelled electrolyte is spillproof and leakproof for installation in virtually any position.
- Full-framed, power path grids and computer-controlled oxide provides maximum durability, power, and life.
- Sealed electrolyte design eliminates gassing making it safe to use around sensitive equipment.
- Convenient carrying handle provides ease of transport and installation.
- These batteries can be transported by air without special containers and are classified non-spillable by DOT (Department Of Transportation) definitions.
- Be sure to use a good, fully automatic, temperature-sensing, voltageregulated charger, with an adjustable voltage feature. The charger must be voltage regulated otherwise, it will overcharge the battery and shorten its life.
- For 12-volt batteries, the charger must be voltage-regulated at a minimum of 13.80 volts, but at no more than 14.10 volts at 68°F (20°C). Proper charging is critical.
- Over 250 quality control checks assures quality and reliable performance.