



BATTERIES

AGM THE LEGEND PREMIUM



- Meets OEM AGM standards for an exact fit replacement including power, configuration, and venting requirements.
- Convenient, non-obstructive fold-down handles provide ease of transport and installation.
- Provides an exact fit for import vehicles, and domestic as well.
- Absorbed electrolyte technology is spillproof and delivers long maintenance-free cycle life.
- Specially-engineered safety relief valve system effectively controls critical internal gas pressure preventing capacity loss from excessive gas seepage.
- Microfiber glass separators have extremely low electrical resistance for higher capacity and faster discharge rates.
- Maintenance-free construction eliminates the need to add water.
- Requires less charging time than conventional batteries.
- Flexible design can be installed in almost any position (upside down is not recommended).
- High freeze-resistance offers longer battery life and more power for dependable cold weather service.
- Optimized Component Compression resists vibration damage for longer operating time and service life.
- Charging: Use a good, constant potential, voltage-regulated charger.
Charge / Absorption / Equalize between 13.8 – 14.6 volts @ 77°F (25°C).
Float / Standby between 13.4 – 13.6 volts @ 77°F (25°C).
Temperature corrected charging required. Do not charge in a sealed container.
- Over 250 quality control checks make the International line one of the most reliable in the world.