Material Safety Data Sheet



1. Chemical product and company identification

Product name Castrol Import Multivehicle ATF

MSDS # 465368

Historic MSDS #: 0000003229

Code 465368-US10

Product use Automatic transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: (973) 633-2200 Telecopier: (973) 633-7475

EMERGENCY HEALTH 1 (800) 447-8735

INFORMATION: Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT 1 (866) 4 BP - MSDS

INFORMATION (866-427-6737 Toll Free - North America)

email: bpcares@bp.com

2. Composition/information on ingredients

Ingredient name CAS # %

Base oil - highly refined 64742-55-8 75 - 80
Base oil - highly refined Mixture 5 - 10

3. Hazards identification

Physical state Liquid.

Color Red.

Emergency overview WARNING!

CAUSES EYE IRRITATION. CAUSES SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can

defat the skin and lead to irritation and/or dermatitis.

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes Causes eye irritation.

Skin Causes skin irritation. May cause allergic skin reaction. Prolonged or repeated contact can defat

the skin and lead to irritation and/or dermatitis.

Inhalation May cause respiratory tract irritation.

Product Castrol Import Multivehicle ATF Product code 465368-US10 Page: 1/6

name

Version 3 Date of issue 04/02/2007. Format US Language ENGLISH.

Build 5.3.1 (ENGLISH)

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

Medical conditions aggravated by overexposure

None identified.

See toxicological Information (section 11).

First aid measures

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical Eye contact

attention immediately.

Skin contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention

immediately.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, Inhalation

give oxygen. Get medical attention.

Ingestion Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of

this material are swallowed, call a physician immediately.

5. Fire-fighting measures

Flammability of the product

May be combustible at high temperature.

Flash point 158 °C (Closed cup) Pensky-Martens.

Products of combustion These products are carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide).

Unusual fire/explosion

hazards

Non-explosive in the presence of the following materials or conditions: open flames, sparks and

static discharge, heat and shocks and mechanical impacts.

Fire-fighting media and

instructions

In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.

Protective clothing (fire)

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full

turnout gear.

6. Accidental release measures

Personal precautions

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").

Environmental precautions and clean-up methods

If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.

Personal protection in case of a large spill

Version 3

Chemical splash goggles. Chemical resistant protective suit. Boots. Chemical resistant gloves. Vapor respirator or a self-contained breathing apparatus. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

Product Castrol Import Multivehicle ATF name

Date of issue 04/02/2007.

Product code

465368-US10

Page: 2/6

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

7. Handling and storage

Handling Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact

with eyes. Use only with adequate ventilation Avoid breathing vapor or mist. Wash thoroughly

after handling.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers

may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these

nazards.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name Occupational exposure limits

Base oil - highly refined ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral

Some states may enforce more stringent exposure limits.

Control Measures Provide exhaust ventilation or other engineering controls to keep the relevant airborne

concentrations below their respective occupational exposure limits. Ensure that eyewash stations

and safety showers are close to the work-station location.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes Avoid contact with eyes. Chemical splash goggles.

Skin and body Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory Use only with adequate ventilation In accordance with good industrial hygiene and safety work

practices, airborne exposures should be controlled to the lowest extent practicable.

Hands Wear gloves that cannot be penetrated by chemicals or oil.

Recommended: nitrile gloves

The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended

application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state Liquid.
Color Red.

Heat of combustion Not available.

Pour Point -40 °C

Product Castrol Import Multivehicle ATF Product code 465368-US10 Page: 3/6

name

Version 3 Date of issue 04/02/2007. Format US Language ENGLISH.

Build 5.3.1 (ENGLISH)

Specific gravity 0.85

Density 850 kg/m³ (0.85 g/cm³) at 15.6°C

Solubility insoluble in water.

Viscosity Kinematic: 33.7 mm²/s (33.7 cSt) at 40°C

Kinematic: 7.1 mm²/s (7.1 cSt) at 100°C

10. Stability and reactivity

Stability and reactivity The product is stable.

Conditions to avoid Keep away from heat, sparks and flame.

Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

(NTP) or the U.S. Occupational Safety and Health Act (OSHA).

Hazardous decomposition

products

Products of combustion: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide).

Hazardous polymerization Will not occur.

11. Toxicological information

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program

Mutagenic effects

effects

No component of this product at levels greater than 0.1% is classified by established regulatory

criteria as a mutagen.

Reproductive

No component of this product at levels greater than or equal to 0.1% is classified by established

regulatory criteria as a reproductive toxin.

Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory

criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information Avoid contact of spilled material and runoff with soil and surface waterways. Consult an

environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and

Product code

national regulations.

Consult your local or regional authorities.

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

Product Castrol Import Multivehicle ATF

name

Version 3 Date of issue 04/02/2007. Format US Language ENGLISH.

Build 5.3.1 (ENGLISH)

465368-US10

Page: 4/6

15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 12(b) one-time export notification:: Diphenylamine

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol Import

Multivehicle ATF: Immediate (Acute) Health Hazard

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: This material is not

regulated under CERCLA Sections 103 and 107.

State regulations

Massachusetts **Substances**

Massachusetts RTK: The following components are listed: MINERAL OIL, PETROLEUM

DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

New Jersey Hazardous Substances **New Jersey Hazardous Substances**: None of the components are listed.

Pennsylvania RTK **Hazardous Substances**

Pennsylvania RTK: None of the components are listed.

California Prop 65: No products were found

Inventories Canada inventory: All components are listed or exempted.

Europe inventory: At least one component is not listed in EINECS but all such components are

listed in ELINCS.

Please contact your supplier for information on the inventory status of this material.

Australian Inventory Status: Not determined. China inventory (IECSC): Not determined. Japan inventory (ENCS): Not determined. Korea inventory (KECI): Not determined.

Philippines inventory (PICCS): Not determined.

16. Other information

Label requirements WARNING!

> CAUSES EYE IRRITATION. CAUSES SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

- 2 Health **HMIS® Rating:**

1 **Flammability Protection Association Physical** 0 Hazard

Personal X

protection

National Fire

(U.S.A.)

Fire hazard Instability Specific hazard

History

Date of issue 04/02/2007. Date of previous issue 01/15/2007.

Product Castrol Import Multivehicle ATF

name

Version 3 Date of issue 04/02/2007. Format US Language ENGLISH.

> Build 5.3.1 (ENGLISH)

Product code

465368-US10

Page: 5/6

Prepared by

Product Stewardship

Notice to reader

NOTICE: This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product Castrol Import Multivehicle ATF name

Version 3

Date of issue 04/02/2007.

Product code

465368-US10

Page: 6/6

Format US Language ENGLISH.

Build 5.3.1 (ENGLISH)