

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product:	LE-5, LE-5BK	Trade Name:	Lock - Ease
Manufacturer:	AGS Company	Common Name:	Lock Lubricant
Street Address:	2651 Hoyt St		
City/ State/ Zip	Muskegon Hts., MI 49444		
Phone:	800-253-0403		
Phone:	231-733-2101	Original Issue Date:	11/12/1985
FAX:	231-733-1784	Revision No	16 Date 12/10/2012
Transportation Emergency:	CHEM-TEL		
Phone:	800-255-3924		

SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS

ITEM		CAS NUMBER	WT/WT %
1	N - Hexane	110-54-3	30-60
2	Stoddard Solvent	8052-41-3	15-40
3	Propane / Isobutane / N-Butane	68476-86-8	10-30
4	Dripless Base Compound	Mixture	7-13

EXPOSURE LIMITS

ITEM	ACGIH		OSHA	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING
1	50 ppm	N.E.	50	500 ppm
2	100 ppm	N.E.	100 ppm	500 ppm
3	800 ppm	N.E.	800 ppm	N.E.
4	N.E.	N.E.	N.E.	N.E.

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION

EYE CONTACT: Liquid and vapors may be irritating and can cause pain, tearing, reddening and swelling.

SKIN CONTACT: Prolonged or repeated contact may result in irritation and/or dermatitis.

INHALATION: Prolonged inhalation may cause headaches, dizziness, nausea and drowsiness leading to unconsciousness.

INGESTION: This material may be harmful or fatal if swallowed.

CHRONIC HAZARDS: Overexposure may cause nervous system, pulmonary and kidney damage.

Primary Route(s) of Entry Inhalation, skin and eye contact or ingestion.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT: Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

INGESTION: Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

MATERIAL SAFETY DATA SHEET

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT LD-50 >5000 mg/kg PRODUCT LC-50 >5500 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME	LD50	LC50
N - Hexane	28710 mg/kg/rat	150000 mg/m ³ /mouse
Stoddard Solvent	>5000 mg/kg/rat	>5500 mg/m ³ /4h/rat
Propane / Isobutane / N-Butane	N.E.	658000 mg/m ³ /4h/rat
Dripless Base Compound	N.E.	N.E.
Graphite	N.E.	N.E.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME Aerosol - Consumer Commodity
 DOT TECHNICAL NAME ORM-D
 DOT HAZARD CLASS 2 HAZARD SUBCLASS: 2.1
 DOT UN / NA NUMBER: UN1950 PACKING GROUP: NA RESP. GUIDE PAGE 126

SECTION 15 - REGULATORY INFORMATION

U.S FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 cfr 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD
 PRESSURIZED GAS HAZARD

SARA SECTION 313

This product contains the following substance subject to the reporting requirements of Section 313 of Title of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT /WT % IS LESS THAN
---------------	------------	-----------------------

MATERIAL SAFETY DATA SHEET

n-hexane 110-54-3 40.0 %

TOXIC SUBSTANCE CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
Stoddard Solvent	8052-41-3

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
No non-hazardous materials are among the top five ingredients.	

PENNSYLVANIA RIGHT-TO-Know

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
No non-hazardous ingredients are present at greater than 3%	

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are know to the state of California to causes cancer, birth defects or other reproductive harm.

CHEMICAL NAME	CAS NUMBER
No Proposition 65 chemicals exist in this product.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:	Health	2	Flammability	4	Phys. Haz.	0	PPE	A
NFPA	Health	2	Flammability	4	Reactivity	0		

VOLATILE ORGANIC COMPOUNDS (VOCs): 5.05 lbs / gal 605 grams / liter

LEGEND:	N.A.	Not Applicable	N.E.	Not Established
	N.D.	Not Determined		

Disclaimer: The information contained herein is base on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.