



SAFETY DATA SHEET

Issuing Date 20-Nov-2013

Revision Date 20-Nov-2013

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Lock-Ease Aerosol

Other means of identification

Product Code(s) LE-5, LE-5BK (765-1384)

UN-Number UN1950

Synonyms Lock Lubricant, Graphited Lock Fluid

Recommended use of the chemical and restrictions on use

Recommended Use All types of locks, household appliances, tools, guns, reels and other mechanisms.

Uses advised against No information available

Supplier's details

Supplier Address

AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number 800-255-3924

2. HAZARDS IDENTIFICATION


Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

| | |
|---|------------|
| Serious Eye Damage/Eye Irritation | Category 2 |
| Skin Sensitization | Category 1 |
| Specific Target Organ Systemic Toxicity (Single Exposure) | Category 3 |
| Flammable aerosols | Category 1 |

GHS Label elements, including precautionary statements

Emergency Overview

| | |
|---|--|
| <p>Signal Word</p> <p>Hazard Statements</p> <ul style="list-style-type: none"> • Causes serious eye irritation • May cause an allergic skin reaction • May cause drowsiness or dizziness • • Extremely flammable aerosol • Pressurized container: may burst if heated | <p>Warning</p> <div style="text-align: center; margin: 10px 0;">  </div> <p>Appearance Black, Liquid</p> <p>Physical State Aerosol.</p> <p>Odor Pungent</p> |
|---|--|

Precautionary Statements

Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Contaminated work clothing should not be allowed out of the workplace
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces - No smoking
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- None

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. 0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

Lock Lubricant, Graphited Lock Fluid

| Chemical Name | CAS-No | Weight % | Trade secret |
|--------------------|------------|----------|--------------|
| Alkanes, C7-8-iso- | 70024-92-9 | 55-60 | * |
| Acetone | 67-64-1 | 15-20 | * |
| Butane | 106-97-8 | 10-15 | * |
| Propane | 74-98-6 | 5-10 | * |
| Calcium Sulfonate | - | < 1 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures**Eye Contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists.

Skin Contact

Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Remove and wash contaminated clothing before re-use.

Inhalation

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

Ingestion

Clean mouth with water and afterwards drink plenty of water.

Protection of First-aiders

Remove all sources of ignition. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Drowsiness. Dizziness. Central nervous system depression. Irritation.

Indication of immediate medical attention and special treatment needed, if necessary**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Foam. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Extremely flammable. Will form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up For undamaged containers: Pick up and transfer to properly labeled containers. In case of rupture: Soak up with inert absorbent material. Take precautionary measures against static discharges. Use clean non-sparking tools to collect absorbed material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not smoke. Do not puncture or incinerate cans. Contents under pressure. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep at temperatures below 50° C.

Incompatible Products Acids. Strong oxidizing agents. Oxygen.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------|-------------------------------|---|--|
| Acetone 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³ |

| | | | |
|---|---|---|--|
| Butane 106-97-8 | TWA: 1000 ppm | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | TWA: 800 ppm TWA: 1900 mg/m ³ |
| Propane 74-98-6 | TWA: 1000 ppm | TWA: 1000 ppm TWA: 1800 mg/m ³ | IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ |
| Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4 | TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral | TWA: 5 mg/m ³ , as oil mist, mineral | - |
| Benzene 71-43-2 | STEL = 2.5 ppm TWA: 0.5 ppm S* | TWA: 1 ppm TWA: 10 ppm (vacated) TWA: 10 ppm (vacated) STEL: 50 ppm (vacated) Ceiling: 25 ppm Ceiling: 25 ppm STEL: 5 ppm | IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Eyewash stations. Showers. Explosion proof ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.
Skin and Body Protection Wear protective gloves/clothing.
Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|-----------------------|---------|-----------------------|--------------------------|
| Physical State | Aerosol | Appearance | Black Liquid |
| Odor | Pungent | Odor Threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks/ - Method</u> |
|---|-------------------|--------------------------|
| pH | No data available | None known |
| Melting Point/Range | No data available | None known |
| Boiling Point/Boiling Range | No data available | None known |
| Flash Point | No data available | None known |
| Evaporation rate | No data available | None known |
| Flammability (solid, gas) | No data available | None known |
| Flammability Limits in Air | | |
| upper flammability limit | 12.8% | |
| lower flammability limit | 1.0% | |
| Vapor Pressure | No data available | None known |
| Vapor Density | Heavier than air | Air = 1 |
| Relative Density | No data available | None known |
| Specific Gravity | 0.69-0.75 | For concentrate |
| Water Solubility | Negligible | None known |
| Solubility in other solvents | No data available | None known |
| Partition coefficient: n-octanol/water | No data available | None known |
| Autoignition Temperature | No data available | None known |

| | | |
|----------------------------------|-------------------|------------|
| Decomposition Temperature | No data available | None known |
| Viscosity | No data available | None known |
| Flammable Properties | Not flammable | |
| Explosive Properties | No data available | |
| Oxidizing Properties | No data available | |
| Other information | | |
| VOC Content (%) | 79% | |

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Temperatures above 50°C.

Incompatible materials

Acids. Strong oxidizing agents. Oxygen.

Hazardous decomposition products

Carbon oxides. Aldehydes. Nitrogen

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Product does not present an acute toxicity hazard based on known or supplied information. May cause irritation of respiratory tract. May cause drowsiness and dizziness. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye Contact

Causes serious eye irritation.

Skin Contact

May cause allergic skin reaction

Ingestion

Ingestion may cause irritation to mucous membranes. May cause additional affects as listed under "Inhalation".

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---------------|----------------------|--------------------|-------------------------|
| Acetone | = 5800 mg/kg (Rat) | 1700mg/kg (rabbit) | 18892 mg/m ³ |
| Butane | - | - | 658 mg/L (Rat) 4 h |
| Propane | - | - | = 658 mg/L (Rat) 4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Vapors may cause drowsiness and dizziness Irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Irritation Causes serious eye irritation
Sensitization Calcium sulfonate may cause skin sensitization.
Mutagenic Effects No information available.
Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Reproductive Toxicity No information available.
STOT - single exposure May cause respiratory irritation
STOT - repeated exposure No information available.
Aspiration Hazard No information available.

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|---|--|--|----------------------------|--|
| Acetone 67-64-1 | | LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus) | EC50 = 14500 mg/L 15 min | EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna) |
| Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4 | | LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss) | | EC50 48 h: > 1000 mg/L (Daphnia magna) |
| Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5 | | LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss) | | EC50 48 h: > 1000 mg/L (Daphnia magna) |
| Benzene 71-43-2 | EC50 72 h: = 29 mg/L (Pseudokirchneriella subcapitata) | LC50 96 h: 10.7-14.7 mg/L flow-through (Pimephales promelas) LC50 96 h: 22330-41160 µg/L static (Pimephales promelas) LC50 96 h: 70000-142000 µg/L static (Lepomis macrochirus) LC50 96 h: = 22.49 mg/L static (Lepomis macrochirus) LC50 96 h: = 28.6 mg/L static (Poecilia reticulata) LC50 96 h: = 5.3 mg/L flow-through (Oncorhynchus mykiss) | | EC50 48 h: 8.76 - 15.6 mg/L Static (Daphnia magna) EC50 48 h: = 10 mg/L (Daphnia magna) |

Persistence and Degradability No information available.

Bioaccumulation No information available.

| Chemical Name | Log Pow |
|---------------|---------|
| Acetone | -0.24 |
| Butane | 2.89 |
| Propane | 2.3 |

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Pressurized container: Do not pierce or burn, even after use. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|-------------------|------|-----------------------------------|------------------------|------------------------|
| Acetone - 67-64-1 | | Included in waste stream: F039 | | U002 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|---------------|----------------------------|
| Acetone | Ignitable |

14. TRANSPORT INFORMATION

DOT

UN-Number UN1950
Proper shipping name Aerosols, flammable
Hazard Class 2.1
Reportable Quantity (RQ) Acetone: RQ kg= 11350.00
Description UN1950, Aerosols, flammable, 2.1, RQ
Emergency Response Guide Number 126

TDG

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

ICAO

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

IATA

UN-Number UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.2
ERG Code 10L
Description UN1950, Aerosols, flammable, 2.2

IMDG/IMO

UN-Number UN1950
Proper Shipping Name Aerosols

| | |
|-------------------------|----------------------------------|
| Hazard Class | 2 |
| Subsidiary Class | See SP63 |
| EmS No. | F-D, S-U |
| Description | UN1950, Aerosols, 2.1 (See SP63) |

| | |
|-----------------------------|-----------------------|
| UN-Number | UN1950 |
| Proper Shipping Name | Aerosols |
| Hazard Class | 2 |
| Classification Code | 5F |
| Description | UN1950, Aerosols, 2.1 |

ADR

| | |
|-----------------------------|----------|
| UN-Number | UN1950 |
| Proper Shipping Name | Aerosols |
| Hazard Class | 2 |
| Classification Code | 5F |

| | |
|--------------------------------|----------------------------|
| Tunnel Restriction Code | (D) |
| Description | UN1950, Aerosols, 2.1, (D) |
| ADR/RID-Labels | 2.1 |

| | |
|-----------------------------|-----------------------|
| Proper Shipping Name | Aerosols |
| Hazard Class | 2 |
| Classification Code | 5F |
| Special Provisions | 190, 327, 344, 625 |
| Description | UN1950, Aerosols, 2.1 |
| Limited Quantity | 1 L |
| Ventilation | VE01, VE04 |

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| | |
|-------------|----------|
| TSCA | Complies |
| DSL | Complies |

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

| | |
|--|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | Yes |
| Reactive Hazard | No |

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|---------------|--------------------------|------------------------------------|--|
| Acetone | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name | CAS-No | California Prop. 65 |
|---------------|---------|--|
| Benzene | 71-43-2 | Carcinogen Developmental Male Reproductive |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Illinois | Rhode Island |
|---------------|------------|---------------|--------------|----------|--------------|
| Acetone | X | X | X | | X |
| Butane | X | X | X | | X |
| Propane | X | X | X | | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

| |
|------------------------------|
| 16. OTHER INFORMATION |
|------------------------------|

| | | | | |
|--------------------|------------------|----------------|-------------------|--|
| <u>NFPA</u> | Health Hazard 2 | Flammability 3 | Instability 0 | Physical and Chemical Hazards - Personal Protection X |
| <u>HMIS</u> | Health Hazard 2* | Flammability 3 | Physical Hazard 1 | |

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 20-Nov-2013
Revision Date 20-Nov-2013
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet