# **S Permatex**

# SAFETY DATA SHEET

Revision Date 09-Mar-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 765-1461 NAPA ULTRA BLUE GASKET MAKER 3.35 OZ (PTX81724)

Other means of identification

Product Code 21177 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Manufacturer Address</u> <u>Distributor</u>

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

### Label elements

#### **Emergency Overview**

#### Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer

\_\_\_\_\_



Appearance Blue Physical state Paste Odor Mild

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Call a POISON CENTER or doctor/physician if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

26.18% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	15 - 40	*
CALCIUM CARBONATE	471-34-1	10 - 30	*
LIMESTONE	1317-65-3	10 - 30	*
SYNTHETIC ISOPARAFFINIC HYDROCARON	64742-47-8	3 - 7	*
VINYL OXIMINOSILANE	2224-33-1	3 - 7	*
POLYDIMETHYLSILOXANE	63148-62-9	1 - 5	*
STEARIC ACID	57-11-4	1 - 5	*
2-BUTANONE OXIME	96-29-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

# 21177 - 765-1461 NAPA ULTRA BLUE GASKET MAKER 3.35 OZ (PTX81724)

**Description of first aid measures** 

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m <sup>3</sup> total dust
471-34-1			TWA: 5 mg/m <sup>3</sup> respirable dust
LIMESTONE	-	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m³ total dust
1317-65-3		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total dust	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

# 21177 - 765-1461 NAPA ULTRA BLUE GASKET MAKER 3.35 OZ (PTX81724)

Remarks • Method

Polymerization

Air = 1

Polymerization

Tag Closed Cup

Physical state Paste
Appearance Blue
Odor Mild

Odor threshold No information available

<u>Property</u> <u>Values</u>

pH No information available
Melting point / freezing point No information available

Boiling point / boiling range
Flash point

Not Applicable

> 93 °C / > 200 °F

**Evaporation rate**Flammability (solid, gas)
No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure

No information available
No information available
5 mm Hq @ 80°F

Vapor density 3.0

Relative density 1.44

Water solubility Not applicable

No information available Solubility in other solvents **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

**VOC Content (%)** 3.1%

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Excessive heat. Exposure to air or moisture over prolonged periods. Heat, flames and sparks.

#### Incompatible materials

Strong oxidizing agents, Acids, Water

#### **Hazardous Decomposition Products**

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg(Rabbit)	> 8750 mg/m³(Rat)7 h
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	-	-
SYNTHETIC ISOPARAFFINIC HYDROCARON 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
POLYDIMETHYLSILOXANE 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg(Rabbit)	-
STEARIC ACID 57-11-4	-	> 5 g/kg(Rabbit)	-
2-BUTANONE OXIME 96-29-7	= 930 mg/kg ( Rat )	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h

# Information on toxicological effects

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Target Organ Effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10659 mg/kg ATEmix (dermal) 8982 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

94.07% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
SYNTHETIC ISOPARAFFINIC	-	45: 96 h Pimephales promelas mg/L	4720: 96 h Den-dronereides
HYDROCARON		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
64742-47-8		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
2-BUTANONE OXIME	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
		320 - 1000: 96 h Leuciscus idus	
		mg/L LC50 static 760: 96 h Poecilia	
		reticulata mg/L LC50 static	

#### Persistence and degradability

No information available.

# 21177 - 765-1461 NAPA ULTRA BLUE GASKET MAKER 3.35 OZ (PTX81724)

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical Name	Partition coefficient
2-BUTANONE OXIME	0.65
96-29-7	

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

**IMDG** 

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA** Complies **DSL/NDSL EINECS/ELINCS** Not Listed **ENCS** Not Listed **IECSC** Complies Complies KECL **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
SILICA, QUARTZ - 14808-60-7	Carcinogen	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE 1317-65-3	Х	X	Х
ALUMINIUM POWDER 7429-90-5	X	X	X
CI PIGMENT BLUE 15, CI #74160 147-14-8	X	-	X
SILICA, QUARTZ 14808-60-7	X	X	X
ETHANOL 64-17-5	X	X	X

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 1 Instability 0 -

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 09-Mar-2015

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**