# **S Permatex**

# SAFETY DATA SHEET

Revision Date 01-Jun-2015 Version 1

# 1. IDENTIFICATION

Product identifier

Product Name VERSACHEM EXHAUST SYSTEM JOINT & CRACK SEALER 142 GR.

Other means of identification

Product Code 10160 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant Automotive Care Product

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 1A Category 2

# Label elements

#### **Emergency Overview**

#### Warning

Harmful if swallowed

Suspected of causing cancer



Appearance Gray Physical state Paste Odor Mild

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

# **Precautionary Statements - Storage**

Store locked up

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

Not applicable.

Unknown acute toxicity 48.8 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

# substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
KAOLIN	1332-58-7	30 - 60	*
CRYSTALLINE SILICA	14808-60-7	1 - 5	*
TITANIUM DIOXIDE	13463-67-7	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### Description of first aid measures

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

**Skin contact** IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions** See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel

into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store locked up.

Incompatible materials Strong oxidizing agents, Acids

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

L	Chemical Name	Chemical Name ACGIH TLV		cal Name ACGIH TLV OSHA PEL		NIOSH IDLH	
Г	KAOLIN TWA: 2 mg/m³ particulate matter		TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust			
	1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust			
		crystalline silica, respirable fraction	(vacated) TWA: 10 mg/m³ total dust				
			(vacated) TWA: 5 mg/m³ respirable				
L			fraction				
	CRYSTALLINE SILICA	TWA: 0.025 mg/m³ respirable	(vacated) TWA: 0.1 mg/m <sup>3</sup>	IDLH: 50 mg/m³ respirable dust			
	14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m³ respirable dust			
			: (30)/(%SiO2 + 2) mg/m³ TWA				
			total dust				
			: (250)/(%SiO2 + 5) mppcf TWA				
			respirable fraction				
			: (10)/(%SiO2 + 2) mg/m³ TWA				
L			respirable fraction				
	TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>			
	13463-67-7		(vacated) TWA: 10 mg/m <sup>3</sup> total dust				

NIOSH IDLH Immediately Dangerous to Life or Health

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical statePasteAppearanceGray

# 10160 - VERSACHEM EXHAUST SYSTEM JOINT & CRACK SEALER 142 GR.

Butyl acetate = 1

Air = 1

Odor Mild

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range No information available
110 °C / 230 °F

Flash point None

Evaporation rate < 1
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Vapor pressure <1 @ 25°C

Vapor density >1
Relative density 1.65
Water solubility Negligible

Solubility in other solvents No information available No information available Partition coefficient **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available No information available **Explosive properties** Oxidizing properties No information available

**Other Information** 

Softening point No information available Molecular weight No information available

VOC Content (%)

Density
No information available
Bulk density
No information available

# 10. STABILITY AND REACTIVITY

# Reactivity

No data available

# **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

# **Conditions to avoid**

Excessive heat.

# **Incompatible materials**

Strong oxidizing agents, Acids

#### **Hazardous Decomposition Products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis.

**Ingestion** Harmful if swallowed.

Chemical Name Oral LD50		Dermal LD50	Inhalation LC50
CRYSTALLINE SILICA 14808-60-7	= 500 mg/kg(Rat)	-	-
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-

# Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA 14808-60-7	A2	Group 1	Known	Х
TITANIUM DIOXIDE 13463-67-7	-	Group 2B	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Eyes, Lungs, Respiratory system.

# The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 1468 mg/kg **ATEmix (dermal)** 6275 mg/kg

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

# Persistence and degradability

No information available.

# **Bioaccumulation**

No information available.

# **Mobility**

No information available.

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

# 10160 - VERSACHEM EXHAUST SYSTEM JOINT & CRACK SEALER 142 GR.

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

US EPA Waste Number Not applicable

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

<u>IMDG</u>

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Not Listed. **IECSC** Complies **KECL** Complies **PICCS** Complies Complies **AICS** 

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardYesFire hazardNoSudden release of pressure hazardNoReactive HazardNo

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CRYSTALLINE SILICA - 14808-60-7	Carcinogen	
TITANIUM DIOXIDE - 13463-67-7	Carcinogen	

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KAOLIN 1332-58-7	X	X	X
WATER 7732-18-5	-	-	X
CRYSTALLINE SILICA 14808-60-7	X	X	X
SILICA, MICA 12001-26-2	Х	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	Х

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA_	Health hazards 2	Flammability 0	Instability 0	-
HMIS	Health hazards 2	Flammability 0	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 01-Jun-2015

#### Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**