


MATERIAL SAFETY DATA SHEET

765-2630, 765-2631

Product: Squeak Relief™ Brake Finishing Treatment

Stock Number	Size	NFPA Rating
90201	11.25 oz	0-Insignificant
90031	2 oz	1-Slight 2-Moderate 3-High 4-Extreme



SECTION I. MANUFACTURER AND LOCATION

Manufacturer: International Lubricants, Inc.
Location: P.O. Box 24743, Seattle, WA 98124-0743
Telephone: (206) 7625-5343
Emergency Contact: CHEMTEL, (800) 255-3924

SECTION II. MATERIAL IDENTIFICATION AND INFORMATION

COMPONENT	CAS NUMBER	TLV/PEL (MG/M ³)	VOLUME %
Isobutane	75-28-5	1000/1000	15 - 25
Propane	74-98-6	1800	5 - 15
Acetone	67-64-1	500/1000	20 - 34
Aluminum Flake	7429-90-5	10/15	25 - 35
Triethylbenzene	95-63-6	100/100	1 - 4

The specific chemical name and composition of the components not disclosed is confidential business information and is withheld as permitted by 29CFR 1910.1200 and various state Right-to-Know laws.

This material is not known to contain any chemical listed as a carcinogen or suspected carcinogen by OSHA Hazard Communication Standard 29CFR 1910.1200, IARC, or the National Toxicology Program (NTP) at a concentration greater than 0.1%.

Squeak Relief® does not contain, as an ingredient, chlorine, phenols, nitrites, heavy metals, arsenic, PCB, PCT, TCDD or other Dioxin related substances.

California – California Proposition 65 No regulated Ingredients.

SECTION III. PHYSICAL AND CHEMICAL PROPERTIES

765-2630, 765-2631

Chemical Name:	Mixture
Form:	Silver colored liquid aerosol
Odor:	Slightly aromatic under pressure
Specific Gravity (Water = 1.00):	0.5-0.65
Melting Point:	NE
Boiling Point:	- 18°C
Volatility, weight % at 25°C:	Negligible
Evaporation Rate:	Negligible
Vapor Pressure, mmHg at 25°C:	< 2 mm
Solubility in Water:	Negligible
Stability:	Stable under normal conditions

SECTION IV. FIRE AND EXPLOSION DATA

Flashpoint (Cleveland Open Cup):	> - 100°F
Auto Ignition Temperature:	ND
Flammable Limits:	ND
Fire Extinguishing Agents:	Water spray (fog), dry chemical, foam, or CO ₂ . Water stream may splash burning liquid and spread fire. Do not use halogenated extinguishing agents.
Special Fire Fighting Procedures:	As for petroleum products. Do not use direct or heavy water stream to fight fire. Use self-contained breathing apparatus to fight fires.

SECTION V. FIRST AID

Contact with EYES:	Immediately flush with large quantities of cool water for at least 15 minutes. Get medical attention.
Contact with SKIN:	Wash off with soap and water.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
Ingestion:	Do not induce vomiting. Get emergency medical attention.

SECTION VI. REACTIVITY

765-2630, 765-2631

Reactivity:	Stable under normal temperatures and pressures.
Incompatibilities:	Strong oxidizing agents, halogens, heat, open flame.
Hazardous Polymerization:	Has not been known to occur.
Hazardous Decomposition Products:	CO ₂ , CO, aluminum oxide

SECTION VII. SPECIAL PROTECTION INFORMATION

Ventilation (Local, Mechanical, Special):	Use in a well ventilated area with local exhaust ventilation.
Respiratory Protection:	None required in normal use. Use only NIOSH/MSHA
Gloves:	Not required in normal use.
Eye Protection:	Goggles or safety glasses are recommended.
Other Protective Equipment:	Practice good personal hygiene. Wash hands after using and handling.

SECTION VIII. ENVIRONMENTAL PROCEDURES

Spills or Leaks:	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Take up small spills with dry chemical absorbent. Large spills may be taken up with pump or vacuum and finished off with dry chemical absorbent. May require excavation of contaminated soil.
Waste Disposal:	To the best of International Lubricants, Inc.'s knowledge, this product is not regulated by CERCLA/RCRA as a hazardous waste or material. However, this product has not been tested for the toxicity characteristic via the Toxicity Characteristic Leaching Procedure. Therefore, it may be disposed of as an industrial waste in a manner acceptable local, state, and federal regulations.
Right-to-Know:	There is no requirement to report this product under existing SARA Title III regulations.
TSCA:	This material is in compliance with the Toxic Substances Control Act (15 USC 2601 – 2629).

SECTION IX. STORAGE AND HANDLING

765-2630, 765-2631

Keep containers sealed until ready to use. Avoid excessive long-term storage temperatures to prolong shelf life. Maximum storage temperature: 120°F. Store in well ventilated areas.

SECTION X. TRANSPORT

D.O.T. Shipping Name:	Brake Finishing Treatment
D.O.T. ID Number:	UN1950
Reportable Quantity:	NE
Special Transportation Notes:	Flammable aerosol

Notes: NA = Not Applicable
 NE = Not Established

International Lubricants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. No warranty of fitness, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and of the information referred to herein are beyond the control of International Lubricants, Inc., International Lubricants, Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Origin Date:	06/12/01
Revision Date:	NA
Reformatted Date:	NA
Supersedes:	NA

Prepared by: _____

End of Material Safety Data Sheet