Printing date 12/7/2012 Revision:3/29/2016

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Bar's Leaks® Radiator Stop Leak Pellitized
- · Article number: PLT11
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Anti-Leak product for radiators.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Bar's Products P.O. Box 187 Holly, MI 48442 USA Phone: (810) 603-1321



ChemTel Inc.

(800)255-3924, +1 (813)248-0585



2 Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1B H317 May cause an allergic skin reaction.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/38: Irritating to eyes and skin.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 1)

· Hazard pictograms



- · Signal word Warning
- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

Keep out of reach of children. P102

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling. P264

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

- · Hazard description:
- · WHMIS-symbols:

D2B - Toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 1Fire = 1Reactivity = 0

HMIS-ratings (scale 0 - 4)



1 Health = 1 Fire = 1Reactivity = 0

· HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. vPvB: Not applicable.

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 2)

3 Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 69029-75-0	SULFURIZED MINERAL OIL XI R36/38	50-100%
CAS: 68608-26-4	Sulfonic acids sodium salts Xn R22; Xi R36/38	2,5-10%
CAS: 61790-12-3 EINECS: 263-107-3	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Tall Oil Fatty Acid Xn R21	2,5-10%
CAS: 102-71-6 EINECS: 203-049-8	2,2',2"-nitrilotriethanol substance with a Community workplace exposure limit	≤ 2,5%
CAS: 107-41-5 EINECS: 203-489-0	2-methylpentane-2,4-diol Xi R36/38	≤ 2,5%
Index number: 603-053-00-3	Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 497-19-8 EINECS: 207-838-8	sodium carbonate Xi R36	≤ 2,5%
Index number: 011-005-00-2	•	
CAS: 9036-19-5	Polyethylene glycol octylphenyl ether Xi R41	≤ 2,5%
	♦ Eye Dam. 1, H318	
CAS: 25322-68-3 NLP: 500-038-2	Polyethylene glycol substance with a Community workplace exposure limit	≤ 2,5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 5)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 4)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

102-71-6 2,2',2"-nitrilotriethanol

TLV (USA) 5 mg/m³ EL (Canada) 5 mg/m³

EV (Canada) 3.1 mg/m³, 0.5 ppm

107-41-5 2-methylpentane-2,4-diol

REL (USA) Short-term value: C 125 mg/m³, C 25 ppm TLV (USA) Short-term value: C 121 mg/m³, C 25 ppm

EL (Canada) Short-term value: C 25 ppm

25322-68-3 Polyethylene glycol

WEEL (USA) 10 mg/m³ aerosol

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Contact lenses should not be worn.



Safety glasses

· Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

No further relevant information available.

9 Physical and chemical properties

General Information		
Appearance:		
Form:	Water dispersible granulate	
Colour:	Dark brown	
Odour:	Petroleum-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	> 138 °C (> 280 °F)	
Flash point:	> 138 °C (> 280 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	0.96 g/cm ³	
Relative density	Not determined.	

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

		(Contd. of page
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	2.0 %	
Solids content:	6.0 %	
· 9.2 Other information	No further relevant information available.	

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Powdered aluminium and zinc catalyse decomposition.

Reacts with strong oxidizing agents.

Reacts with ammonia.

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

11 Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitizing effect by skin contact is possible by prolonged exposure.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 7)

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

Transport information		
14.1 UN-Number		
DOT, ADR, ADN, IMDG, IATA	N/A	
14.2 UN proper shipping name		
DOT, ADR, ADN, IMDG, IATA	N/A	
14.3 Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	N/A	
14.4 Packing group		
DOT, ADR, IMDG, IATA	N/A	
14.5 Environmental hazards:		
Marine pollutant:	No	

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 8)

• 14.6 Special precautions for user Not applicable.

• 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation":

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- · SARA

Section 355 (extremely hazardous substances):	hetances).	hazardous subs	(extremely l	ion 355	Section

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · TSCA (Toxic Substances Control Act):
- 69029-75-0 SULFURIZED MINERAL OIL
- 68608-26-4 Sulfonic acids sodium salts
- 61790-12-3 Tall Oil Fatty Acid
 - 458-37-7 1,7-bis(4-hydroxy-3-methoxyphenyl)hepta-1,6-diene-3,5-dione
 - 102-71-6 2,2',2"-nitrilotriethanol
 - 107-41-5 2-methylpentane-2,4-diol
 - 497-19-8 sodium carbonate
- 9036-19-5 Polyethylene glycol octylphenyl ether
- 25322-68-3 Polyethylene glycol
- · Proposition 65 (California):
- · Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic Categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

	(Contd. of pa
IARC (International Agency for Research on Cancer)	<u> </u>
102-71-6 2,2',2"-nitrilotriethanol	
TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
Canada	
Canadian Domestic Substances List (DSL)	
69029-75-0 SULFURIZED MINERAL OIL	
68608-26-4 Sulfonic acids sodium salts	
61790-12-3 Tall Oil Fatty Acid	
458-37-7 1,7-bis(4-hydroxy-3-methoxyphenyl)hepta-1,6-diene-3,5-dione	
102-71-6 2,2',2"-nitrilotriethanol	
107-41-5 2-methylpentane-2,4-diol	
497-19-8 sodium carbonate	
9036-19-5 Polyethylene glycol octylphenyl ether	
25322-68-3 Polyethylene glycol	
Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 1%)	
102-71-6 2,2',2"-nitrilotriethanol	
107-41-5 2-methylpentane-2,4-diol	
497-19-8 sodium carbonate	
9036-19-5 Polyethylene glycol octylphenyl ether	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- R21 Harmful in contact with skin.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R36/38 Irritating to eyes and skin.

(Contd. on page 11)

Printing date 12/7/2012 Revision: 3/29/2016

Trade name: Bar's Leaks® Radiaor Stop Leak Pellitized

(Contd. of page 10)

R41 Risk of serious damage to eyes.

· Abbreviations and acronyms:

Website: www.chemtelinc.com

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

Sources

SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

