

MATERIAL SAFETY DATA SHEET

Effective Date: 1-21-98 Revision Date: none
Slick 50 Advanced Formula Engine Treatment 41306032
Code: BCI Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: Slick 50 Advanced Formula Engine Treatment 41306032

MANUFACTURER'S NAME:
Blue Coral/Slick 50 Ltd.
5700 South Lee Road
Maple Heights, OH 44137

EMERGENCY TELEPHONE NUMBER
(800)546-6040

MISCELLANEOUS INFORMATION
(800)458-4998

Section 2 - Hazardous Ingredients

HAZARDOUS COMPONENTS CAS NUMBER OSHA PEL ACGIH TLV % OPTIONAL
Petroleum Oil 64742-65-0 5mg/m3

Antiwear Rust & Oxidation Inhibitor mixture NA

Section 3 - Hazards Identification

HEALTH HAZARDS (Acute or Chronic)
Mild irritant
SIGNS AND SYMPTOMS OF EXPOSURE
Fumes may cause drowsiness, nausea, headache or lung irritation
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Section 4 - First Aid Measures

EMERGENCY AND FIRST AID PROCEDURES
Inhalation: Remove victim to fresh air, restore support breathing if
required,
see, prompt medical attention.
Skin contact: Wash with soap & water; if irritation persists, seek medical
attention.
Eye contact: Flush with large volumes of water for 15 minutes; seek medical
attention.
Ingestion: Do not induce vomiting; seek prompt medical attention.

Section 5 - Firefighting Measures

FLASH POINT (Method Used) FLAMMABLE LIMITS LEL UEL
392F N/A N/A

EXTINGUISHING MEDIA
CO2 , Dry Chemical, Foam, Water Fog
SPECIAL FIRE FIGHTING PROCEDURES
None

UNUSUAL FIRE AND EXPLOSION HAZARDS

None

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 1-21-98

Revision Date: none

Slick 50 Advanced Formula Engine Treatment 41306032

Code: BCI

Page: 2

=====

Section 6 - Environmental Release Measures

No information.

=====

Section 7 - Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store below 150F, keep away from high heat or flame. Keep separate from strong oxidizing agents.

OTHER PRECAUTIONS

Keep out of reach of children

HMIS NFPA

Health 0 0

Flammability 1 1

Reactivity 0 0

=====

Section 8 - Exposure Controls/Personal Protection

RESPIRATORY PROTECTION (Specify Type)

Provide properly engineered ventilation to maintain oil mist levels below OSHA PEL & TLV-TWA of 5 mg/cubic meter.

VENTILATION LOCAL EXHAUST MECHANICAL (General)

Recommended

SPECIAL OTHER

PROTECTIVE GLOVES EYE PROTECTION OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Recommended goggles

WORK/HYGIENIC PRACTICES

=====

Section 9 - Physical and Chemical Properties

BOILING POINT SPECIFIC GRAVITY (H2O = 1)

665F 0.872

VAPOR PRESSURE (mm Hg.) MELTING POINT

N/D

VAPOR DENSITY (AIR = 1) EVAPORATION RATE (Butyl Acetate = 1)

>1.0 <1.0

SOLUBILITY IN WATER pH

negligible

APPEARANCE AND ODOR

Amber Oil

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 1-21-98

Revision Date: none

Slick 50 Advanced Formula Engine Treatment 41306032

Code: BCI

Page: 3

=====
Section 10 - Stability and Reactivity

STABILITY UNSTABLE STABLE CONDITIONS TO AVOID

X None known to Blue Coral-Slick 50, LTD.

INCOMPATIBILITY (Materials to Avoid)

Strong Oxidants

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS

CO2, Traces S, P, Zn, CA MG

HAZARDOUS MAY OCCUR WILL NOT OCCUR CONDITIONS TO AVOID

POLYMERIZATION X None known to Blue Coral-Slick 50, LTD.

=====
Section 11 - Toxicological Information

No information.

=====
Section 12 - Ecological Information

No information.

=====
Section 13 - Disposal Considerations

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Apply inert absorbent

WASTE DISPOSAL METHOD

Dispose of in accordance with Local, State & Federal regulations

=====
Section 14 - Transport Information

DOT PROPER SHIPPING NAME NONE

DOT HAZARD CLASS N/A

DOT I.D. NUMBER N/A

IATA PROPER SHIPPING NAME NONE

IATA HAZARD CLASS N/A

IMO NUMBER N/A

=====
Section 15 - Regulatory Information

No information.

=====
Section 16 - Other Information