Safety Data Sheet



Section 1: Identification

Product identifier

Product Name · NAPA Fuel Stabilizer and Ethanol Treatment

Synonyms • 590410 Product Code • 5800

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Fuel stabilizer

Restrictions on use • Do NOT use in diesel fuel

Details of the supplier of the safety data sheet

Manufacturer
 Gold Eagle Co.

4400 S. Kildare Avenue Chicago, IL 60632-4372

United States

http://www.goldeagle.com/

Telephone (General) • 773-376-4400

Emergency telephone number

• 1-800-535-5053 - (INFOTRAC #22283)

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Flammable Liquids 4

Aspiration 1

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Carcinogenicity 2
Reproductive Toxicity 2

Label elements

OSHA HCS 2012

DANGER





Hazard statements · Combustible liquid

May be fatal if swallowed and enters airways

May cause drowsiness or dizziness

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Avoid breathing mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • In case of fire: Use appropriate media for extinction.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or


international regulations.

Other hazards

OSHA HCS 2012

 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Other information



Section 3 - Composition/Information on Ingredients

Substances

· Material does not meet the criteria of a substance.

Mixtures

Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive		
Distillates (petroleum), hydrotreated	CAS:64742-47-	0% TO	NDA	OSHA HCS 2012: Flam. Liq. 4; Asp. Tox. 1; STOT SE 3:		
light	8	90%	INDA	Narc.		
Proprietary additive	Proprietary	0% TO 10%	NDA	OSHA HCS 2012: Not Classified		

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

 In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Remove and isolate contaminated clothing. Wash skin with soap and water.

Eye

 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get medical attention immediately.

Ingestion

• Do NOT induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Use carbon dioxide, dry chemical, foam and/or water fog.

Unsuitable Extinguishing Media

· No data available

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers. Combustible material: may burn but does not ignite readily.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Water may cause frothing.

Hazardous Combustion Products

No data available

Advice for firefighters

• Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Move containers from fire area if you can do it without risk.

LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

• Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no

smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.

Absorb or cover with dry earth, sand or other non-combustible material and transfer to

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

 Use only in well ventilated areas. Avoid contact with heat and ignition sources. Take precautionary measures against static charges. Do not use sparking tools. All equipment used when handling the product must be grounded. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing . Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage

· Store in a tightly closed container. Keep away from incompatible materials. Store in a well-ventilated place. Store in an area equipped with automatic sprinklers or fire extinguishing system. Store below 150° F. Empty containers contain product residues, assume emptied containers to have same hazards as full containers.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure controls

Engineering Measures/Controls · Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Pictograms





Respiratory

· In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear safety glasses.

Skin/Body

Wear appropriate gloves.

Environmental Exposure Controls

Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description				
Physical Form	Liquid	Appearance/Description	Red liquid with a solvent odor.	
Color	Red	Odor	Solvent	
Odor Threshold	No data available			
General Properties			-	
Boiling Point	g Point 180 F(82.2222 C) Me		No data available	
Decomposition Temperature	No data available	рН	No data available	
Specific Gravity/Relative Density	= 0.8 Water=1	Water Solubility	Negligible < 0.1 %	
Viscosity 3 Centistoke (cSt, cS) or mm2/sec @ 40 C(104 F)		Explosive Properties	No data available	
Oxidizing Properties:	No data available			
Volatility				
Vapor Pressure	por Pressure 97 mmHg (torr)		> 1 Air=1	
Evaporation Rate	> 1 n-Butyl Acetate = 1	VOC (Wt.)	100 %	
Volatiles (Vol.)	100 %			
Flammability			•	
Flash Point	h Point > 141.5 F(> 60.8333 C)		0.8 %	
LEL	7 %	Autoignition	No data available	
Flammability (solid, gas)	Not relevant.			

Section 10: Stability and Reactivity

Reactivity

· No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

· Excess heat. Incompatible materials.

Incompatible materials

· Strong oxidants.

Hazardous decomposition products

• Excessive heating and/or incomplete combustion will produce carbon monoxide.

Section 11 - Toxicological Information

Information on toxicological effects

Components				
Proprietary additive (0% TO 10%)	Proprietary	Acute Toxicity: Ingestion/Oral-Rat LDLo • 5 mL/kg; Sense Organs and Special Senses:Olfaction:Other changes; Sense Organs and Special Senses:Eye:Other; Skin and Appendages:Other:Hair; Inhalation-Rat LC50 • >590 mg/m³ 4 Hour(s); Skin-Rabbit LD50 • >2 mL/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Changes in motor activity (specific assay); Behavioral:Irritability; Irritation: Skin-Rabbit • 500 µL 24 Hour(s) • Mild irritation		

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	OSHA HCS 2012 • Data lacking
Acute toxicity	OSHA HCS 2012 • Data lacking
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 2
Skin corrosion/Irritation	OSHA HCS 2012 • Data lacking
Skin sensitization	OSHA HCS 2012 • Data lacking
STOT-RE	OSHA HCS 2012 • Data lacking
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Toxicity for Reproduction	OSHA HCS 2012 • Toxic to Reproduction 2
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking

Potential Health Effects Inhalation

Acute (Immediate)

 May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

Material is classified as non-irritant and non-corrosive using GHS criteria.

Chronic (Delayed)

· No data available.

Skin

Acute (Immediate)

Chronic (Delayed)

No data available.

Eye

Acute (Immediate)

Material is classified as non-irritant using GHS criteria.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

 Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

Chronic (Delayed)

No data available.

Carcinogenic Effects

 Suspected of causing cancer. This product contains components that are considered carcinogenic by OSHA, IARC, NTP.

Reproductive Effects

Animal tests for components have shown adverse reproductive effects.

Key to abbreviations

LD = Lethal Dose TC = Toxic Concentration

MLD = Mild TD = Toxic Dose

SEV = Severe

Section 12 - Ecological Information

Toxicity

 Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

 Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

 Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

 Non-mandatory section - information about this substance not complied for this reason.

Other adverse effects

Non-mandatory section - information about this substance not complied for this reason.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	None applicable	Gasoline Additive, N.O.I.	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Acute. Chronic

United States

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

Not Listed

U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Flammable Substances

Not Listed

U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Toxic Substances

Not Listed

Preparation Date: 24/September/2015 Revision Date: 24/September/2015

Format: GHS Language: English (US) OSHA HCS 2012 U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Not Lister

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

Not Listed

U.S. - CWA (Clean Water Act) - Hazardous Substances

Not Listed

U.S. - CWA (Clean Water Act) - Toxic Pollutants

Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Not Listed

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Section 16 - Other Information

Revision Date

Preparation Date

Other Information

Disclaimer/Statement of Liability

24/September/2015

24/September/2015

Schedule B Number: 3811.90.0000.

Information presented herein is believed to be factual, as it has been derived from the
works and opinions of persons believed to be qualified experts. However, nothing
contained in this information is to be taken as warranty or representation for which the
Gold Eagle Co. bears legal responsibility. The user should review any

recommendations in the specific context of the intended use to determine whether they are appropriate.

Key to abbreviations

NDA = No Data Available