Safety Data Sheet



Section 1: Identification

Product identifier

Product Name • NAPA Diesel Fuel Conditioner with Antigel

Synonyms • 590159

Product Code • 9600; 9601; 9612

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Read label for use directions and claims

Restrictions on use • For use only in diesel fuel

Details of the supplier of the safety data sheet

Manufacturer
 Gold Eagle Co.

4400 S. Kildare Avenue Chicago, IL 60632-4372

United States

http://www.goldeagle.com/

Telephone (General) • 773-376-4400

Emergency telephone number

Manufacturer • 1-800-535-5053 - (INFOTRAC #22283)

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Flammable Liquids 4

Aspiration 1

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Carcinogenicity 2
Reproductive Toxicity 1B

Label elementsOSHA HCS 2012

DANGER





Hazard statements · Combustible liquid

May be fatal if swallowed and enters airways

May cause drowsiness or dizziness Suspected of causing cancer.

May damage fertility or the unborn child.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Avoid breathing mists, vapours, and/or spray. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use appropriate media for extinction.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

Call a POISON CENTER or doctor/physician if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Store in a well-ventilated place. Keep container tightly closed.

> Keep cool. Store locked up.


Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

OSHA HCS 2012 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Other information



Section 3 - Composition/Information on Ingredients

Substances

· Material does not meet the criteria of a substance.

Mixtures

Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive		
Distillates (petroleum), hydrotreated light	CAS :64742-47-8	0% TO 50%	NDA	OSHA HCS 2012: Flam. Liq. 4; Asp. Tox. 1; STOT SE 3: Narc.		
2-Ethylhexyl nitrate	CAS: 27247- 96-7	0% TO 24%	NDA	OSHA HCS 2012: Flam. Liq. 4		
Proprietary	Proprietary	<= 10%	NDA	OSHA HCS 2012: Flam. Liq. 4; Eye Irrit. 2; STOT SE 3: Narc.		
Solvent naphtha	CAS :64742- 94-5	0% TO 6%	NDA	OSHA HCS 2012: Not Classified		
1,2,4-Trimethylbenzene	CAS:95-63-6	0% TO 4%	NDA	OSHA HCS 2012: Flam. Liq. 3; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3: Narc; STOT SE 3: Resp. Irrit. (inhl); Asp. Tox. 1		
Solvent naphtha (petroleum), light aromatic	CAS :64742- 95-6	0% TO 3.7%	NDA	OSHA HCS 2012: Eye Irrit. 2; Asp. Tox. 1		

Preparation Date: 16/October/2015

Format: GHS Language: English (US) OSHA HCS 2012 Revision Date: 16/October/2015 Page 2 of 15

1,3,5-Trimethylbenzene	CAS :108-67-	0% TO 0.6%	NDA	OSHA HCS 2012: Flam. Liq. 3; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3: Resp. Irrit.; STOT SE 3: Narc.; Asp. Tox. 1
1,2,3-Trimethylbenzene	CAS :526-73-	0% TO 0.6%	NDA	OSHA HCS 2012: Flam. Liq. 3; STOT SE 3: Narc.
Xylene	CAS :1330- 20-7	0% TO 0.5%	NDA	OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (inhl); Skin Irrit. 2; Eye Irrit. 2; Repr. 1B (Inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit.
Naphthalene	CAS :91-20-3	0% TO 0.499%	NDA	OSHA HCS 2012: Flam. Sol. 2; Acute Tox. 4 (orl); Skin Irrit. 2; Muta. 2; Carc. 2; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (Blood, Eyes; Orl, Inhl)
1-Methylethylbenzene	CAS:98-82-8	0% TO 0.12%	NDA	OSHA HCS 2012: Flam. Liq. 3; Acute Tox. 4 (orl); Skin Irrit. 2; Eye Irrit. 2; Carc. 2 (inhl); STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (inhl); Asp. Tox. 1

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

Skin

 In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Remove and isolate contaminated clothing. Wash skin with soap and water.

Eye

 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get medical attention immediately.

Ingestion

• Do NOT induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Use carbon dioxide, dry chemical, foam and/or water fog.

Unsuitable Extinguishing Media

Water spray or fog can cool fire but may not be effective in extinguishing fire.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

· Containers may explode when heated.

Vapor explosion hazard indoors, outdoors or in sewers.

Combustible material: may burn but does not ignite readily.

Many liquids are lighter than water.

Most vapors are heavier than air. They will spread along ground and collect in low or

confined areas (sewers, basements, tanks).

Runoff to sewer may create fire or explosion hazard.

Vapors may form explosive mixtures with air.

Vapors may travel to source of ignition and flash back.

Water may cause frothing.

Hazardous Combustion Products

· No data available

Advice for firefighters

Structural firefighters' protective clothing will only provide limited protection.
 Wear positive pressure self-contained breathing apparatus (SCBA).
 Move containers from fire area if you can do it without risk.
 LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Ventilate enclosed areas. Do not walk through spilled material. Use appropriate
Personal Protective Equipment (PPE) Do not touch damaged containers or spilled
material unless wearing appropriate protective clothing.

Emergency Procedures

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

Stop leak if you can do it without risk.
 Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors.

All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Use only in well ventilated areas. Avoid contact with heat and ignition sources. Take
precautionary measures against static charges. Do not use sparking tools. All
equipment used when handling the product must be grounded. Wear appropriate
personal protective equipment, avoid direct contact. Avoid breathing mist, vapours,
spray. Avoid contact with skin, eyes, and clothing. Wash thoroughly with soap and
water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities

Storage

Store in a tightly closed container. Store in a well-ventilated place. Store below 150°
 F. Store in an area equipped with automatic sprinklers or fire extinguishing system.

 Empty containers contain product residues, assume emptied containers to have same hazards as full containers. Do not apply high heat or flame to containers. Keep separate from strong oxidizing agents.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines					
Result ACGIH NIOSH OSHA					

Naphthalene	TWAs 10 ppm TWA		10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA; 50 mg/m3 TWA
(91-20-3)	STELs	Not established	15 ppm STEL; 75 mg/m3 STEL	Not established
1- Methylethylbenzene (98-82-8)	TWAs	/As 50 ppm TWA 50 ppm TWA; 245 mg/m3 TWA		50 ppm TWA; 245 mg/m3 TWA
Xylene	TWAs	100 ppm TWA	Not established	100 ppm TWA; 435 mg/m3 TWA
(1330-20-7)	STELs	150 ppm STEL	Not established	Not established
1,2,3- Trimethylbenzene (526-73-8)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established
1,2,4- Trimethylbenzene (95-63-6)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established
1,3,5- Trimethylbenzene (108-67-8)	TWAs	Not established	25 ppm TWA; 125 mg/m3 TWA	Not established
Proprietary	TWAs	100 ppm TWA	100 ppm TWA; 600 mg/m3 TWA	100 ppm TWA; 600 mg/m3 TWA
(Proprietary)	STELs	150 ppm STEL	150 ppm STEL; 900 mg/m3 STEL	Not established

Exposure controls

Engineering Measures/Controls

 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Respiratory

 In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear chemical splash safety goggles.

Skin/Body

Wear appropriate gloves.

Environmental Exposure Controls

Controls should be engineered to prevent release to the environment, including
procedures to prevent spills, atmospheric release and release to waterways. Follow
best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures
TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description						
Physical Form	Liquid	Appearance/Description	Amber liquid with a solvent odor.			
Color	Amber	Odor	Solvent			
Odor Threshold	No data available					
General Properties						
Boiling Point	No data available	Melting Point/Freezing Point	-40 F(-40 C)			
Decomposition Temperature	> 212 F(> 100 C)	рН	No data available			
Specific Gravity/Relative Density	= 0.86 Water=1	Water Solubility	Negligible < 0.1 %			

Viscosity	4 Centistoke (cSt, cS) or mm2/sec					
Volatility						
Vapor Pressure	0.035 mmHg (torr)	Vapor Density	4.5 Air=1			
Evaporation Rate	< 1 n-Butyl Acetate = 1	VOC (Wt.)	100 %			
VOC (Vol.)	100 %	Volatiles (Wt.)	100 %			
Volatiles (Vol.) 100 %						
Flammability	Flammability					
Flash Point	170 F(76.6667 C) CC (Closed Cup)	UEL	5.5 %			
LEL	0.6 %	Autoignition	215 C(419 F)			
Flammability (solid, gas)	No data available					

Section 10: Stability and Reactivity

Reactivity

• No dangerous reaction known under conditions of normal use.

Chemical stability

· Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

• Keep away from heat, sparks, and flame. Incompatible materials.

Incompatible materials

· Strong oxidants.

Hazardous decomposition products

 Decomposes with heat. Hazardous gases/vapors produced are oxides of nitrogen and carbon monoxide. Decomposition temperature is >212°F.

Section 11 - Toxicological Information

Information on toxicological effects

		Components
2-Ethylhexyl nitrate (0% TO 24%)	27247-96- 7	Acute Toxicity: Ingestion/Oral-Rat LD50 • >10 mL/kg; Skin-Rabbit LD50 • >5 mL/kg; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 2800 mg/kg 28 Day(s)-Continuous; Liver:Changes in liver weight; Kidney, Ureter, and Bladder:Changes in tubules (including acute renal failure, acute tubular necrosis); Kidney, Ureter, and Bladder:Other changes in urine composition
Solvent naphtha (0% TO 6%)	64742-94- 5	Acute Toxicity: Inhalation-Rat LC50 • >590 mg/m³ 4 Hour(s); Skin-Rabbit LD50 • >2 mL/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Changes in motor activity (specific assay); Behavioral:Irritability; Irritation: Skin-Rabbit • 500 µL 24 Hour(s) • Mild irritation
1,2,4-Trimethylbenzene (0% TO 4%) 95-63-6		Acute Toxicity: Ingestion/Oral-Rat LD50 • 5 g/kg; Inhalation-Rat LC50 • 18000 mg/m³ 4 Hour(s); Multi-dose Toxicity: Inhalation-Rat TCLo • 100 ppm 6 Hour(s) 20 Day(s)-Intermittent; Behavioral:Changes in motor activity (specific assay); Behavioral:Analgesia; Behavioral:Alteration of operant conditioning; Inhalation-Rat TCLo • 20 mg/m³ 16 Week(s)-Continuous; Kidney, Ureter, and Bladder:Other changes in urine composition
		Acute Toxicity: Ingestion/Oral-Rat LD50 • 490 mg/kg; Ingestion/Oral-Mouse TDLo • 158 mg/kg; Brain and Coverings:Other degenerative changes; Liver:Other changes; Biochemical:Metabolism (intermediary):Lipids, including transport; Inhalation-Human TCLo • 250 mg/m³; Sense Organs and Special Senses:Eye:Lacrimation; Behavioral:Headache; Skin-Rabbit LD50 • >20 g/kg; Unreported-

Naphthalene (0% TO 0.499%)	91-20-3	Guinea Pig LD50 • 1200 mg/kg; Behavioral:Somnolence (general depressed activity); Irritation: Skin-Rabbit • 0.05 mL 24 Hour(s) • Severe irritation; Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 500 mg/kg 10 Day(s)-Intermittent; Behavioral:Sleep; Lungs, Thorax, or Respiration:Dyspnea; Ingestion/Oral-Rat TDLo • 4500 mg/kg 10 Day(s)-Intermittent; Brain and Coverings:Other degenerative changes; Mutagen: Specific locus test • Inhalation-Rat • 30 ppm 13 Week(s)-Intermittent; Micronucleus test • Unreported Route-Human • Lymphocyte (Somatic cell) • 30 mg/L; Reproductive: Ingestion/Oral-Mouse TDLo • 2400 mg/kg (7-14D preg); Reproductive Effects:Effects on Newborn:Live birth index; Reproductive Effects:Effects on Newborn:Viability index (e.g., # alive at day 4 per # born alive); Ingestion/Oral-Rat TDLo • 4500 mg/kg (6-15D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Other developmental abnormalities; Tumorigen / Carcinogen: Inhalation-Mouse TCLo • 30 ppm 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Neoplastic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Inhalation-Rat TCLo • 1575 mg/kg 105 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors; Inhalation-Rat TCLo • 60 ppm 6 Hour(s) 105 Week(s)- Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors
Solvent naphtha (petroleum), light aromatic (0% TO 3.7%)	64742-95- 6	Acute Toxicity: Ingestion/Oral-Rat LD50 • 8400 mg/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Tremor; Lungs, Thorax, or Respiration:Other changes; Irritation: Eye-Rabbit • 100 μL 24 Hour(s) • Mild irritation; Reproductive: Inhalation-Rat TCLo • 1500 ppm (9W male/9W pre-16D post); Reproductive Effects:Effects on Newborn:Growth statistics (e.g., reduced weight gain)
1,3,5-Trimethylbenzene (0% TO 0.6%)	108-67-8	Acute Toxicity: Ingestion/Oral-Rat LD50 • 5000 mg/kg; Inhalation-Rat LC50 • 24000 mg/m³ 4 Hour(s); Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Skin-Rabbit • 20 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 100 ppm 6 Hour(s) 20 Day(s)-Intermittent; Behavioral:Changes in motor activity (specific assay); Behavioral:Analgesia; Behavioral:Alteration of operant conditioning; Inhalation-Rat TCLo • 20 mg/m³ 16 Week(s)-Continuous; Kidney, Ureter, and Bladder:Other changes in urine composition
1,2,3-Trimethylbenzene (0% TO 0.6%)	526-73-8	Multi-dose Toxicity: Inhalation-Rat TCLo • 100 ppm 6 Hour(s) 20 Day(s)-Intermittent; Behavioral:Alteration of classical conditioning
1-Methylethylbenzene (0% TO 0.12%)	98-82-8	Acute Toxicity: Ingestion/Oral-Rat LD50 • 1400 mg/kg; Gastrointestinal:Gastritis; Inhalation-Rat LC50 • 39000 mg/m³ 4 Hour(s); Inhalation-Human TCLo • 200 ppm; Behavioral:Somnolence (general depressed activity); Behavioral:Antipsychotic; Behavioral:Irritability; Inhalation-Mouse TCLo • 5150 mg/m³ 2 Hour(s); Behavioral:General anesthetic; Inhalation-Rat TCLo • 300 ppm 30 Minute(s); Lungs, Thorax, or Respiration:Respiratory depression; Skin-Rabbit LD50 • 12300 μL/kg; Irritation: Eye-Rabbit • 500 mg 24 Hour(s) • Mild irritation; Skin-Rabbit • 100 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Mouse TCLo • 2000 mg/m³ 14 Week(s)-Continuous; Behavioral:Somnolence (general depressed activity); Inhalation-Rabbit TCLo • 10000 mg/m³ 2 Hour (s) 24 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Acute pulmonary edema; Blood:Hemorrhage; Blood:Changes in leucocyte (WBC) count; Inhalation-Rat TCLo • 1200 ppm 6 Hour(s) 13 Week(s)-Intermittent; Sense Organs and Special Senses:Eye:Other; Behavioral:Changes in motor activity (specific assay); Blood:Pigmented or nucleated red blood cells; Mutagen: Mutation in microorganisms • Unreported Route-Salmonella typhimurium • 100 μg/plate 3 Hour(s) (-S9)
Xylene (0% TO 0.5%)	1330-20-7	Acute Toxicity: Ingestion/Oral-Rat LD50 • 4300 mg/kg; Liver:Other changes; Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat LC50 • 5000 ppm 4 Hour(s); Inhalation-Human TCLo • 200 ppm; Sense Organs and Special Senses:Olfaction:Other changes; Sense Organs and Special Senses:Eye:Conjunctive irritation; Lungs, Thorax, or Respiration:Other changes; Skin-Rabbit LD50 • >1700 mg/kg; Irritation: Eye-Rabbit • 5 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 1000 ppm 6 Hour(s) 8 Day(s)-Intermittent; Nutritional and Gross Metabolic:Gross Metabolite Changes:Weight loss or decreased weight gain; Reproductive: Inhalation-Rat TCLo • 1000 ppm 6 Hour(s)(7-20D preg); Reproductive Effects:Effects on Fertility:Abortion; Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s)(1-21D preg); Reproductive Effects:Effects on Fertility:Post-implantation mortality; Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity

Abnormalities: Craniofacial (including nose and tongue); Inhalation-Rat TDLo		(except death, e.g., stunted fetus); Reproductive Effects: Specific Developmental Abnormalities: Craniofacial (including nose and tongue); Inhalation-Rat TDLo • 200 ppm 6 Hour(s)(4-20D preg); Reproductive Effects: Specific Developmental Abnormalities: Musculoskeletal system; Reproductive Effects: Effects on Newborn: Behavioral
Proprietary (<= 10%)		Acute Toxicity: Ingestion/Oral-Rat LD50 • 5400 μL/kg; Skin-Rabbit LD50 • 10 mL/kg; Irritation: Eye-Human • 8 mg • Mild irritation; Skin-Rabbit • 500 mg-Open • Mild irritation

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • No data available
Acute toxicity	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 2
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
Toxicity for Reproduction	OSHA HCS 2012 • Toxic to Reproduction 1B
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available

Potential Health Effects

Inhalation

Acute (Immediate)

- May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- **Chronic (Delayed)**

· No data available.

Skin

Acute (Immediate)

Chronic (Delayed)

Material is classified as non-irritant and non-corrosive using GHS criteria.

No data available.

Eye

Acute (Immediate)

Material is classified as non-irritant using GHS criteria.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

 Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.

Chronic (Delayed)

· No data available.

Carcinogenic Effects

Suspected of causing cancer. This product contains components that are considered carcinogenic by OSHA, IARC, NTP.

Carcinogenic Effects					
CAS IARC NTP					
1-Methylethylbenzene	98-82-8	Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen		
Naphthalene 91-20-3		Group 2B-Possible Carcinogen	Reasonably Anticipated to be Human Carcinogen		

Reproductive Effects

· Animal tests for components have shown adverse reproductive effects.

Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information

Toxicity

 Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

Non-mandatory section - information about this substance not complied for this reason.

Other adverse effects

Non-mandatory section - information about this substance not complied for this reason.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Acute, Chronic, Fire

Inventory			
Component	CAS	TSCA	

1,2,3- Trimethylbenzene	526-73-8	Yes
1,2,4- Trimethylbenzene	95-63-6	Yes
1,3,5- Trimethylbenzene	108-67-8	Yes
1- Methylethylbenzene	98-82-8	Yes
Proprietary	Proprietary	Yes
Distillates (petroleum), hydrotreated light	64742-47-8	Yes
Naphthalene	91-20-3	Yes
2-Ethylhexyl nitrate	27247-96-7	Yes
Solvent naphtha	64742-94-5	Yes
Solvent naphtha (petroleum), light aromatic	64742-95-6	Yes
Xylene	1330-20-7	Yes

United States

Labor			
U.S OSHA - Process Safety Management - Highly Hazardous Chemicals		N	
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed	
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed	
Naphthalene	91-20-3	Not Listed	
1-Methylethylbenzene	98-82-8	Not Listed	
Proprietary	Proprietary	Not Listed	
Xylene	1330-20-7	Not Listed	
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed	
 Solvent naphtha (petroleum), light aromatic 	64742-95-6	Not Listed	
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed	
Solvent naphtha	64742-94-5	Not Listed	
2-Ethylhexyl nitrate	27247-96-7	Not Listed	
U.S OSHA - Specifically Regulated Chemicals			
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed	
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed	
Naphthalene	91-20-3	Not Listed	
1-Methylethylbenzene	98-82-8	Not Listed	
Proprietary	Proprietary	Not Listed	
• Xylene	1330-20-7	Not Listed	
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed	
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed	
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed	
Solvent naphtha	64742-94-5	Not Listed	
2-Ethylhexyl nitrate	27247-96-7	Not Listed	
= =			

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Distillates (petroleum), hydrotreated light 64742-47-8 Not Listed

• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	
1-Methylethylbenzene	98-82-8	
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	(isomers and mixtures)
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
IIS CAA (Clean Air Act) Accidental Balance Broventian Flammable Substance		
 U.S CAA (Clean Air Act) - Accidental Release Prevention - Flammable Substanc Distillates (petroleum), hydrotreated light 	64742-47-8	Not Listed
	526-73-8	Not Listed
• 1,2,3-Trimethylbenzene	91-20-3	
Naphthalene Methylethylbograps	91-20-3	Not Listed Not Listed
• 1-Methylethylbenzene		
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S CAA (Clean Air Act) - Accidental Release Prevention - Toxic Substances		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
• Naphthalene	91-20-3	Not Listed
1-Methylethylbenzene	98-82-8	Not Listed
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
2-Lutymexyr mudic	21241-30-1	Not Elsted
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	100 lb final RQ; 45.4 kg final RQ
• 1-Methylethylbenzene	98-82-8	5000 lb final RQ; 2270 kg final RQ
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	100 lb final RQ; 45.4 kg final RQ
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		

Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	Not Listed
1-Methylethylbenzene	98-82-8	Not Listed
 Proprietary 	Proprietary	Not Listed
Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
 Solvent naphtha (petroleum), light aromatic 	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S. OFFICIA/OADA O. //. O40 F D. //.		
U.S CERCLA/SARA - Section 313 - Emission Reporting	04740 47 0	Not Listed
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	0.1 % de minimis concentration
1-Methylethylbenzene	98-82-8	1.0 % de minimis concentration
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	1.0 % de minimis concentration
• 1,2,4-Trimethylbenzene	95-63-6	1.0 % de minimis
•		concentration
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S CERCLA/SARA - Section 313 - PBT Chemical Listing		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	Not Listed
1-Methylethylbenzene	98-82-8	Not Listed
• Proprietary	Proprietary	Not Listed
Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed

J.S CWA (Clean Water Act) - Hazardous Substances Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
1,2,3-Trimethylbenzene	526-73-8	Not Listed
	91-20-3	NOI LISIEU
Naphthalene		Not Listed
1-Methylethylbenzene	98-82-8	Not Listed
Proprietary	Proprietary	Not Listed
Xylene	1330-20-7	
1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
J.S CWA (Clean Water Act) - Toxic Pollutants		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	
1-Methylethylbenzene	98-82-8	Not Listed
Proprietary	Proprietary	Not Listed
Xylene	1330-20-7	Not Listed
1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
	108-67-8	Not Listed
1,3,5-Trimethylbenzene Solvent naphtha	64742-94-5	Not Listed

United States - California

Environment		
U.S California - Proposition 65 - Carcinogens List		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	carcinogen, initial date 4/19/02
• 1-Methylethylbenzene	98-82-8	carcinogen, initial date 4/6/10
• Proprietary	Proprietary	Not Listed
Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
 Solvent naphtha (petroleum), light aromatic 	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S California - Proposition 65 - Developmental Toxicity		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed
Proprietary	Proprietary	Not Listed
Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed

U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	64740 47 0	Not Listed
Distillates (petroleum), hydrotreated light	64742-47-8 526-73-8	Not Listed Not Listed
1,2,3-TrimethylbenzeneNaphthalene	91-20-3	Not Listed
	98-82-8	Not Listed
1-Methylethylbenzene Proprietory		
Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	5.8 μg/day NSRL
1-Methylethylbenzene	98-82-8	Not Listed
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene	91-20-3	Not Listed
• 1-Methylethylbenzene	98-82-8	Not Listed
• Proprietary	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male	04740 47 0	Not Listed
Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• 1,2,3-Trimethylbenzene	526-73-8	Not Listed
Naphthalene A Mathalathalanaaaa	91-20-3	Not Listed
1-Methylethylbenzene	98-82-8	Not Listed
Proprietary Yelena	Proprietary	Not Listed
• Xylene	1330-20-7	Not Listed
• 1,2,4-Trimethylbenzene	95-63-6	Not Listed
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Listed
• 1,3,5-Trimethylbenzene	108-67-8	Not Listed
Solvent naphtha	64742-94-5	Not Listed
2-Ethylhexyl nitrate	27247-96-7	Not Listed

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

Preparation Date

Other Information

Disclaimer/Statement of Liability

• 16/October/2015

16/October/2015

• Schedule B Number: 3811.19.0000.

Information presented herein is believed to be factual, as it has been derived from the
works and opinions of persons believed to be qualified experts. However, nothing
contained in this information is to be taken as warranty or representation for which the
Gold Eagle Co. bears legal responsibility. The user should review any
recommendations in the specific context of the intended use to determine whether
they are appropriate.

Key to abbreviations NDA = No Data Available