Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: NAPA® PREM PERF SAE 10W-40 MOTOR OIL

Recommended use of the chemical and restrictions on use Use of the Substance/Mixture : MOTOR OIL

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE
Valvoline LLC	Regulatory Information Number
3499 Blazer Parkway	1-800-TEAMVAL
Lexington, KY 40509	
United States of America	Product Information
	1-800-TEAMVAL
SDS@valvoline.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60-	90194-32-4	Eye Irrit. 2A; H319	6.23
alkyl derivs., sodium salts			

Valvoline.	Page	e: 2
SAFETY DATA SHEET	Revision Date: 07/31/20	016
	Print Date: 9/27/20	016
	SDS Number: R0164	091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version:	1.1
NP75104		

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	3.70

SECTION 4. FIRST AID MEASURES

General advice	:	No hazards which require special first aid measures.
If inhaled	:	If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye.
If swallowed	:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
		Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	:	No hazards which require special first aid measures.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical 	
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.	
Hazardous combustion products	 carbon dioxide and carbon monoxide Hydrocarbons Aldehydes 	
Specific extinguishing methods	:	
	Product is compatible with standard fire-fighting agents.	
Further information	: Standard procedure for chemical fires.	
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

Materials to avoid

: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

			-			
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E		
		STEL	10 mg/m3 Mist.	NIOSH/GUID E		
		PEL	5 mg/m3 Mist.	OSHA_TRA NS		
Engineering measures	conditions of exist, provide exhaust) ven guidelines (if	General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.				
Personal protective equipmer	nt					
Respiratory protection	No personal respiratory protective equipment normally required.					
Eye protection		Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.				
Skin and body protection	Safety shoes	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).				
Hygiene measures	: General indu	General industrial hygiene practice.				

Components with workplace control parameters

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid	
Colour	: amber	
Odour	: hydrocarbon-l	ike
Odour Threshold	: No data availa	able



Revision Date: 07/31/2016

Print Date: 9/27/2016

NAPA® PREM PERF SAE 10W-40 MOTOR OIL NP75104 SDS Number: R0164091 Version: 1.1

pН : No data available Melting point/freezing point : No data available Boiling point/boiling range : 570.00 °F / 298.89 °C (1013.33 hPa) Flash point : > 390 °F / > 199 °C Method: Cleveland open cup Evaporation rate 1 : Ethyl Ether Flammability (solid, gas) : No data available Upper explosion limit : No data available Lower explosion limit : No data available : No data available Vapour pressure Relative vapour density : No data available Relative density : No data available Density : 0.8690 g/cm3 (15.56 °C) Solubility(ies) Water solubility : No data available Solubility in other solvents : No data available Partition coefficient: n-: No data available octanol/water Thermal decomposition : No data available Viscosity : No data available Viscosity, dynamic : 104 mm2/s (40 °C) Viscosity, kinematic Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.



Version: 1.1

Revision Date: 07/31/2016

Print Date: 9/27/2016 SDS Number: R0164091

NAPA® PREM PERF SAE 10W-40 MOTOR OIL

NP75104

Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact
		Ingestion

Acute toxicity

Not classified based on available information. **Skin corrosion/irritation** Not classified based on available information. <u>Product:</u> Result: Repeated exposure may cause skin dryness or cracking.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: Not irritating to skin

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Result: Mildly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts: Result: Irritating to eyes

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.



Revision Date: 07/31/2016

Print Date: 9/27/2016 SDS Number: R0164091

Version: 1.1

NAPA® PREM PERF SAE 10W-40 MOTOR OIL

NP75104

Germ cell mutagenicity Not classified based on available information. Carcinogenicity Not classified based on available information. Reproductive toxicity Not classified based on available information. STOT - single exposure Not classified based on available information. STOT - repeated exposure Not classified based on available information. Aspiration toxicity Not classified based on available information. Product: No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE: May be fatal if swallowed and enters airways.

Further information Product:

Remarks: No data available

Carcinogenicity:

ouromogementy.	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity
No data available
Persistence and degradability
No data available
Bioaccumulative potential
No data available
Mobility in soil
No data available
Other adverse effects
No data available

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

Product:

Additional ecological : information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

RECOLATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.
h	•				

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant		no	
------------------	--	----	--

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312	Hazards :	No SARA Hazards		
SARA 313 Component(s)		This material does not conta known CAS numbers that e reporting levels established	xceed the thresho	old (De Minimis)
Pennsylvania	Right To Know			
	HEAVY PARAF	FINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
	Benzenesulfonio sodium salts	c acid, C10-60-alkyl derivs.,	90194-32-4	5.00 - 10.00 %
	HYDROTREATI DISTILLATE	ED LIGHT PARAFFINIC	64742-55-8	1.00 - 5.00 %
New Jersey Ri	ght To Know			
	HEAVY PARAF	FINIC DISTILLATE	64742-54-7	90.00 - 100.00 %
	Benzenesulfonio sodium salts	c acid, C10-60-alkyl derivs.,	90194-32-4	5.00 - 10.00 %
	HYDROTREATI DISTILLATE	ED LIGHT PARAFFINIC	64742-55-8	1.00 - 5.00 %
	POLYOLEFIN A	MIDE ALKENEAMINE	Not Assigned	1.00 - 5.00 %

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

LUBRICANT ADDITIVE

Not Assigned 1.00 - 5.00 %

California Prop 65	Proposition 65 warnings are not required for this product based on the results of a risk assessment.
The components of this prod TSCA	ict are reported in the following inventories: : On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
ENCS	: q (quantity restricted)
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: q (quantity restricted)


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.



Revision Date: 07/31/2016

Print Date: 9/27/2016 SDS Number: R0164091

Version: 1.1

NAPA® PREM PERF SAE 10W-40 MOTOR OIL

NP75104

H304May be fatal if swallowed and enters airways.H319Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0164091
NAPA® PREM PERF SAE 10W-40 MOTOR OIL	Version: 1.1
NP75104	

HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System