

Revision Date: 11/02/2012

Print Date: 4/8/2014

MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland Regulatory Information Number 1-800-325-3751 P.O. Box 2219 Telephone 614-790-3333

Columbus, OH 43216 Emergency telephone number 1-800-ASHLAND (1-800-274-

5263)

Product name NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL

Product code NP75510

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eve contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause slight skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HYDROTREATED HEAVY PARAFFINIC BASE	64742-54-7	>=70-<80%
OIL		
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=10-<15%



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray





Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Contains no substances with occupational exposure limit values.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid





Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Colour	amber	
Boiling point/boiling range	626 °F / 330 °C @ 1,013.33 hPa Calculated Phase	
	Transition Liquid/Gas	
Flash point	> 390 °F / > 199 °C Cleveland open cup	
Vapour pressure	1.333 hPa @ 68 °F / 20 °C Calculated Vapor	
	Pressure	
Density	0.8552 g/cm3 @ 60.01 °F / 15.56 °C	
	7.12 lb/gal @ 60.00 °F / 15.56 °C	
Viscosity, kinematic	18.4 mm2/s	

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

None known.

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity - : no data available Product

Acute oral toxicity - Components

HYDROTREATED : LD 50: > 15 g/kg Species: Rat



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

HEAVY PARAFFINIC

BASE OIL

HEAVY PARAFFINIC : LD 50: > 15 g/kg Species: Rat

DISTILLATE

Acute inhalation toxicity

Acute inhalation toxicity - : no data available

Product

Acute dermal toxicity

Acute dermal toxicity - : no data available

Product

Acute dermal toxicity - Components

HYDROTREATED : LD 50: > 5 g/kg Species: Rabbit

HEAVY PARAFFINIC

BASE OIL

HEAVY PARAFFINIC : LD 50: > 5 g/kg Species: Rabbit

DISTILLATE

Acute toxicity (other routes of administration)

Acute toxicity (other : no data available

routes of administration)

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects

Toxicity to fish



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Toxicity to fish - Product	: no data available	
----------------------------	---------------------	--

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and : no data available

other aquatic invertebrates

- Product

Toxicity to algae

Toxicity to algae - : no data available Product

Toxicity to bacteria

Toxicity to bacteria -

: no data available

Product

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION

ID	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
NUMBER		CLASS	HAZARDS	GROUP	POLLUTANT
					/ LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods



Revision Date: 11/02/2012

Print Date: 4/8/2014

MSDS Number: R0393461 Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

	Not dangerous goods
	1vot dangerous goods
TRANS	PORT CANADA - ROAD
	Not dangerous goods
ΓRANS]	PORT CANADA - RAIL
	Not dangerous goods
<u> </u>	PORT CANADA - INLAND WATERWAYS
	Not dangerous goods
	Not dangerous goods
INTERI	ATIONAL AIR TRANSPORT ASSOCIATION - CARGO
	Not dangerous goods
	A THOUGH A LID TO A NIGOOD A GGO CLATION. DA GGENGED
	ATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER
INTERN	
INTERI	Not dangerous goods
MEXIC	AN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND
	AN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based	
on the results of a risk assessment.	



Revision Date: 11/02/2012

Print Date: 4/8/2014 MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

SARA Hazard Classification
SARA 311/312 Classification
No SARA Hazards

SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

New Jersey RTK Label Information

Tiew delsey Killi Lubel Information	
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7
HEAVY PARAFFINIC DISTILLATE	64742-54-7
POLYMER	68037-01-4
POLYOLEFIN AMIDE ALKENEAMINE	
LUBRICANT ADDITIVE	

Pennsylvania RTK Label Information

HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7
HEAVY PARAFFINIC DISTILLATE	64742-54-7
POLYMER	68037-01-4

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA).	y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	
Australia. Industrial Chemical (Notification and Assessment)	y (positive listing)
Act	
New Zealand. Inventory of Chemicals (NZIoC), as published	n (Negative listing)
by ERMA New Zealand	
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear	y (positive listing)
Waste Control Act	
China. Inventory of Existing Chemical Substances	q (quantity restricted)

	HMIS	NFPA
Health	1	1



Revision Date: 11/02/2012

Print Date: 4/8/2014

MSDS Number: R0393461

Version: 3.2

NAPA® PREM PERF SYN SAE 15W50 SYNTHETIC MOTOR OIL NP75510

Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	1	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).