Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

29 CFR 1910.1200 (OSHA HazCom 2012)

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : Valvoline™ HD SAE 75W-90

SYNTHETIC GEAR OIL

#### Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509	Regulatory Information Number 1-800-TEAMVAL
United States of America	Product Information 1-800-TEAMVAL
SDS@valvoline.com	

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin sensitization : Category 1

**GHS Label element** 

Hazard pictograms



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : If medical advice is needed, have product container or label at

hand.

Keep out of reach of children. Read label before use.

Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Contaminated work clothing must not be allowed out of the

workplace.

Wear protective gloves.

Response:

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

## Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
OLEFINSULFIDE	68937-96-2	Skin Sens. 1B; H317	5.00
		Aquatic Chronic 3; H412	
N-PHENYL-1-NAPHTHYLAMINE	90-30-2	Acute Tox. 4; H302 Skin Sens. 1; H317 STOT RE 2; H373	0.99

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

<b>Valvoline</b>	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction. No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide oxides of sulfur, nitrogen and phosphorus

Sulphur oxides

Specific extinguishing

methods

•

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Components with workplace control parameters

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Colour : amber

Odour : pungent

Odour Threshold : No data available

pH : No data available

:

No data available

: No data available

Flash point : 419 °F / 215 °C

Method: Closed Cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.879 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 122 mm2/s (40 °C)

Oxidizing properties : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

oxides of sulfur, nitrogen and phosphorus

Sodium oxides

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Inhalation

exposure

InhalationSkin contact

Eye Contact Ingestion

**Acute toxicity** 

Not classified based on available information.

**Product:** 

Acute oral toxicity

Remarks: Not toxic, not known to be toxic, not expected to be

toxic by Ingestion

Acute inhalation toxicity : Remarks: Not toxic, not known to be toxic, not expected to be

toxic by Inhalation Mild respiratory irritant

Components:

N-PHENYL-1-NAPHTHYLAMINE:

Acute oral toxicity : LD 50 (Rat, Male): ca. 1,625 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Not irritating to skin

Remarks: May cause skin irritation in susceptible persons.

Components:

**OLEFINSULFIDE:** 

Result: Mildly irritating to skin

N-PHENYL-1-NAPHTHYLAMINE:

Species: Rabbit

Method: OECD Test Guideline 404 Result: Mildly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Result: Mildly irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

Components:

**OLEFINSULFIDE:** 

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

Result: Mildly irritating to eyes

N-PHENYL-1-NAPHTHYLAMINE: Result: Mildly irritating to eyes Method: OECD Test Guideline 405

## Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

<u>Components:</u> OLEFINSULFIDE:

Assessment: The product is a skin sensitiser, sub-category 1B.

N-PHENYL-1-NAPHTHYLAMINE: Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 406

## Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

# STOT - single exposure

Not classified based on available information.

# STOT - repeated exposure

Not classified based on available information.

#### Components:

## N-PHENYL-1-NAPHTHYLAMINE:

Exposure routes: Ingestion Target Organs: Blood

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2.

### **Aspiration toxicity**

Not classified based on available information.

## **Further information**

Product:

Remarks: No data available

## Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

# Components:

OLEFINSULFIDE:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

N-PHENYL-1-NAPHTHYLAMINE:

Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): 0.44 - 0.74 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: EC 50 (Water flea (Daphnia magna)): 0.3 - 0.68 mg/l

Exposure time: 48 h Test Type: static test

## Persistence and degradability

## Components:

N-PHENYL-1-NAPHTHYLAMINE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301C

## Bioaccumulative potential

#### **Components:**

N-PHENYL-1-NAPHTHYLAMINE:

Partition coefficient: n- : log Pow: 4.20

octanol/water

#### Mobility in soil

## **Components:**

No data available

## Other adverse effects

No data available

#### **Product:**

Additional ecological : An environmental hazard cannot be excluded in the event of

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

information unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

Components:

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

## **SECTION 14. TRANSPORT INFORMATION**

## International transport regulations

#### REGULATION

112002/111011					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

### **U.S. DOT - ROAD**

Not dangerous goods	

## CFR RAIL C

_	 	
		Not dangerous goods
		Not dangerous goods

## **U.S. DOT - INLAND WATERWAYS**

<u>0.0. D 0 .</u>	THE THE TOTAL ELECTRICAL
	Not dangerous goods

## TDG ROAD C

	Not dangerous goods

#### TDG\_RAIL\_C

Not dangerous goods	
<u> </u>	

<b>Valvoline</b>	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

TDG	INWT	

Not dangerous goods

## INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

#### **INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

## MX DG

Not dangerous goods

## \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no	l

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : Acute Health Hazard

SARA 313

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

PROPRIETARY SYNTHETIC GEAR Not Assigned 90.00 - LUBRICANT 100.00 %

MIXTURE OF OLEFIN SULFIDE, H2OP4 Not Assigned 10.00 - 20.00 %

ESTER, AMINE SALTS, ALKYLSULFIDE,

ALKENYLAMIDE AND OTHER

**INGREDIENTS** 

OLEFINSULFIDE 68937-96-2 5.00 - 10.00 %

<b>Valvoline</b>	Page: 12
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

**New Jersey Right To Know** 

PROPRIETARY SYNTHETIC GEAR Not Assigned 90.00 - LUBRICANT 100.00 %

MIXTURE OF OLEFIN SULFIDE, H2OP4 Not Assigned 10.00 - 20.00 %

ESTER, AMINE SALTS, ALKYLSULFIDE,

ALKENYLAMIDE AND OTHER

**INGREDIENTS** 

OLEFINSULFIDE 68937-96-2 5.00 - 10.00 %

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer. 2-NAPHTHALENAMINE 91-59-8

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AICS : Not in compliance with the inventory

NZIOC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI: Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

## Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

Revision Date: 07/31/2016



# NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure
	if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### **Further information**

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

Valvoline.	Page: 14
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL	Version: 1.2
VV70026	

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

**DOT**: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System