

MATERIAL SAFETY DATA SHEET

4301
02 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER	DATE OF PREPARATION	HMIS CODES
4301	13-AUG-08	Health 2* Flammability 3 Reactivity 0

PRODUCT NAME
White Fast & Firm Sealer

MANUFACTURER'S NAME
MARTIN SENOUR PAINTS
4440 Warrensville Center Road
Warrensville Hts., OH 44128-2837

TELEPHONE NUMBERS and WEBSITES
Regulatory Information
(216) 566-2902
Medical Emergency
(216) 566-2917
Transportation Emergency (800) 424-9300 for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
3	64742-89-8	V. M. & P. Naphtha		
		ACGIH TLV	300 ppm	12 mm
		OSHA PEL	300 ppm	
		OSHA PEL	400 ppm STEL	
9	108-88-3	Toluene		
		ACGIH TLV	20 ppm	22 mm
		OSHA PEL	100 ppm (Skin)	
		OSHA PEL	150 ppm (Skin) STEL	
0.9	100-41-4	Ethylbenzene		
		ACGIH TLV	100 ppm	7.1 mm
		ACGIH TLV	125 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	125 ppm STEL	
4	1330-20-7	Xylene		
		ACGIH TLV	100 ppm	5.9 mm
		ACGIH TLV	150 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	150 ppm STEL	
1	95-63-6	1,2,4-Trimethylbenzene		
		ACGIH TLV	25 ppm	2.03 mm
		OSHA PEL	25 ppm	
3	78-93-3	Methyl Ethyl Ketone		
		ACGIH TLV	200 ppm	70 mm
		ACGIH TLV	300 ppm STEL	
		OSHA PEL	200 ppm	
		OSHA PEL	300 ppm STEL	

Continued on page 2

4	108-10-1	Methyl Isobutyl Ketone							
		ACGIH TLV	50	ppm					16 mm
		ACGIH TLV	75	ppm	STEL				
		OSHA PEL	50	ppm					
		OSHA PEL	75	ppm	STEL				
0.8	14808-60-7	Quartz							
		ACGIH TLV	0.025	mg/m3	as Resp. Dust				
		OSHA PEL	0.1	mg/m3	as Resp. Dust				
5	1332-58-7	Kaolin							
		ACGIH TLV	2	mg/m3	as Resp. Dust				
		OSHA PEL	10	mg/m3	Total Dust				
		OSHA PEL	5	mg/m3	Respirable Fraction				
33	471-34-1	Calcium Carbonate							
		ACGIH TLV	10	mg/m3	as Dust				
		OSHA PEL	15	mg/m3	Total Dust				
		OSHA PEL	5	mg/m3	Respirable Fraction				

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	10.40 lb/gal	1245 g/l
SPECIFIC GRAVITY	1.25	
BOILING POINT	174 - 337 F	78 - 169 C
MELTING POINT	Not Available	
VOLATILE VOLUME	41 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)		
2.88 lb/gal	346 g/l	Less Water and Federally Exempt Solvents
2.88 lb/gal	346 g/l	Emitted VOC

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Continued on page 5

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

TOXICOLOGY DATA

CAS No.	Ingredient Name					
64742-89-8	V. M. & P. Naphtha	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
108-88-3	Toluene	LC50	RAT	4HR	4000	ppm
		LD50	RAT		5000	mg/kg
100-41-4	Ethylbenzene	LC50	RAT	4HR	Not Available	
		LD50	RAT		3500	mg/kg
1330-20-7	Xylene	LC50	RAT	4HR	5000	ppm
		LD50	RAT		4300	mg/kg
95-63-6	1,2,4-Trimethylbenzene	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
78-93-3	Methyl Ethyl Ketone	LC50	RAT	4HR	Not Available	
		LD50	RAT		2740	mg/kg
108-10-1	Methyl Isobutyl Ketone	LC50	RAT	4HR	Not Available	
		LD50	RAT		2080	mg/kg
14808-60-7	Quartz	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
1332-58-7	Kaolin	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	
471-34-1	Calcium Carbonate	LC50	RAT	4HR	Not Available	
		LD50	RAT		Not Available	

Continued on page 6

 Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

 Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 Section 14 -- TRANSPORT INFORMATION

US Ground (DOT)

1 Gallon and Less may be Classed as CONSUMER COMMODITY, ORM-D

Larger Containers are Regulated as:

UN1263, PAINT, 3, PG II, (ERG#128)

DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

Toluene 1000 lb RQ

Xylenes (isomers and mixture) 100 lb RQ

Bulk Containers may be Shipped as (check reportable quantities):

RQ, UN1263, PAINT, 3, PG II, (XYLENES (ISOMERS AND MIXTURE)), (ERG#128)

Canada (TDG)

UN1263, PAINT, CLASS 3, PG II, (ERG#128)

IMO

UN1263, PAINT, CLASS 3, PG II, (7 C c.c.), EmS F-E, S-E

 Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene	9	
100-41-4	Ethylbenzene	0.8	
1330-20-7	Xylene	4	
95-63-6	1,2,4-Trimethylbenzene	1	
108-10-1	Methyl Isobutyl Ketone	4	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Continued on page 7

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.