

imageRUNNER ADVANCE C3530i C3525i

imageRUNNER ADVANCE C3500 III Series

Color | Low- to Mid-volume | Multifunction

Print up to 30 ppm (BW/color)

Scan up to 160 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive!
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM* systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control² utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.³



QUALITY AND

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² color profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.







- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.⁴

CONFIGURATION OPTIONS

Puncher Unit-A1)



Main Unit

Type

Color Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store Standard:

Optional: Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory 3.0 GB RAM Hard Disk Drive Standard: 250 GB

Interface Connection 1000Base-T/100Base-TX/10Base-T, Network:

Optional: Others

USB 2.0 x1 (Host), USB 3.0 x1 (Host), Standard:

USB 2.0 x1 (Device)

Serial Interface, Copy Control Interface Optional:

NFC, Bluetooth Low Energy

Wireless LÁN (IEEE 802.11 b/g/n)

Paper Capacity (LTR, 20 lb. Bond) Standard: 1,200 Sheets

Maximum: 2,300 Sheets Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet

Stack Bypass

Dual 550-sheet Paper Cassettes Optional: (CASSETTE FEEDING UNIT-AP1)

Paper Output Capacity (LTR, 20 lb. Bond)

250 Sheets Standard: 3.450 Sheets Maximum:

(with External Finisher and Copy Tray)

Finishing Capabilities

Standard:

Collate, Group Collate, Group, Offset, Staple, Staple-Free With Inner Staple, Staple On Demand Finisher-

Collate, Group, Offset, Staple, Booklet, Staple-Free Staple, Staple On Demand, With External Finishers:

Hole Punch (Optional)

Supported Media Types

Paper Thin, Plain, Recycled, Color, Heavy, Cassettes Pre-punched, Bond, Transparency, Envelope (1/2):

Stack Bypass:

Thin, Plain, Recycled, Color, Heavy, Pre-punched, Labels, Bond, Coated, Transparency, Tracing, Envelope

Cassette Feeding Unit-AP1: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Bond, Transparency

Supported Media Sizes

Letter, Executive, Statement-R, Envelope Paper Cassette 1: [ISO-C5], Custom Size $(5-1/2" \times 7-1/8"$

to 11-3/4" x 8-1/2")
Paper Cassette 12" x 18", 11" x 17", Legal, Letter, Letter-R,

Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL], Custom Size (5-1/2" x 7-1/8" to 12" x 18") 12" x 18", 11" x 17", Legal, Letter, Letter-R,

Stack Bypass:

Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size

(3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2"

to 12-5/8" x 18")⁵ 12" x 18", 11" x 17", Legal, Letter, Letter-R, Cassette Feeding Unit-Executive, Statement-R, Custom Size

AP1: (5-1/2" x 7-1/8" to 12" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²) Stack Bypass: Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed (BW and Color)

Up to 30 ppm (Letter); Up to 20 ppm C3530i III:

(Letter-R); Up to 15 ppm (Legal); Up to 15 ppm (11" x 17")

Up to 25 ppm (Letter); Up to 20 ppm C3525i III:

(Letter-R); Up to 15 ppm (Legal); Up to 15 ppm (11" x 17")

Warm-up Time

From Power On: Approx. 10 Seconds⁶ From Sleep Approx. 10 Seconds7

Mode:

Quick Startup Approx. 4 Seconds8

Mode:

Dimensions (W x D x H)

22-1/4" x 29-1/4" x 45-1/5" (565 mm x 742 mm x 1148 mm)9

Installation Space (W x D)

Basic: Stack Bypass + Cassette Drawers open: 38-1/2" x 44-1/4" (978 mm x 1123 mm)⁹

Fully

Configured: 63-3/4" x 44-1/4" (1620 mm x 1123 mm)10

Weight

Approx. 213.8 lb. (97 kg)11

Print Specifications

Print Resolution (dpi) 1200 x 1200, 600 x 600

Standard Page Description Languages

UFR II, PCL®6, Adobe® PS® 3

Direct Print

Available from USB, Advanced Box, Remote UI,

and Web Access1

Supported File Types PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and

Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese,

Korean, Simplified and Traditional Chinese),13

Barcode Fonts¹⁴ 136 Roman

PS fonts: Operating System¹⁵

UFRII/PS: Windows®/Server 2008/Windows® 7/

Server 2008 R2/Server 2012/Windows 8.1/ Server 2012 R2/Windows 10/Server 2016,

MAC OS X (10.9 or later)
Windows/Server 2008/Windows 7/Server PCL:

2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016

PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

Copy Specifications

First-Copy-Out Time (LTR)

As fast as 5.9 seconds (BW)/8.2 seconds (Color)

Multiple Copies Up to 999

Magnification

25%-400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements 121%, 129%, 200%, 400%

Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Twosided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, Non 1, Add Cover, Insert Sheets, Different-size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Job Done Notice, Mirror Image, Copy ID Card, Multi Sheet Feed Detection, Free Size Original, Adjust One-Touch Color, Color Balance, Area Designation, Skip

Scan Specifications

Single-pass Duplexing Automatic Document Feeder¹⁶

Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17" (128 mm x 139.7 mm to 304.8 mm x 431.8 mm)

Document Feeder Supported Media Weights

13 lb. Bond to 58 lb. Cover (50 to 157 g/m²) BW Original: Color Original: 17 lb. Bond to 58 lb. Cover $(64 \text{ to } 157 \text{ g/m}^2)$

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: Up to 2" (50mm),

Weight: up to 4.4 lb. (2kg)]

Platen Maximum Scanning Size

11-3/4" x 17" (297.0 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10/

Server 2008/Server 2008 R2/ Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,

200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (LTR)

Single-sided Scanning (BW and Color): 80 ipm (300 dpi)/51 ipm (600 dpi) Double-sided Scanning (BW and Color): 160 ipm (300 dpi)/51 ipm (600 dpi)

Send Specifications

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,

200 x 100, 150 x 150, 100 x 100

Communication Protocol

FTP (TCP/IP), SMB v3.0, WebDAV

File: SMTP POP3

Email:

Optional:

File Format Standard:

TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Searchable, Compact, Device Signature), Office Open XML (PowerPoint, Word)

PDF (Trace & Smooth, User Signature), XPS (User Signature)

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

Fax Specifications

Maximum Number of Connection Lines

Modem Speed

Super G3: 33.6 Kbps G3 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17'

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

Store Specifications

Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMR-

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure

Audit Manager Support Memory Media

Standard: USB

Security Specifications

Authentication

Universal Login Manager, uniFLOW Online Standard-

Express, 17 User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in

Optional: uniFLOW

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup,

McAfee Embedded Control²

Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network Standard

Optional:

Encrypted Secure Print, IP/Mac

Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME,

SIEM Integration

Document

Optional:

Standard Secure Watermark, Secure Print, Adobe

LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Digital Signature, User Signatures, Document Scan Lock

Environmental Specifications

Operating Environment

Temperature: 50 to 86 °F

20 to 80 % RH (Relative Humidity) Humidity:

Power Requirements

C3530i III/ 120-127V AC 60 Hz,7.5 A C3525i III:

Plug (Main Unit)

C3530i III/ **NEMA 5-15P**

C3525i III:

Power Consumption

Approx. 1,500 W Maximum: Approx. 42.9 W¹⁸ Standby: Sleep Mode: Approx. 0.8 W¹⁹

Typical Electricity Consumption (TEC) Rating²⁰

. C3530i III: Ó.37 kWh C3525i III: 0.31 kWh

Standards

ENERGY STAR® Certified Rated EPEAT® Gold

Consumables

GPR-53 Toner²¹

Toner Yield (Estimated @ 5% Coverage)

Black 36,000 Images Color (C,M,Y): 19,000 Images

- Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.
- Requires Unified Firmware Platform v3.9.
- 3 Requires additional option
- For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
- ⁵ Heavy paper (95 to 110 lb. Cover) can be supported as follows: Standard format paper size (excluding SRA3), Custom size (3-7/8" x 5-1/2" to 12" x 18"), Free size (3-7/8" x 5-1/2" to 12" x 18")
- ⁶ Time from device power-on to when copy jobs can be
- programmed with Quick Start Up mode.

 Time from exiting Sleep mode to when printing is operational. 8 Time from device power-on to when key operation can be
- performed on the touch screen. Includes main unit and either Cassette Feeding Unit-AP1 or Cabinet Type-R.
- Includes main unit and either Cassette Feeding Unit-API or Cabinet Type-R and Staple/Booklet Finisher-AAI.
 Includes main unit, ADF consumables, and Cassette Feeding
- ¹² PDF print from Web sites is supported.
- ¹³ Requires the optional PCL International Font Set-Al. ¹⁴ Requires the optional Barcode Printer Kit-Dl.
- Other operating systems and environments, including AS/400, UNIX, Linux and Citrix, may be supported. Some solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

 Detect Feeder Multi Sheet Feed is supported.
 No charge for this solution; however activation is required.

- Reference value (measured one unit).
- ¹⁹ 0.8 W sleep mode not available in all circumstances
- due to certain settings. Based on ENERGY STAR Product Specification for Imaging
- Equipment Version 3.0. ¹ GPR-53L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 8,500 images.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C3500 III Series Specifications document.















As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Solutions America Sales Representative for details. Products shown with optional accessories. Canon U.S.A. and Canon Solutions America do not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical

©2019 Canon U.S.A., Inc. All rights reserved.

 $Federal\,Law\,prohibits\,copying\,of\,certain\,documents.\,Violators\,may\,be\,subject\,to\,penalties.\,We\,suggest\,that\,you\,check\,with\,your\,own\,legal\,counsel.\,Canon\,U.S.A.,\,Inc.\,and\,Canon\,Canada,\,Inc.\,intend$ to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.









CANON SOLUTIONS AMERICA

