

Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Krazy Glue Maximum Bond Wood & Leather Glue

Synonyms

KG821

Chemical Family

Cyanoacrylate containing adhesive

Restrictions on Use

None known.

Details of the supplier of the safety data sheet

Newell Office Brands

Product of Newell Office Brands, Inc.

6655 Peachtree Dunwoody Rd. NE

Atlanta, GA 30328

www.krazyglue.com

Phone: 1.888.435.6377

Emergency Phone #: 1.888.516.2502

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 4

Acute Toxicity - Inhalation - Vapor - Category 4

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

Reproductive Toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3

GHS Label Elements

Symbol(s)



Signal Word

Warning

Hazard Statement(s)

Combustible liquid.

Harmful if inhaled.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Precautionary Statement(s)

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from flames and hot surfaces. – No smoking.
Use only outdoors or in a well-ventilated area.
Wear protective gloves and eye protection.
Avoid breathing vapors.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response

In case of fire: Use dry chemical or carbon dioxide to extinguish.
IF exposed or concerned: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Specific treatment (see label).

Storage

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Statement(s) of Unknown Acute Toxicity

Inhalation 4.2% of the mixture consists of ingredient(s) of unknown acute toxicity.

Other Hazards

No additional information is available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7085-85-0	Ethyl cyanoacrylate	>90
119-47-1	2,2'-Methylenebis(4-methyl-6-tert-butylphenol)	0.1

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Skin

Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Peel or roll the surfaces apart using a blunt edge, such as a spatula or spoon handle.

Eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Immediately call a POISON CENTER.

Most Important Symptoms/Effects

Acute

May cause respiratory irritation, eye irritation. May cause allergic skin reaction.

Delayed

Suspected of damaging fertility or the unborn child.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None known. Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Combustible liquid

Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen

Special Protective Equipment and Precautions for Firefighters

Self-contained breathing apparatus with face piece and protective clothing can be used if involved in a fire of other materials. Do not scatter spilled material with high-pressure water streams.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. Ventilate closed spaces before entering.

Methods and Materials for Containment and Cleaning Up

Eliminate all sources of ignition. Do not touch or walk through spilled material. Stop leak if possible without personal risk. Prevent entry into waterways, sewers, basements, or confined areas. Reduce vapors with water spray. Absorb with earth, sand or other non-combustible material and transfer to container. Use non-sparking tools. Large spills: Dike for later disposal.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Avoid contact with water or moisture. Keep away from heat and ignition sources. Keep away from incompatible materials. Protect from sunlight.

Incompatible Materials

alcohols, amines, bases

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Ethyl cyanoacrylate	7085-85-0
ACGIH:	0.2 ppm TWA

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure adequate ventilation.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed. A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	clear colorless liquid	Physical State	liquid
Odor	irritating odor	Color	Not available
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	62 °C
Boiling Point Range	Not available	Freezing point	-22 °C
Evaporation Rate	Not available	Flammability (solid, gas)	Not available



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Autoignition Temperature	Not available	Flash Point	83 °C
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	0.13 mmHg (@ 20 °C)
Vapor Density (air=1)	>1	Specific Gravity (water=1)	Not available
Water Solubility	Insoluble (causes rapid polymerization)	Partition coefficient: n-octanol/water	Not available
Viscosity	300 cps (@ 25 °C)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	1.05 g/cm ³
VOC	0 g/L (SCAQMD Method 316B)	Molecular Weight	Not available

Section 10 - STABILITY AND REACTIVITY

Reactivity

May polymerize when heated. Avoid contact with water or moisture. Avoid contact with light.

Chemical Stability

Unstable at elevated temperatures.

Possibility of Hazardous Reactions

May polymerize. Avoid contact with water or moisture.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat. Keep out of water supplies and sewers. Avoid contact with water or moisture.

Incompatible Materials

alcohols, amines, bases

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause respiratory irritation.

Skin Contact

May cause allergic skin reaction.

Eye Contact

Causes eye irritation.

Ingestion

No information on significant adverse effects.



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Ethyl cyanoacrylate (7085-85-0)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg (no deaths occurred)

Inhalation LC50 Rat <21.1 mg/L 1 h

2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)

Oral LD50 Rat >10000 mg/kg

Dermal LD50 Rabbit >10000 mg/kg

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Inhalation - Vapor	11.0125 mg/L
Oral	> 2000 mg/kg

Immediate Effects

May cause respiratory irritation, eye irritation. May cause allergic skin reaction.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause respiratory irritation, eye irritation. May cause allergic skin reaction.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Respiratory system

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information available for the product.



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

Medical Conditions Aggravated by Exposure

No data available.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not Regulated

IATA Information:

UN#: Not Regulated

TDG Information:

UN#: Not Regulated

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2017 reporting categories

Flammable; Acute toxicity; Reproductive Toxicity; Respiratory/Skin Sensitization; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Ethyl cyanoacrylate	7085-85-0	No	No	No	Yes	No

Not listed under California Proposition 65

Canada Regulations

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

WHMIS Classification

B3 , D2A , D2B

Component Analysis - Inventory

Ethyl cyanoacrylate (7085-85-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

2,2'-Methylenebis(4-methyl-6-tert-butylphenol) (119-47-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 2 Reactivity: 1

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Updated SDS: 1/24/2017

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR’s Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; NDSL – Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport;



Safety Data Sheet

Material Name: Krazy Glue Maximum Bond Wood & Leather Glue

SDS ID: SDS-78

SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.