


MODEL 2280A FOUR CHANNEL H2S CONTROLLER



2280A - 1 - 1 - 1 - 0 1 - 1 - 4

CONTROLLER:

(Std) FOUR CHANNEL HYDROGEN SULFIDE CONTROLLER

A. POWER:

- 1- (Std) 110 VAC/24 VDC
- 2- 220 VAC/24 VDC

B. RELAY-ALARM:

- 1- (Std) COMMON RELAY/COMMON ALARMS
- 4- DISCRETE RELAYS/DISCRETE ALARMS

C. RELAY-STATE-NC:

- 1- (Std) LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 2- LATCH ALARM/NON-LATCH WARN ENERGIZED
- 3- LATCH ALARM/LATCH WARN DE-ENERGIZED
- 4- LATCH ALARM/LATCH WARN ENERGIZED
- 5- NON-LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 6- NON-LATCH ALARM/NON-LATCH WARN ENERGIZED
- 7- NON-LATCH ALARM/LATCH WARN DE-ENERGIZED
- 8- NON-LATCH ALARM/LATCH WARN ENERGIZED

D. H2S-SENSOR: (price per active channel)

- 00- NONE
- 01- (Std) 50445-1 SENSOR ALUMINUM 0-100 ppm H2S
- 02- 50445-5 SENSOR ALUMINUM 0-50 ppm H2S
- 03- 50445-9 SENSOR ALUMINUM 0-20 ppm H2S
- 04- 50448-1 SENSOR STAINLESS STEEL 0-100 ppm H2S
- 05- 50448-5 SENSOR STAINLESS STEEL 0-50 ppm H2S
- 06- 50448-9 SENSOR STAINLESS STEEL 0-20 ppm H2S
- 11- 51457-1 SENSOR STAINLESS STEEL ATEX H2S 0-100 ppm
- 12- 51457-1L SENSOR STAINLESS STEEL ATEX H2S 0-100 ppm (W/LUGS)
- 13- 51457-5 SENSOR STAINLESS STEEL ATEX H2S 0-50 ppm
- 14- 51457-5L SENSOR STAINLESS STEEL ATEX H2S 0-50 ppm (W/LUGS)
- 15- 51457-9 SENSOR STAINLESS STEEL ATEX H2S 0-20 ppm
- 16- 51457-9L SENSOR STAINLESS STEEL ATEX H2S 0-20 ppm (W/LUGS)

E. H2S-METER-SCALE:

- 1- (Std) 99 ppm SCALE
- 2- 50 ppm SCALE
- 3- 20 ppm SCALE

F. ACTIVE CHANNELS:

- 0- CONTROLLER ONLY
- 1- ONE ACTIVE CHANNEL
 - 1 X BOX OF 12 AMPOULES
 - 3 X H2S SENSOR SIMULATOR W/O SW
 - 1 X SENSOR HOUSING
 - 1X CALIBRATION BOTTLE
- 2- TWO ACTIVE CHANNELS
 - 2 X BOX OF 12 AMPOULES
 - 2 X H2S SENSOR SIMULATOR W/O SW
 - 2 X SENSOR HOUSING
 - 1 X CALIBRATION BOTTLE
- 3- THREE ACTIVE CHANNELS
 - 3 X BOX OF 12 AMPOULES
 - 1 X H2S SENSOR SIMULATOR W/O SW
 - 3 X SENSOR HOUSING
 - 1 X CALIBRATION BOTTLE
- 4- (Std) FOUR ACTIVE CHANNELS
 - 4 X BOX OF 12 AMPOULES
 - 4X SENSOR HOUSING
 - 1 X CALIBRATION BOTTLE