

V-Series Tie-Back Lanyards Conversion Guide



CSA

Complex Worksites. Simplified Solutions.

Our new line of V-Series Tie-Back Lanyards simplifies product selection by offering a concise line of standard lanyards that will meet a wide range of customer needs. All new lanyards shown below also meet the latest ANSI standard for tie-back lanyards: ANSI Z359.13. The tie-back shock-absorbing lanyard uses an FP5K carabiner which can be tied directly back to the lanyard. All tie-back lanyards can be easily identified by the  icon on the energy absorber's cover.

| Old P/N | Description | New CSA P/N | Description | Standard |
|-----------------|---|-------------------|--|----------------|
| Legacy Lanyards | | V-Series Lanyards | | |
| 10047084 | FP5K Energy-Absorbing Single-Leg Web Lanyard, 6', tie-back version, 36C snaphook & (2) FP5K snaphooks, adjustable | 10193943 | V-Series single-leg energy-absorbing 6' tie-back lanyard | CSA Z259.11-17 |
| 10047085 | FP5K Energy-Absorbing Twin-Leg Web Lanyard, 6', tie-back version, 36C snaphook & (2) FP5K snaphooks, adjustable | 10193944 | V-Series twin-leg energy-absorbing 6' tie-back lanyard | CSA Z259.11-17 |



Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
 1000 Cranberry Woods Drive
 Cranberry Township, PA 16066 USA
 Phone 724-776-8600
www.MSAafety.com
U.S. Customer Service Center
 Phone 1-800-MSA-2222
 Fax 1-800-967-0398

MSA Canada
 Phone 1-800-672-2222
 Fax 1-800-967-0398
MSA Mexico
 Phone 01 800 672 7222