

MSA Latchways **Leading Edge SRL**

Self-retractable lifeline for horizontal and vertical use



Advanced fall protection for leading edge applications including roofing, wooden beams and leading edge construction.

Expansive mobility

With its easy-to-use self-locking function, the **MSA Latchways Leading Edge SRL** automatically extends and retracts during use — for freedom to move over large working areas.

Versatile connection

The **MSA Latchways Leading Edge SRL** easily connects to a range of personal fall arrest systems — for optimal compatibility with both vertical and horizontal applications.

Reliable technology

The MSA Latchways Leading Edge SRL features patented Constant Force® technology to control the load in the event of a fall and our Full Contact™ locking mechanism to assure that the device will not freeze, hang up or corrode.

Strong and tested

Compliant with Latchways' strict quality-control procedures, the **MSA Latchways Leading Edge SRL** features a toughened case to prevent impact damage, plus premium quality materials with advanced properties for superior resistance to corrosion. The MSA Latchways Leading Edge SRL has been tested to meet the following relevant standards:

- BS EN 360:2002 - Personal Protective Equipment against Falls from Height - Retractable Type Fall Arrester
- VG11 CNB/P/11.060: Edge type A (0.5 mm radius edge)



62705-00EU

62707-00EU

62710-00EU



MSA Latchways Leading Edge SRL

The trusted self-retracting lifeline for work on the edge

- **Energy absorption** - the integral, in-line, patented energy absorber, absorbs energy at a Constant Force® and gives a true indication of impact.
- **Manufacturer identification** - individually serial numbered to ensure full traceability.
- **Colour safety** - bright yellow toughened case is designed to resist impact damage, to protect the internal chassis and to stand out when being used at foot level, to minimise the trip hazard.
- **Thorough protection** - incorporates a secondary unique shock pack that assists with energy absorption.

Materials

Case	Impact Modified Nylon
Pawl & Ratchet Module	Stainless Steel
Chassis	Stainless Steel
Motor Spring	Stainless Spring Steel
Drum Module	Aluminium
Fasteners	Stainless Steel
Cable	Ø6 mm 7x19 Galvanised Cable
CF® Absorber Module	Stainless Steel and Impact Modified Nylon
Snap Hook	Forged Steel / Stainless Steel
Connecting Ring	Aluminium
Shock Pack	Polyester Webbing with a Neoprene Cover



Ordering Information

Part No.	Description	Length (meters)	Line Type	Size L x W x D (mm)	Net Weight (kg)
62705-00EU	5 m Leading Edge Cable SRL	5 m	Ø6 mm Galvanised Steel Cable (7x19)	900 x 170 x 122	5.3
62707-00EU	7 m Leading Edge Cable SRL	7 m	Ø6 mm Galvanised Steel Cable (7x19)	927 x 185 x 125	6.0
62710-00EU	10 m Leading Edge Cable SRL	10 m	Ø6 mm Galvanised Steel Cable (7x19)	966 x 215 x 130	8.0

Your direct contact

MSA Great Britain
Lochard House, Linnet Way
Strathclyde Business Park
Bellshill ML4 3RA
Phone +44 (0)1698 573357
info.gb@MSAsafety.com

Corporate Headquarters:
MSA
1000 Cranberry Woods Drive
Cranberry Township, PA 16066, USA
Phone +1-724-776-8600
info.us@MSAsafety.com

Design Center:
Latchways plc
Hopton Park, Devizes
Wiltshire, SN10 2JP, England
Phone +44 (0)1380 732700
info@latchways.com