

30-ft & 50-ft Sealed Self-Retracting Lanyards (SRLs)

30-ft and 50-ft Cable Self-Retracting Lanyards

Snaphooks and carabiners are marked with the ANSI Z359.12-09 standard, and are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating (consistent with ANSI Z359.12-09).

The sealed line of Latchways SRLs each have an ingress protection rating of IP 69K.

| Meets | Max Arrest Distance | Free Fall Limit | Max Arresting Force | Avg. Arresting Force | Max Capacity |
|---------------------------------|---------------------|--------------------|---------------------|----------------------|---------------------------|
| ANSI - CLASS B Z359.14-2012 | 54 in. (1372 mm) | 24 in. (610 mm) | 1800 lbs (8 kN) | 900 lbs (4 kN) | 30-310 lbs (59-141 kg) |
| CSA - TYPE 2 Z259.2.2-98 | 55 in. (1.4 m) | 24 in. (0.6 m) | 1800 lbs (8 kN) | N/A | 310 lbs (141 kg) |
| OSHA 29 CFR 1910.66/1926.502 | 42 in. (1067 mm) | 24 in. (610mm) | 1800 lbs (8 kN) | N/A | 310 lbs (141 kg) |

| | 62810-00US (30 ft) | 62816-00US (50 ft) |
|--------------------|--|--|
| LANYARD MATERIAL | 3/16 in (7x19) Grade 316 Stainless Steel Cable | 3/16 in (7x19) Grade 316 Stainless Steel Cable |
| HOUSING MATERIAL | Aluminum | Aluminum |
| LANYARD CONNECTION | Stainless Steel Indicating Swivel Snaphook | Stainless Steel Indicating Swivel Snaphook |
| (A) | 17 1/4 in (438 mm) | 18 1/4 in (438 mm) |
| (B) | 9 1/2 in (243 mm) | 11 in (243 mm) |
| DEPTH | 7 1/2 in (195 mm) | 8 1/4 in (195 mm) |
| WIDTH | 21.6 lb (9.8 kg) | 27.7 lb (12.6 kg) |



62810-00US (30 ft)



62816-00US (50 ft)

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products. Specifications subject to change without notice.



MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAafety.com

U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone 01 800 672 7222
Fax 52 - 44 2227 3943