

85-ft and 130-ft Sealed Self-Retracting Lanyards (SRLs)

85-ft and 130-ft Cable Self-Retracting Lanyards

Snaphooks and carabiners are marked with the ANSI Z359.12-09 standard, and are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating (consistent with ANSI Z359.12-09).

The sealed line of Latchways SRLs each have an ingress protection rating of IP 69K.

Meets	Max Arrest Distance	Free Fall Limit	Max Arresting Force	Avg. Arresting Force	Max Capacity
ANSI - CLASS B Z359.14-2012	54 in. (1372 mm)	24 in. (610 mm)	1800 lbs (8 kN)	900 lbs (4 kN)	30-310 lbs (59-141 kg)
CSA - TYPE 2 Z259.2.2-98	55 in. (1.4 m)	24 in. (0.6 m)	1800 lbs (8 kN)	N/A	310 lbs (141 kg)
OSHA 29 CFR 1910.66/1926.502	42 in. (1067 mm)	24 in. (610mm)	1800 lbs (8 kN)	N/A	310 lbs (141 kg)

	62826-00US (85 ft)	62841-00US (130 ft)
LANYARD MATERIAL	3/16 in (7x19) Grade 316 Stainless Steel Cable	3/16 in (7x19) Grade 316 Stainless Steel Cable
HOUSING MATERIAL	Aluminum/Stainless Steel	Aluminum/Stainless Steel
LANYARD CONNECTION	Stainless Steel Indicating Swivel Snaphook	Stainless Steel Indicating Swivel Snaphook
(A)	19 1/2 in (495 mm)	21 in (533 mm)
(B)	12 3/4 in (323 mm)	14 3/4 in (368 mm)
DEPTH	8 1/4 in (206 mm)	8 1/2 in (218 mm)
WIDTH	48.3 lb (21.9 kg)	62 lb (28.1 kg)



62826-00US (85 ft)



62841-00US (130 ft)

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products. Specifications subject to change without notice.



MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAafety.com

U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398

MSA Mexico
Phone 01 800 672 7222
Fax 52 - 44 2227 3943