



# MSA Latchways® Sealed Self-Retracting Lifelines



## **For peace of mind that matters.**

Manufactured to confirm material compatibility and durability, each of our individual components undergoes strict quality-control procedures prior to assembly, including critical component batch x-ray to ensure product integrity.

## **KEY FEATURES**

### **For advanced technology in action**

Traditional SRLs rely on friction braking systems that require re-tension, whereas MSA Latchways' smarter energy absorption is frictionless. The MSA Latchways Sealed SRL utilizes our patented Constant Force® energy absorption to ensure consistent performance, so it won't go out of adjustment like other SRLs.

For protection that doesn't waiver Our Full Contact® pawl locking mechanism provides locking that won't freeze, hang up or corrode. It also contains a built-in reserve line to ensure that a fall is arrested safely even when the cable is at its full limit.

For superior ingress protection To ensure the spring, locking mechanism and absorber are completely impenetrable to material/moisture ingress, the internal critical components are protected by rubber seals. IP69K rated.

## Latchways Standard SRL Range

Model	Line Type	Length	Size L x W x D	Weight	Anchorage
62810-00UK	Ø 5 mm stainless steel cable (7 x 19)	(9 m)	270 x 241 x 178 mm	9.5 kg	Forged/stainless steel snaphook
62816-00UK	Ø 5 mm stainless steel cable (7 x 19)	(15 m)	330 x 279 x 191 mm	12 kg	Forged/stainless steel snaphook
62826-00UK	Ø 5 mm stainless steel cable (7 x 19)	(26 m)	330 x 330 x 200 mm	20 kg	Forged/stainless steel snaphook
62841-00UK	Ø 5 mm stainless steel cable (7 x 19)	(40 m)	381 x 381 x 216 mm	26 kg	Forged/stainless steel snaphook

Latchways Sealed SRLs are also available with galvanized cable and hook assemblies. Please contact MSA for further information.