

V-TEC™ Mini PFL Range



	V-TEC Mini PFL (Single-Leg)						V-TEC Mini PFL (Twin-Leg)					
PRODUCT	V-TEC Mini PFL (Single-Leg)						V-TEC Mini PFL (Twin-Leg)					
PART NUMBER	63011-00A	63011-00B	63011-00C	63011-00D	63011-00E	63011-00F	63111-00A	63111-00B	63111-00C	63111-00D	63111-00E	63111-00F
LENGTH	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)	6 ft. (1.8 m)
ANCHORAGE CONNECTION	AL36CL	36C	Aluminum Swivel Carabiner	Aluminum Carabiner	36CS	36CL	AL36CL (2)	36C (2)	Aluminum Swivel Carabiner (2)	Triple-lock Carabiner (2)	36CS (2)	36CL (2)
HARNES CONNECTION	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Twin-Link Connector	Twin-Link Connector	Twin-Link Connector	Twin-Link Connector	Twin-Link Connector	Twin-Link Connector
PRODUCT WEIGHT	2.8 lbs. (1.3 kg)	2.0 lbs. (0.9 kg)	1.8 lbs. (0.8 kg)	1.7 lbs. (0.8 kg)	2.5 lbs. (1.1 kg)	3.0 lbs. (1.4 kg)	5.7 lbs. (2.6 kg)	4.0 lbs. (1.8 kg)	3.6 lbs. (1.6 kg)	3.4 lbs. (1.5 kg)	5.0 lbs. (2.3 kg)	6.0 lbs. (2.7 kg)
STANDARDS	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2	ANSI Z359.14 (Class B); CSA Z259.2.2
WEIGHT CAPACITY	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)

	V-TEC Tie-back Mini PFL		Latchways WEB PFL (10 ft. / 3 m)				Latchways CABLE PFL (10 ft. / 3 m)		Latchways Arc Flash Mini PFL (Single-Leg)
PRODUCT	V-TEC Tie-back Mini PFL		Latchways WEB PFL (10 ft. / 3 m)				Latchways CABLE PFL (10 ft. / 3 m)		Latchways Arc Flash Mini PFL (Single-Leg)
PART NUMBER	63041-00A	63141-00A	63013-00A	63013-00C	63013-00E	63013-00F	63203-00A	63203-00B	63032-00N
LENGTH	9 ft. (2.7 m)	9 ft. (2.7 m)	10 ft. (3.0 m)	10 ft. (3.0 m)	10 ft. (3.0 m)	10 ft. (3.0 m)	10 ft. (3.0 m)	10 ft. (3.0 m)	6.5 ft. (2 m)
ANCHORAGE CONNECTION	FP5K	FP5K (2)	AL36CL	Aluminum Swivel Carabiner	36CS	36CL	36CS	36CL	Carabiner (2)
HARNES CONNECTION	Steel Carabiner	Twin-Link Connector	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner	Steel Carabiner
PRODUCT WEIGHT	1.9 lbs. (0.9 kg)	3.8 lbs. (1.7 kg)	3.6 lbs. (1.6 kg)	2.6 lbs. (1.2 kg)	3.3 lbs. (1.5 kg)	3.8 lbs. (1.7 kg)	4.9 lbs. (2.2 kg)	5.2 lbs. (2.4 kg)	2.4 lbs. (1.1 kg)
STANDARDS	OSHA	OSHA	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B)	ANSI Z359.14 (Class B), ASTM F887
WEIGHT CAPACITY	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)	400 lbs. (181 kg)

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
 1000 Cranberry Woods Drive
 Cranberry Township, PA 16066 USA
 Phone 724-776-8600
www.MSAsafety.com
U.S. Customer Service Center
 Phone 1-800-MSA-2222
 Fax 1-800-967-0398
MSA Canada
 Phone 1-800-672-2222
 Fax 1-800-967-0398
MSA Mexico
 Phone 01 800 672 7222

ID 4600-062-MC / November 2017
 © MSA 2017 Printed in U.S.A.

WE KNOW WHAT'S AT STAKE.