

# ALTAIR® 4X Multigas Detector (MSHA)

Assemble-To-Order System



## Approvals/Replacement Parts/Kits

ALTAIR 4X Multigas Detector with North American approval, quick-start card, data logging, charger, calibration cap, tubing, and CD manual. MotionAlert feature is now included as standard on all detectors.

### Ordering Information

DESCRIPTION	Part No.
ALTAIR 4X MULTIGAS DETECTOR (CH <sub>4</sub> , O <sub>2</sub> , CO) Charcoal	10125912
ALTAIR 4X MULTIGAS DETECTOR (CH <sub>4</sub> , O <sub>2</sub> , CO) Phosphorescent	10125913
ALTAIR 4X MULTIGAS DETECTOR (CH <sub>4</sub> , O <sub>2</sub> , CO, NO <sub>2</sub> ) Charcoal	10125914
ALTAIR 4X MULTIGAS DETECTOR (CH <sub>4</sub> , O <sub>2</sub> , CO, NO <sub>2</sub> ) Phosphorescent	10125915

CALIBRATION ACCESSORIES	Part No.
CALIBRATION ASSEMBLY (cap, tube, connector)	10089321
REGULATOR 0.25 LPM MODEL RP	467895
34L CALIBRATION CYLINDER MIX (2.5% CH <sub>4</sub> , 15% O <sub>2</sub> , 60 PPM CO)	10049056
34L CALIBRATION CYLINDER MIX (2.5% CH <sub>4</sub> , 15% O <sub>2</sub> , 60 PPM CO, 10 PPM, NO <sub>2</sub> )	10058172
58L CALIBRATION CYLINDER MIX (2.5% CH <sub>4</sub> , 15% O <sub>2</sub> , 60 PPM CO, 10 PPM, NO <sub>2</sub> )	10058171

POWER SUPPLY	Part No.
CHARGING CRADLE COMPONENTS	10086639
NORTH AMERICAN POWER SUPPLY	10087913
CHARGING CRADLE ASSEMBLY	10092233
VEHICLE CHARGER	10095774
4-UNIT MULTI-UNIT CHARGER NA PLUG	10127422
12-UNIT MULTI-UNIT CHARGER NA PLUG	10143372

ACCESSORIES	Part No.
STAINLESS STEEL SUSPENDER CLIP	10069894
MSA LINK™ SOFTWARE CD-ROM	10088099
JetEye IR ADAPTER WITH USB CONNECTOR	10082834

SENSOR / SPARE PARTS	Part No.
KIT, XCell EX-M COMBUSTIBLE SENSOR	10121212
KIT, XCell O <sub>2</sub> SENSOR	10106729
KIT, XCell CO/H <sub>2</sub> S TWO-TOX SENSOR	10106725
KIT, XCell CO/NO <sub>2</sub> TWO-TOX SENSOR	10121217
FRONT HOUSING WITH INTEGRATED DUST FILTERS (CHARCOAL)	10110030
FRONT HOUSING WITH INTEGRATED DUST FILTERS (PHOSPHORESCENT)	10110029
MAIN BOARD WITH BATTERY PACK	10124956
LCD FRAME ASSEMBLY (frame, LCD, zebra strips, screws)	10110061
SENSOR GASKET, PHILLIPS SCREWS (4X), SELF-TAPPING (2X)	10110062
CD MANUAL, ALTAIR 4X MULTIGAS DETECTOR	10106623

GALAXY GX2 AUTOMATED TEST SYSTEM	Part No.
TEST STAND W/ NA POWER SUPPLY	10128630
ELECTRONIC CYLINDER HOLDER	10105756
SD MEMORY CARD	10127111
END CAP	10125907

**Note:** This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



**MSA – The Safety Company**  
1000 Cranberry Woods Drive  
Cranberry Township, PA 16066 USA  
Phone 724-776-8600  
[www.MSAsafety.com](http://www.MSAsafety.com)  
**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398

**MSA Canada**  
Phone 1-800-672-2222  
Fax 1-800-967-0398  
**MSA Mexico**  
Phone 01-800-672-7222  
Fax 52-44 2227 3943



### ALTAIR 4X Detector (MSHA) with MSA XCell® Sensors offers:

- 4-year life.
- 3-year instrument warranty.
- Lower maintenance cost.
- Reduced required calibration gas.
- Response and clear times in less than 15 seconds.
- Improved repeatability and accuracy.
- End-of-sensor-life warning for planned sensor replacement, reducing instrument down time.
- GALAXY® System compatibility for powerful calibration and fleet management.
- MotionAlert™ feature activation when no movement is detected for 30 seconds, indicating "man down".
- InstantAlert™ feature manually-activated alarm to alert others of hazardous situations.
- MSA Link™ Software compatibility for easy data management and configuration through your PC.
- Bump test mode for clear indication of bump test status and long-term record storage.
- Approval agency-certified IP67 rating, dust and water resistance.
- 30+ hour run time for continuous operation over three shifts.
- Ergonomic design for comfort and easy operation even with gloved hands.



### ALTAIR 4X Multigas Detector (MSHA) Assemble-To-Order (ATO) Options

To create your instrument configuration, select the instrument option code and mark them in the boxes to the right.

<b>A</b>	<b>INSTRUMENT TYPE</b>	The ALTAIR 4X Multigas Detector now comes standard with MSA's new XCell Sensors and MotionAlert feature to indicate "man down". Please select your instrument's case color; select option <b>C</b> for charcoal and option <b>G</b> for phosphorescent (glow-in-the-dark).	<table border="1"> <thead> <tr> <th>Instrument Type</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Charcoal</td> <td>C</td> </tr> <tr> <td>Phosphorescent (glow-in-the-dark)</td> <td>G</td> </tr> </tbody> </table>	Instrument Type	Code	Charcoal	C	Phosphorescent (glow-in-the-dark)	G	Selection								
Instrument Type	Code																	
Charcoal	C																	
Phosphorescent (glow-in-the-dark)	G																	
<b>B</b>	<b>COMBUSTIBLE SENSOR</b>	To have a combustible sensor installed in your new ALTAIR 4X Multigas Detector, please select <b>C</b> . For no combustible sensor, please select <b>0</b> .	<table border="1"> <thead> <tr> <th>Combustible Sensor Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>0</td> </tr> <tr> <td>0-5% Vol methane</td> <td>C</td> </tr> </tbody> </table>	Combustible Sensor Options	Code	None	0	0-5% Vol methane	C	Selection								
Combustible Sensor Options	Code																	
None	0																	
0-5% Vol methane	C																	
<b>C</b>	<b>OXYGEN SENSOR</b>	To have an oxygen sensor installed in your new ALTAIR 4X Multigas Detector, please select <b>1</b> . For no sensor, enter <b>0</b> .	<table border="1"> <thead> <tr> <th>Oxygen Sensor Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>0</td> </tr> <tr> <td>0-30% Vol</td> <td>1</td> </tr> </tbody> </table>	Oxygen Sensor Options	Code	None	0	0-30% Vol	1	Selection								
Oxygen Sensor Options	Code																	
None	0																	
0-30% Vol	1																	
<b>D</b>	<b>TOXIC SENSOR</b>	To configure your new ALTAIR 4X Multigas Detector, choose <b>0</b> for no toxic sensor. Choose <b>A</b> for both CO and H <sub>2</sub> S sensors, choose <b>B</b> for CO, <b>C</b> for H <sub>2</sub> S, <b>D</b> for CO and NO <sub>2</sub> , and <b>E</b> for NO <sub>2</sub> .	<table border="1"> <thead> <tr> <th>Toxic Sensor Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>0</td> </tr> <tr> <td>0-1999 ppm CO and 0-200 ppm H<sub>2</sub>S</td> <td>A</td> </tr> <tr> <td>0-1999 ppm CO</td> <td>B</td> </tr> <tr> <td>0-200 ppm H<sub>2</sub>S</td> <td>C</td> </tr> <tr> <td>0-1999 ppm CO and 0-50 ppm NO<sub>2</sub></td> <td>D</td> </tr> <tr> <td>0-50 ppm NO<sub>2</sub></td> <td>E</td> </tr> </tbody> </table>	Toxic Sensor Options	Code	None	0	0-1999 ppm CO and 0-200 ppm H <sub>2</sub> S	A	0-1999 ppm CO	B	0-200 ppm H <sub>2</sub> S	C	0-1999 ppm CO and 0-50 ppm NO <sub>2</sub>	D	0-50 ppm NO <sub>2</sub>	E	Selection
Toxic Sensor Options	Code																	
None	0																	
0-1999 ppm CO and 0-200 ppm H <sub>2</sub> S	A																	
0-1999 ppm CO	B																	
0-200 ppm H <sub>2</sub> S	C																	
0-1999 ppm CO and 0-50 ppm NO <sub>2</sub>	D																	
0-50 ppm NO <sub>2</sub>	E																	
<b>E</b>	<b>POWER SUPPLY</b>	Select the correct power supply for your region. Add an instrument cradle to firmly secure your instrument while charging on the shelf or in a vehicle.	<table border="1"> <thead> <tr> <th>Power Supply Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>None</td> <td>0</td> </tr> <tr> <td>North American</td> <td>N</td> </tr> <tr> <td>North American with cradle</td> <td>M</td> </tr> </tbody> </table>	Power Supply Options	Code	None	0	North American	N	North American with cradle	M	Selection						
Power Supply Options	Code																	
None	0																	
North American	N																	
North American with cradle	M																	
<b>F</b>	<b>APPROVAL LABEL</b>	The ALTAIR 4X Multigas Detector is fully approved by MSHA.	<table border="1"> <thead> <tr> <th>Approval Label Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>MSHA</td> <td>M</td> </tr> </tbody> </table>	Approval Label Options	Code	MSHA	M	Selection M										
Approval Label Options	Code																	
MSHA	M																	
<b>G</b>	<b>EXTENDED WARRANTY</b>	MSA includes a full 3-year warranty on the ALTAIR 4X Multigas Detector, including sensors, battery and electronics. Choose <b>1</b> for an additional year (4 years total).	<table border="1"> <thead> <tr> <th>Extended Warranty Options</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>3 years standard warranty</td> <td>0</td> </tr> <tr> <td>Extended warranty (4 years total)</td> <td>1</td> </tr> </tbody> </table>	Extended Warranty Options	Code	3 years standard warranty	0	Extended warranty (4 years total)	1	Selection								
Extended Warranty Options	Code																	
3 years standard warranty	0																	
Extended warranty (4 years total)	1																	

#### Your Model Part Number

Please write in numbers from selections above in appropriate boxes and contact your safety products distributor to place your order.

Selection      A      B      C      D      E      F      G

A-ALT4XM-