

our direct cont

ibioct to ch

Subject to change without notice

MSA EUROPE Regional Head Offices & Great Britain [www.msa-europe.com]

Northern Europe

MSA Nederland B.V., Hoorn Phone: +31 [229] 25 03 03

E-Mail: info@msaned.nl

Central Europe

MSA AUER GmbH, Berlin Phone: +49[30]6886-0

E-Mail: info@auer.de

Eastern Europe

MSA AUER GmbH, Berlin Phone: +49[30]6886-2599

☐ E-Mail: mee@auer.de

ID 01-181.8 ITL/03/01.07/pdf

Southern Europe

MSA Italiana S.p.A., Rozzano Phone: +39 [02] 89 217-1

E-Mail: info-italy@msa-europe.com

International Sales

MSA EUROPE, Berlin

Phone: +49 [30] 68 86-555 E-Mail: contact@msa-europe.com

Great Britain

MSA Britain, Coatbridge

Phone: +44 [12 36] 42 49 66 E-Mail: info@msabritain.co.uk







MSA is one of the world-wide leading providers of personal equipment and gas detection. Especially the safety products for fire services like the alpha next generation breathing apparatus and personal network set standards in respiratory protection.

To complete the versatility of fire service safety products MSA offers the RespiHood. This rescue hood is designed for rescuing people from hazardous areas.

Features

- Rescue hood with constant airflow
- Flame-retardant hood with anti-fog visor
- Approved according to PPE-Directive 89/686/EEC [using tests from EN 1146]
- Available with European standard or "Staeubli"type medium pressure connection
- Stored in a flame retardant and water-tight pouch



Function

The rescue worker places the hood over the head of the person to be rescued. After tightening the neckband slightly, air is supplied by the second connection on the rescue worker's self contained breathing apparatus. A constant airflow of about 50 l/min is provided with a medium pressure of 7 bar from the feed line.




RespiHood is made from signal yellow flameretardant material ideally suited for rescue work. A large anti-fog coated visor provides a large field of vision and therefore helps to prevent panic.



alpha SingleLite
The manifold at the head of the
alpha SL line integrates the
second connection as a standard



AirMaXX®-Z
The optional second connection
for rescue applications



Storage

RespiHood is stored in a water-tight pouch that attaches to e.g. the hip belt of the SCBA. It comes in two versions. The standard version with common European medium pressure couplings and RespiHood F with a nipple for "Staeubli" type couplings.

Ordering Information

10045764 RespiHood

10045765 RespiHood F [with Staeubli coupling]

