



The Safety Company

Mine Safety Appliances Company • 1000 Cranberry Woods Dr. • Cranberry Twp. PA 16066

Chillgard® LS Monitor – ATO Order Form

A-LS	—	—	—	—	—	—	—	—	—	—	—	—
	1	2	3	4	5	6	7	8	9	10	11	12

1 Gas Type

A = R123
B = R11
C = R22
D = R134A
F = R12
G = R404A
H = R407C
J = R410A
K = R507
L = R-1234YF

Consult factory for custom gas

2 Sample Points

1 = Single Point
* 4 = Four Point

3 Sampling System

0 = None
* 1 = Pump (Matrix code 2 must = 4)

4 Range of Analysis

0 = 0-1000 ppm

5 Alarm Options

0 = None
1 = Beacon

6 Filter Selections

0 = None
1 = Standard Filter
Not required with Diffusion Units

7 Quantity of Filters

Must be "0" if Matrix Code 6 = 0
Maximum quantity = 4



8 Model Type

0 = Standard

9 Power Supply

0 = 24 VAC/DC (Standard)
1 = 110/220 supply (50 – 60 Hz)

10 Enclosure

0 = Plastic

11 Approval Option

2 = cULus

12 Custom Features

2 = Standard

* Requires Chillgard LC