

GENERAL MONITORS FL500 UV/IR FLAME DETECTOR

A B C D E F G H

FL500 - 3 - 5 - 1 - 2 - 1 - 1 - 1 - 1

FL500 FLAME DETECTOR: (Std) UV/IR FLAME DETECTOR

A. ALARM-OUTPUT:

- 1- 4-20 mA SOURCE CURRENT, RELAYS, SINGLE MODBUS, HART off
- 2- 4-20 mA SINK CURRENT, RELAYS, SINGLE MODBUS, HART off
- 3- (Std) 3.5 mA HART, SOURCE CURRENT, RELAYS, SINGLE MODBUS
- 4- 3.5 mA HART, SINK CURRENT, RELAYS, SINGLE MODBUS
- 5- 1.25 mA HART, SOURCE CURRENT, RELAYS, SINGLE MODBUS
- 6- 1.25 mA HART, SINK CURRENT, RELAYS, SINGLE MODBUS

B. RELAY-STATE-NC:

- 1- LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 2- LATCH ALARM/NON-LATCH WARN ENERGIZED
- 3- LATCH ALARM/LATCH WARN DE-ENERGIZED
- 4- LATCH ALARM/LATCH WARN ENERGIZED
- 5- (Std) NON-LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
- 6- NON-LATCH ALARM/NON-LATCH WARN ENERGIZED
- 7- NON-LATCH ALARM/LATCH WARN DE-ENERGIZED
- 8- NON-LATCH ALARM/LATCH WARN ENERGIZED

C. SENSITIVITY:

- 1- (Std) HIGH SENSITIVITY
- 2- MEDIUM SENSITIVITY
- 3- LOW SENSITIVITY

D. TIME-DELAY:

- 1- 2 SECOND DELAY
- 2- (Std) 4 SECOND DELAY
- 3- 8 SECOND DELAY
- 4- 10 SECOND DELAY

E. HOUSING:

- 1- (Std) Stainless steel

F. APPROVALS:

- 1- (Std) FM/CSA/ATEX/IECEX

G. CABLE ENTRY:

- 1- (Std) 2x 3/4" NPT
- 2- 2x 25mm

H. MOUNTING BRACKET

- 0- Without bracket
- 1- (Std) With bracket (p/n 71370-1)

