

FeatherFit Spectacle

Technical Datasheet



Features

- Modern spectacle for entry level
- Soft temple tips and nose pad for cushion fit
- Snug fit wrap around lens for perfect vision & protection
- Weighs only 20 g
- TuffStuff anti-scratch coating according to EN 166 "K"
- Great price/performance ratio
- Lens colours for indoor & outdoor applications: clear, smoke



Technical Specifications

General	
Weight	20 g
Temple length	152 mm
Overall width	132.7 mm
Lens thickness	2.4 mm
Lens base	9.5 curve
Lens size	39.8 mm vertical, 76.1 mm diagonal
Material & Colours	
Lens	Polycarbonate Colours: clear, smoke Coating: TuffStuff anti-scratch
Temple	Polycarbonate & PVC Smoke: smoke with green temple end Clear: transparent with green temple end
Sleeve	Nylon
Nose piece	Bridge – Polycarbonate Nosepad – TPR
Hinge	Polycarbonate
Screw	Stainless steel
Markings / Approvals	
Standard number	EN 166
Frame marking	MSA EN 166-FT CE
Lens marking	Clear: 2C-1.2 MSA 1 FT K CE Smoke: 5-2.5 MSA 1 FT K CE
Filter class	2C (Ultra violet radiation with enhanced colour recognition) 5 (Adequate protection against sun glare)
Scale number	1.2; Luminous transmittance ~89% 2.5; Luminous transmittance ~21%
Optical class	1 (best class, for permanent wear)
Mechanical resistance	F (low energy impact 45 m/s) T (at extreme temperatures -5...+55°C)
Resistance to	K (surface damage by fine particles)
UV filter	99,9%

Ordering Information	
10145075	FeatherFit, Clear, TuffStuff, 12x
10145076	FeatherFit, Smoke, TuffStuff, 12x
Packaging	
Individual	1 pc in polybag with manual and EAN code39 as barcode
Box <i>MSA selling unit</i>	12 pcs with EAN code13 as barcode
Shipping carton	contains 12 boxes, with an EAN code128 as barcode

MSA Europe
Thiemannstrasse 1
DE-12059 Berlin
Phone +49 (0)30 68 86-0
Fax +49 (0)30 68 86-15 17
Email info.de@MSAsafety.com

Subject to change without notice. Rev00, 01.2013