GALAXY GX2 System Ordering Information

	GALAXY GX2 System Test Stand (with Australian Plug)			
	1 Valve (for use with 1 calibration gas cylinder)		4 Valve (for use with 1-4 calibration gas cylinders)	
	Charging*	No-Charging	Charging*	No-Charging
ALTAIR / ALTAIR PRO	/	10128673	/	10128672
ALTAIR 4/4X	10128669	10128671	10128668	10128670
ALTAIR 5/5X	10128665	10128667	10128664	10128666

* Please contact your local MSA affiliate regarding availability.

The GALAXY GX2 System test stand comes with pre-configured plugs, barbs, fresh air filter, power supply with corresponding plug, spare parts kit (gas tubing, barbs and plugs), Ethernet cable (short cable for connection between test stands), DIN rail clip kit, and screen protector. Please see ordering information below for further system components, including electronic cylinder holder (includes regulator) or non-electronic cylinder holder (without regulator), MSA Link Pro Software, digital secure USB key, end cap, and multi-unit charger.

Accessories

Part Number	Description
10105756	Electronic cylinder holder
10125135	Non-electronic cylinder holder
10127111	4 GB SD card
10123938	MSA Link Pro Software key (red)
10123937	Digital secure USB key (black)
10125907	End cap
10127423	ALTAIR 4/4X multi-unit charger
10127428	ALTAIR 5/5X multi-unit charger
10127808	Sticker or receipt / sticker printer
10126437	Detector sticker label roll (2800 labels/roll)
10126138	Receipt & sticker label roll (375 labels/roll)
10127518	12" (TBR) Ethernet cable for test stand to test stand connection
10126657	DIN rail clip kit (2 clips & screws per kit)
10062364	Type Omega DIN Rail 0.5m, perforated, steel, zinc-plated
10062365	Type Omega DIN Rail 1m, perforated, steel, zinc-plated
10062366	Type Omega DIN Rail 2m, perforated, steel, zinc-plated
10082834	USB IR dongle (for use with MSA Link Software)
10034391	Demand flow regulator (universal)
10126268	Vehicle power adapter

Calibration Gas

Part Number	Description
10048280	Calibration gas cylinder (34L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S
10045035	Calibration gas cylinder (58L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S
10117738	Calibration gas cylinder (58L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 10 ppm SO_2
10098855	Calibration gas cylinder (34L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 10 ppm SO_2
10103262	Calibration gas cylinder (58L) 1.45% CH_4, 15% O_2, 60 ppm CO, 20 ppm H_2S, 2.5% CO_2

Technical Specifications

Operating Temperature	GALAXY GX2 System	0-40˚C
Power Input	Power module	100-240 VAC, 47-63 Hz
	Optional vehicle module	9-32 VDC
Physical Characteristics	Test stand	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 7.90" (200.66 mm)
		Material: acrylonitrile butadiene ABS
	Cylinder holder	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 6.10" (154.94 mm)
		Material: acrylonitrile butadiene ABS
	Multi-unit charger	Height: 11.80" (299.72 mm)
		Width: 6.50" (165.10 mm)
		Depth: 6.44" (163.58 mm)
		Material: acrylonitrile butadiene ABS

Your direct contact

MSA Australia – Head Office
MSA (Aust.) Pty. Limited
137 Gilba Road
Girraween NSW 2146
Australia
Phone Toll Free: 1300 728 672
Fax (02) 9896 3224
aus.customerservice@MSAnet.com

MSA Australia – Perth Office
MSA (Aust.) Pty. Limited
4 Iron Road
Malaga WA 6090
Australia
Phone (08) 9247 8900
Fax (08) 9248 3287
perth.customerservice@MSAnet.com

MSA New Zealand
Unit B
707 Great South Road, Penrose
Auckland
New Zealand
Phone 0800 441 335
Fax 0800 441 329
nzcusserv@MSAnet.com

MSA International
1000 Cranberry Woods Drive
Cranberry Township, PA 16066
USA
Phone +1-724-776-8626
Fax +1-724-741-1559
msa.international@msanet.com

www.MSAsafety.com

Subject to change without notice
ID 08-531.2 GB-AU/00

MSA
The Safety Company

GALAXY®GX2 Automated Test System

SIMPLICITY COUNTS

MSA's New GALAXY GX2 Automated Test System /
Advanced Safety Management…
Effortless Operation



Advanced MSA Link Pro Software


Analyze All Data, Any Time


MSA Link Pro Software lets you easily and proactively manage your gas detection fleet. Program offers efficient setup and configuration with dashboard alerts as to all conditions, as well as calibration gas and expiration warnings. Query data, print or save reports including gas exposures incidents; system can be set up to automatically send email exposure alerts. Generate session logs, including periodic as well as calibration and GALAXY GX2 System bank data. Program sends scheduled emails from master test stand based upon detector conditions and events. Directly input your data and filter results live.


View test and exposure data, session and periodic logs at a glance. Dashboard displays live status of GALAXY System test stand banks.



Live filtering can be viewed, printed and saved as PDF document.







System offers direct data input, live filtering, test and exposure queries, and detailed reports.

Print and save detailed calibration, bump test and exposure reports.

MSA

SIMPLICITY COUNTS

The new **GALAXY GX2 Automated Test System** provides simple and intelligent testing and calibration of MSA ALTAIR® and ALTAIR PRO Single-Gas Detectors, as well as with ALTAIR 4X and ALTAIR 5X Multigas Detectors, driven by the most advanced technology available in any portable gas detector: MSA XCell® Sensors.

This easy-to-use automated test stand offers high performance as either a stand-alone unit or an integrated portable detector management system, enabling total data access and control of the MSA ALTAIR Gas Detector fleet.

Once any ALTAIR Family Gas Detector is placed within the GALAXY GX2 System, it can be tested, calibrated and charged* automatically. Flexibility allows for up to 10 test stations, four cylinder holders and multi-unit charger within one GALAXY GX2 System detector bank.



Ease of Use
Calibrate & Test Effortlessly

- Easy setup, simple use with touch-free testing.
- Color touch screen enhances user experience at the test stand.
- Can be used with a PC or as a stand-alone system, the perfect solution for large fleet end users, as well as for smaller applications.
- Automated test system and MSA Link™ Software (transfers portable gas detector records to a connected PC) provided as standard in many commonly spoken languages.
- Your ALTAIR 4X and ALTAIR 5X Multigas Detectors are always ready for use. If you're faced with an urgent, short-notice situation, these units are ready for deployment, ideal for emergency applications.*

Cost of Ownership
Save Time, Save Gas & Save Money

- Exceeds 50% reduction in cost of ownership, including calibration gas expenses when combined with high-performance MSA XCell Sensors.
- Faster total testing of ALTAIR Family Gas Detectors.0
- Test up to 10 gas detectors simultaneously in the time most competitive systems take to test one device.
- RFID-tagged calibration gas cylinders to help ensure use of correct gas.


Proactive Safety
Command, Control, Configure

- With MSA Link Pro Software, proactively manage safety by addressing gas exposure information and missing or failed calibrations and bump tests.
- Calibration gas and expiration warnings provided by the GALAXY GX2 System and via advanced MSA Link Pro Software.
- Print calibration stickers for gas detectors to provide easy and fast user information.
- Query the system for gas exposures, and then email responses to users.

* Please contact your local MSA affiliate regarding availability.

Color touch screen for ease of setup and viewing; no touch operation is needed to calibration or bump test

Clear and intuitive navigation via large touch buttons and scrolling arrows for scrolling. When test completes, users view results on test stand popup screen and detailed information on PC dashboard.






Visual indicators on GALAXY GX2 System and software

Status at-a-glance is provided through various light indicators: test stand pass/fail LED, charging progress LEDs on multi-unit charger and lighted cylinder band on electronic cylinder holder for low gas and expiration date warning display.

RFID automated calibration gas setup, status alerts and traceability

Gas cylinder information necessary for successful calibration is automatically entered when using RFID-tagged gas cylinders, providing users with exceptionally easy setup. Onscreen gas cylinder pressure gauge shows multiple cylinder status simultaneously.





MSA Link Pro and MSA Link Software

Redesigned software interface offers efficient setup; configure every detector's set points quickly and save settings. Overdue calibration and bump test email notifications are delivered via MSA Link Pro Software and an active network connection. Master test stand sends scheduled emails based upon detector conditions and events.



Global platform – Many language options

18 languages are available to serve customers globally. Easily change languages via onscreen menu. Languages chosen other than English are those most widely spoken.



Significant cost of ownership reduction

System offers more than 50% reduction in cost of ownership including calibration gas expenses when used with high-performance MSA XCell Sensors, resulting in faster total testing of ALTAIR Family Gas Detectors.


Simultaneous testing of up to 10 gas detectors

Calibrate up to 10 gas detectors simultaneously in less time than it takes most competitive units to test one. Patented gas flow process increases pressure from demand flow regulator to deliver consist gas flow from one to 10 units. Connect up to 10 test stands and four cylinder holders to perform simultaneous tests.



Securely configure gas detectors at the touch of a button

The GALAXY GX2 Automated Test System allows users to configure many gas detector and cylinder settings at the test stand, settings that can be saved to a reusable file. Settings are stored on a digital-secure USB; no gas detector setting files are stored locally.



MSA XCell Sensor Technology

The GALAXY GX2 Automated Test System is optimized for use with MSA's high performance XCell Sensors. Sensors offer end-of-sensor-life warning, typical life greater than four years for combustible, O_2, CO/H_2S, and SO_2 sensors and greater than three years for NH_3 and Cl_2 sensors. Bump test in less than 15 seconds, span calibration time of 60 seconds and sensor response and clear times in less than 15 seconds for most common sensor configurations.

Your MSA multigas detectors are always ready for use

Your ALTAIR 4X and ALTAIR 5X Multigas Detectors are available to use immediately. If you're faced with an urgent, short-notice situation, these units are ready for deployment, ideal for emergency applications.*



THE MSA COMMITMENT. FROM THE LATEST IN SENSOR TECHNOLOGY TO INSTRUMENT DESIGN AND MANUFACTURING, MSA HAS THE CAPABILITIES AND EXPERTISE TO SUPPORT YOUR PORTABLE GAS DETECTION CHALLENGES.